



Labworks, LLC  
230 North 1200 E #202  
Lehi, UT 84043  
Phone: 844 452-2967  
[www.labworks.com](http://www.labworks.com)

---

## LABWORKS LIMS v7.1

---

### Database Dictionary

---

---

**Last Updated:** March 2022

---

## Table of Contents

|                       |    |
|-----------------------|----|
| ACTIONCODES.....      | 8  |
| ANALYSIS .....        | 8  |
| ANALYST_TEAM .....    | 10 |
| ANALYSTS .....        | 10 |
| ANALYTES .....        | 11 |
| ANALYTES_HIST.....    | 11 |
| ANL_LIST .....        | 12 |
| ANL_LIST_HIST.....    | 14 |
| ANL_MATRIX .....      | 14 |
| ANLOBJECT.....        | 15 |
| ANLSUBST.....         | 15 |
| ANLTESTS .....        | 16 |
| APPPRIVS.....         | 16 |
| AUDITTRAIL.....       | 16 |
| AUDTRAIL.....         | 17 |
| AUSERFLDS .....       | 17 |
| BATCHHEAD.....        | 18 |
| BATCHITEMSTOCKS ..... | 18 |
| BATCHSAMPS .....      | 19 |
| BATCHTEMPLATE.....    | 19 |
| BATHEAD .....         | 19 |
| BATSAMPS .....        | 20 |
| BMESSAGEQUEUE .....   | 20 |
| BMessageTypes .....   | 21 |
| BOTTLELIST .....      | 21 |
| CALCDEFS.....         | 21 |
| CALCPARAMS .....      | 22 |
| CBANLS.....           | 22 |
| CBCHARTANL.....       | 23 |
| CBCHARTHEAD.....      | 23 |
| CBHEADER .....        | 24 |
| CBPROMPT.....         | 25 |
| CBVARS .....          | 25 |
| CCHARTDATA .....      | 26 |
| CCHARTHEADER .....    | 26 |

|                                   |    |
|-----------------------------------|----|
| CCHARTSETUP .....                 | 26 |
| CIM_Actions.....                  | 27 |
| CIM_AnlMethods .....              | 27 |
| CIM_CAPAEffectChecks .....        | 27 |
| CIM_CAPAReports .....             | 28 |
| CIM_CAPARootCauses.....           | 29 |
| CIM_CAPAStepApprovers.....        | 29 |
| CIM_CollectionGroups.....         | 29 |
| CIM_CollectionGroupSamples .....  | 30 |
| CIM_InstMethods.....              | 30 |
| CIM_NotificationActions.....      | 31 |
| CIM_Notifications.....            | 31 |
| CIM_Project .....                 | 31 |
| CIM_ProjectUserFields .....       | 32 |
| CIM_SampleLog .....               | 32 |
| CIM_Schedule .....                | 32 |
| CIM_ScheduleAction .....          | 33 |
| CIM_ScheduledPrograms.....        | 33 |
| CIM_ScheduleRecipientGroup .....  | 33 |
| CIM_ScheduleRecipientUser.....    | 34 |
| CIM_Settings .....                | 34 |
| CInv_Analysis .....               | 34 |
| CInv_Certifications.....          | 35 |
| CInv_ItemAttachments .....        | 35 |
| CInv_ItemMixtureInst.....         | 35 |
| CInv_ItemMixtureMaster.....       | 36 |
| CInv_Items.....                   | 36 |
| CInv_ItemsSafteyInformation ..... | 37 |
| CInv_ItemStock.....               | 38 |
| CInv_ItemStockMixture.....        | 39 |
| CInv_ItemStockMixtureInst.....    | 39 |
| CInv_ItemSuppliers .....          | 39 |
| CInv_KitItems.....                | 40 |
| CInv_Kits.....                    | 40 |
| CInv_Picklists.....               | 40 |
| CInv_PurchaseReq.....             | 41 |
| CInv_PurchaseReqDet.....          | 41 |

|                              |    |
|------------------------------|----|
| CInv_ReceiptItemPrice .....  | 42 |
| CInv_Sample .....            | 42 |
| CInv_StorageLocations .....  | 43 |
| CInv_Suppliers.....          | 43 |
| CInv_TestConfig .....        | 44 |
| CInv_TestConfigDetails ..... | 44 |
| CInv_Transaction.....        | 44 |
| CInv_TransactionItems.....   | 45 |
| CMDP_EXPORT_LOOKUP .....     | 45 |
| COAANLS.....                 | 45 |
| COAHEAD .....                | 46 |
| COMMENTS .....               | 47 |
| COMPONENT.....               | 48 |
| CONTAINER_ANALYSIS .....     | 48 |
| CONTAINER_HEADER.....        | 48 |
| CONTAINER_HISTORY.....       | 49 |
| DATASTORE .....              | 50 |
| DCL_ChartPoints.....         | 50 |
| DCL_Charts .....             | 51 |
| DCL_Template.....            | 51 |
| DCL_TemplLimit .....         | 52 |
| DCL_TemplPoints.....         | 52 |
| DE_HISTORY .....             | 53 |
| DE_SETUP .....               | 53 |
| DE_TRANSITION .....          | 54 |
| DLCOMMENTS .....             | 55 |
| DOCREFERENCE .....           | 55 |
| DV_NARRATIVE_STATUS .....    | 55 |
| DV_NARRATIVE_VALUES .....    | 56 |
| ERDETAIL .....               | 56 |
| ERHEADER .....               | 56 |
| ErrorLog .....               | 57 |
| EWORKSHEETDATA.....          | 57 |
| EWRKSHEETSAMPS .....         | 58 |
| FileObjMgmt.....             | 58 |
| GROUPHEADER.....             | 59 |
| GROUPMEMBERS .....           | 59 |

|                         |    |
|-------------------------|----|
| GROUPPARAMS .....       | 59 |
| GROUPSIPROMPTS .....    | 60 |
| HOLIDAYS.....           | 60 |
| I18NApplications .....  | 60 |
| I18NAppModules .....    | 61 |
| I18NLanguages .....     | 61 |
| I18NListStrings.....    | 61 |
| I18NLocalStrings .....  | 62 |
| I18NModStrings .....    | 62 |
| I18NSourceModules ..... | 62 |
| I18NStrings .....       | 63 |
| IMCINSTCALI .....       | 63 |
| IMCINSTMAINT .....      | 63 |
| IMCPROCS.....           | 64 |
| INSTLIST .....          | 64 |
| INSTTESTS .....         | 65 |
| INVCOMMENTS.....        | 65 |
| INVDETAIL .....         | 66 |
| INVHEAD .....           | 66 |
| INVSPECINFO.....        | 67 |
| INVUSRFLDS .....        | 68 |
| IPP_ACTION.....         | 68 |
| IPP_PERMIT.....         | 68 |
| IPP2LWANLS .....        | 69 |
| IPPLIMITS.....          | 70 |
| IPPMUNI .....           | 70 |
| IPPSAMPFREQ.....        | 71 |
| IPPSTATUS .....         | 71 |
| IPPVIOLS.....           | 72 |
| LABOBJCOMMENTS .....    | 72 |
| LABOBJMAILLIST .....    | 72 |
| LABOBJOBJECTS .....     | 73 |
| LABOBJSPECINFO.....     | 74 |
| LICENSEKEYINFO.....     | 74 |
| LOCLIST .....           | 74 |
| LOCTESTS .....          | 76 |
| LWObjects .....         | 76 |

|                            |    |
|----------------------------|----|
| MDLCALCHEADER.....         | 77 |
| MDLCALCSETUP.....          | 77 |
| MDLCHARTDATA .....         | 78 |
| MESSAGEQUEUE .....         | 78 |
| MLADDRESSES.....           | 79 |
| MORDETAIL.....             | 80 |
| MORHEADER.....             | 80 |
| NTRLTS.....                | 81 |
| NTTEXT.....                | 82 |
| OGROUPS.....               | 82 |
| OGRPMEMBS .....            | 82 |
| OGRPPERMIT.....            | 83 |
| OLDMESSAGEQUEUE .....      | 83 |
| PASSHISTORY .....          | 84 |
| PICKLISTS.....             | 84 |
| PRIVS .....                | 85 |
| PSAUDIT .....              | 85 |
| PSCONTAINER .....          | 85 |
| PSCONTAINER_PRELOG.....    | 86 |
| PSPRIORITY .....           | 87 |
| PSSCHEDULE.....            | 87 |
| PSSHelfLife .....          | 88 |
| PSTIMEHEAD .....           | 89 |
| PSTIMEHEADEXTENSION.....   | 90 |
| PSTIMEMAIN.....            | 90 |
| PTExperience .....         | 91 |
| PTLicense .....            | 91 |
| PTSchools.....             | 92 |
| PTTraining .....           | 92 |
| QUALIFIERS.....            | 92 |
| REASONMASTER.....          | 93 |
| REPLICATEGRAPHCONFIG ..... | 93 |
| REPORTHEAD .....           | 93 |
| REPORTSAMPS .....          | 94 |
| RESULT.....                | 94 |
| RESULTSPECS.....           | 95 |
| RLDEFANL .....             | 95 |

|                              |     |
|------------------------------|-----|
| RLDEFHED.....                | 96  |
| RLSMPANL.....                | 96  |
| RLSMPHED .....               | 97  |
| RLTSPECS .....               | 97  |
| SAMPLE .....                 | 98  |
| SAMPLELOGINGROUP .....       | 100 |
| SAMPMAILLIST .....           | 101 |
| SAMPRELOGINGRP .....         | 101 |
| SECURITY_EVENT .....         | 102 |
| SECURITYLIC .....            | 102 |
| SECURITYLOG .....            | 103 |
| SESSIONPROCESSES .....       | 103 |
| SESSIONS.....                | 103 |
| SFRANGES .....               | 104 |
| SGTESTS .....                | 104 |
| SIADEFLT .....               | 105 |
| SIDEFLT .....                | 105 |
| SIFORMDEF .....              | 106 |
| SIGNATURE_OBJ.....           | 106 |
| SPECIALPRICELIST .....       | 107 |
| SPECINFO.....                | 107 |
| SPECMASTER .....             | 107 |
| State_Location .....         | 108 |
| StateMaster.....             | 108 |
| StateTransitions .....       | 109 |
| SUSERFLDS .....              | 109 |
| SYSMGR .....                 | 110 |
| TPHEADER .....               | 110 |
| TPPLOT .....                 | 110 |
| Transition_Location .....    | 111 |
| URESOURCE .....              | 112 |
| USERFLDS.....                | 112 |
| USERHEAD .....               | 112 |
| VIOLATIONREORDERDETAILS..... | 113 |
| VIOLATIONREORDERMASTER.....  | 113 |
| VIOLREORDER.....             | 114 |
| WORKINGDAYTIME .....         | 115 |

|  |                              |
|--|------------------------------|
| XLCALCHEAD .....   | 115                          |
| XLPARAMS .....   | 115                          |
| Appendix: LABWORKS 7.1 Entry Relationship Diagrams ..... | 117                          |
| Process Scheduler.....                                   | Error! Bookmark not defined. |
| Calculations and Result Conditioning .....               | Error! Bookmark not defined. |
| Analysis and Instrument Qualification .....              | Error! Bookmark not defined. |
| QA-QC Templates and Samples .....                        | Error! Bookmark not defined. |
| Persisted Groups .....                                   | Error! Bookmark not defined. |

## ACTIONCODES

Listing of Workflow Action Codes

### Primary Keys

- ACTIONCODE
- OBJECTTYPE

| Sr.No. | Name            | Type    | Size (Characters) | Allow Null (True/False) | Description                     |
|--------|-----------------|---------|-------------------|-------------------------|---------------------------------|
| 1      | ACTIONCODE      | varchar | 50                | False                   | Code                            |
| 2      | ACTIONLABEL     | varchar | 50                | False                   | String used for display         |
| 3      | OBJECTTYPE      | varchar | 50                | False                   | Associated LabWorks Object Type |
| 4      | ACTIONTYPE      | varchar | 50                | False                   | STANDARD or Custom              |
| 5      | ACTIONCODEORDER | int     | 10                | False                   | Order                           |

## ANALYSIS

Analysis Codes (Tests) assigned to samples

### Primary Keys

- SAMPNO
- ACODE

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description            |
|--------|-------------|----------|-------------------|-------------------------|------------------------|
| 1      | SAMPNO      | varchar  | 7                 | False                   | Sample Number          |
| 2      | ACODE       | varchar  | 24                | False                   | Analysis Code          |
| 3      | ADEPT       | varchar  | 24                | True                    | Department Code        |
| 4      | ASTATUS     | smallint |                   | False                   | Status                 |
| 5      | QBATCHED    | smallint |                   | False                   | QA/QC Batched          |
| 6      | ASSIGN_ANL  | varchar  | 12                | True                    |                        |
| 7      | ASSIGN_INST | varchar  | 24                | True                    |                        |
| 8      | RADUEDATE   | datetime |                   | True                    |                        |
| 9      | ADUEDATE    | datetime |                   | True                    | Analysis Due Date      |
| 10     | ASDATE      | datetime |                   | True                    | Analysis Start Date    |
| 11     | AEDATE      | datetime |                   | True                    | Analysis End Date      |
| 12     | APRICE      | real     |                   | False                   | Analysis Price         |
| 13     | ANALYST     | varchar  | 12                | True                    | Analyst                |
| 14     | AVALUSER    | varchar  | 12                | True                    | Validated User         |
| 15     | AVALDATE    | datetime |                   | True                    | Validated Date         |
| 16     | RLTSOURCE   | varchar  | 255               | True                    | Result Source          |
| 17     | ANLLIMIT    | smallint |                   | False                   | Analysis Limit         |
| 18     | SIFORM      | varchar  | 24                | True                    | Special Info Form code |

|    |                |          |     |       |   |
|----|----------------|----------|-----|-------|---|
| 19 | ANUM           | smallint |     | False | Analysis Number (serial number)   |
| 20 | AMODDATE       | datetime |     | True  | Last Modified Date  |
| 21 | AMODUSER       | varchar  | 12  | True  | Last Modified User  |
| 22 | APRICESET      | smallint |     | False | Price   |
| 23 | AOWNER         | varchar  | 24  | True  | Analysis Owner  |
| 24 | hSec           | int      | 10  | False | Security Handle   |
| 25 | RLT_TYPE       | varchar  | 255 | True  | Field is used to set pick lists for results entry. The acceptable content for the field can be null or one of the following: LIST-INC:A B C D, LIST-EXC:1 2 3 4, PICKLIST-EXC:POSNEG, PICKLIST-INC:POSNEG |
| 26 | RLT2_TYPE      | varchar  | 255 | True  | Field is used to set pick lists for results entry. The acceptable content for the field can be null or one of the following: LIST-INC:A B C D, LIST-EXC:1 2 3 4, PICKLIST-EXC:POSNEG, PICKLIST-INC:POSNEG |
| 27 | QUAL_TYPE      | varchar  | 255 | True  | Field is used to set pick lists for results entry. The acceptable content for the field can be null or one of the following: LIST-INC:A B C D, LIST-EXC:1 2 3 4, PICKLIST-EXC:POSNEG, PICKLIST-INC:POSNEG |
| 28 | AREADOWNER     | varchar  | 24  | True  | Analysis Read Owner   |
| 29 | SGACODE        | varchar  | 24  | True  | Parent Study group  |
| 30 | CACODE         | varchar  | 24  | True  |   |
| 31 | NOOFREPLICATES | int      | 10  | False | Number of replicates  |

|    |                  |          |    |      |   |
|----|------------------|----------|----|------|---|
| 32 | REPLICATEME THOD | varchar  | 20 | True | Replicate method. Content of the field can be null or one of the following:MIN, MAX, AVERAGE                      |
| 33 | AREF             | varchar  | 50 | True | Analysis method reference   |
| 34 | REPSELECTION     | varchar  | 15 | True | Replicate selection on. Content of the field can be null or one of the following:<br>ALL_REPLICATES,<br>MDL_RANGE |
| 35 | INSTRUMENT       | varchar  | 24 | True |   |
| 36 | PREPDATE         | datetime |    | True | Preparation DateTime  |

## ANALYST\_TEAM

Listing of Analyst Team Membership

### Primary Keys

- INITIALS
- TEAMNAME

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------|---------|-------------------|-------------------------|-------------|
| 1      | INITIALS | varchar | 12                | False                   | Initials    |
| 2      | TEAMNAME | varchar | 50                | False                   | Team Name   |

## ANALYSTS

Listing of LAB Analysts

### Primary Keys

- INITIALS

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description     |
|--------|----------|----------|-------------------|-------------------------|-----------------|
| 1      | INITIALS | varchar  | 12                | False                   | Initials        |
| 2      | FULLNAME | varchar  | 50                | False                   | Full Name       |
| 3      | STATUS   | smallint |                   | False                   | Analyst Status  |
| 4      | EmpDate  | datetime |                   | True                    | Employed Date   |
| 5      | EmpType  | smallint |                   | False                   | Employment Type |
| 6      | Other    | varchar  | 255               | True                    | Other info      |
| 7      | hSec     | int      | 10                | False                   | Security Handle |

|   |             |          |    |      |                       |
|---|-------------|----------|----|------|-----------------------|
| 8 | TEAMNAME    | varchar  | 24 | True | Users Team Membership |
| 9 | COMMENTTEXT | nvarchar | -1 | True |                       |

## ANALYTES

Analytes List for each multi -component Analysis listed in the ANL\_LIST table

### Primary Keys

- ACODE
- ANLNAME

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description                     |
|--------|------------------|----------|-------------------|-------------------------|---------------------------------|
| 1      | ACODE            | varchar  | 24                | False                   | Analysis Code                   |
| 2      | ANLNAME          | varchar  | 100               | False                   | Analyte Name                    |
| 3      | ANLNUM           | smallint |                   | False                   | Analyte Number (serial Number)  |
| 4      | ANLABBR          | varchar  | 40                | True                    | Analyte Abbreviation            |
| 5      | ANLMDL           | varchar  | 14                | True                    | Analyte Minimum Detection Limit |
| 6      | CASNUMB          | varchar  | 20                | True                    | Chemical Abstract Number        |
| 7      | ANLPQL           | varchar  | 14                | True                    | Practical Quantitation Limit    |
| 8      | hSec             | int      | 10                | False                   | Security Handle                 |
| 9      | ANLUNIT          | varchar  | 14                | True                    | Units for Analyte               |
| 10     | AREF             | varchar  | 50                | True                    | Analyte method reference        |
| 11     | MODDATE          | datetime |                   | True                    | ModDate                         |
| 12     | DEFAULTQUALIFIER | varchar  | 14                | True                    | Default Qualifier for analytes  |

## ANALYTES\_HIST

### Primary Keys

- ACODE
- ANLNAME
- VERSION

| Sr.No. | Name    | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|---------|----------|-------------------|-------------------------|-------------|
| 1      | ACODE   | varchar  | 24                | False                   |             |
| 2      | ANLNAME | varchar  | 40                | False                   |             |
| 3      | VERSION | int      | 10                | False                   |             |
| 4      | ANLNUM  | smallint |                   | False                   |             |
| 5      | ANLABBR | varchar  | 40                | True                    |             |
| 6      | ANLMDL  | varchar  | 8                 | True                    |             |

|   |         |         |    |       |  |
|---|---------|---------|----|-------|--|
| 7 | CASNUMB | varchar | 20 | True  |  |
| 8 | ANLPQL  | varchar | 14 | True  |  |
| 9 | hSec    | int     | 10 | False |  |

## ANL\_LIST

Table to hold all Analyses

### Primary Keys

- ACODE

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description   |
|--------|-----------|----------|-------------------|-------------------------|---|
| 1      | ACODE     | varchar  | 24                | False                   | Analysis Code   |
| 2      | ANAME     | varchar  | 40                | True                    | Analysis Name   |
| 3      | AUNIT     | varchar  | 14                | True                    | Analysis Unit   |
| 4      | AMDL      | varchar  | 14                | True                    | MDL   |
| 5      | ADEPT     | varchar  | 24                | True                    | Department  |
| 6      | AREF      | varchar  | 50                | True                    | Method reference  |
| 7      | CHOLDMINS | int      | 10                | False                   | Analysis Hold Minutes   |
| 8      | RHOLDMINS | int      | 10                | False                   | Result Hold Minutes   |
| 9      | APRICE    | real     |                   | False                   | Analysis Price  |
| 10     | NONREP    | smallint |                   | False                   | Reportable flag   |
| 11     | NONINV    | smallint |                   | False                   | Invoiceable flag  |
| 12     | SIGFIGS   | smallint |                   | False                   | Significant figures flag  |
| 13     | WORKUNIT  | real     |                   | False                   | Work unit   |
| 14     | COMPFILE  | varchar  | 255               | True                    |   |
| 15     | REPALL    | smallint |                   | False                   | Report All flag   |
| 16     | ADDCOMPS  | smallint |                   | False                   |   |
| 17     | SIFORM    | varchar  | 24                | True                    | Special Info Template name  |
| 18     | MODDATE   | datetime |                   | False                   | Last Modified Date  |
| 19     | MODUSER   | varchar  | 12                | True                    | Last Modified User  |
| 20     | AOWNER    | varchar  | 24                | True                    | Owner   |
| 21     | hSec      | int      | 10                | False                   | Security Handle   |
| 22     | RLT_TYPE  | varchar  | 255               | True                    | Field is used to set pick lists for results entry. The acceptable content for the field can be null or one of the following: LIST-INC:A B C D, LIST-EXC:1 2 3 4, PICKLIST-EXC:POSNEG, PICKLIST-INC:POSNEG |

|    |                      |         |     |       |  |
|----|----------------------|---------|-----|-------|--|
| 23 | RLT2_TYPE            | varchar | 255 | True  | Field is used to set pick lists for results entry. The acceptable content for the field can be null or one of the following: LIST-INC:A B C D, LIST-EXC:1 2 3 4, PICKLIST-EXC:POSNEG, PICKLIST-INC:POSNEG  |
| 24 | QUAL_TYPE            | varchar | 255 | True  | Field is used to set pick lists for results entry. The acceptable content for the field can be null or one of the following: LIST-INC:A B C D , LIST-EXC:1 2 3 4, PICKLIST-EXC:POSNEG, PICKLIST-INC:POSNEG |
| 25 | CURRENT_STA<br>TE    | varchar | 50  | True  | Analysis Code State  |
| 26 | ANLOWNER             | varchar | 24  | True  | Analysis Code Owner  |
| 27 | ANLREADOWN<br>ER     | varchar | 24  | True  | Analysis Read Owner  |
| 28 | ANLRLTOWNE<br>R      | varchar | 24  | True  | Analysis Result Owner  |
| 29 | NOOFREPLICA<br>TES   | int     | 10  | False | Number of replicates   |
| 30 | REPLICATEME<br>THOD  | varchar | 20  | True  | Replicate method. Content of the field can be null or one of the following:MIN, MAX, AVERAGE   |
| 31 | REPSELECTION         | varchar | 15  | True  | Replicate selection on. Content of the field can be null or one of the following: ALL_REPLICATES, MDL_RANGE  |
| 32 | DEFAULTRESU<br>LT    | varchar | 14  | True  |  |
| 33 | RLTUNIT_TYPE         | varchar | 255 | True  | Result Unit  |
| 34 | DEFAULTQUALI<br>FIER | varchar | 14  | True  | Default Qualifier for Analysis   |

## ANL\_LIST\_HIST

### Primary Keys

- ACODE
- VERSION

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-----------|----------|-------------------|-------------------------|-------------|
| 1      | ACODE     | varchar  | 24                | False                   |             |
| 2      | VERSION   | int      | 10                | False                   |             |
| 3      | ANAME     | varchar  | 40                | True                    |             |
| 4      | AUNIT     | varchar  | 14                | True                    |             |
| 5      | AMDL      | varchar  | 8                 | True                    |             |
| 6      | ADEPT     | varchar  | 24                | True                    |             |
| 7      | AREF      | varchar  | 16                | True                    |             |
| 8      | CHOLDMINS | int      | 10                | False                   |             |
| 9      | RHOLDMINS | int      | 10                | False                   |             |
| 10     | APRICE    | real     |                   | False                   |             |
| 11     | NONREP    | smallint |                   | False                   |             |
| 12     | NONINV    | smallint |                   | False                   |             |
| 13     | SIGFIGS   | smallint |                   | False                   |             |
| 14     | WORKUNIT  | real     |                   | False                   |             |
| 15     | COMPFILE  | varchar  | 255               | True                    |             |
| 16     | REPALL    | smallint |                   | False                   |             |
| 17     | ADDCOMPS  | smallint |                   | False                   |             |
| 18     | SIFORM    | varchar  | 24                | True                    |             |
| 19     | MODDATE   | datetime |                   | False                   |             |
| 20     | MODUSER   | varchar  | 12                | True                    |             |
| 21     | AOWNER    | varchar  | 24                | True                    |             |
| 22     | hSec      | int      | 10                | False                   |             |
| 23     | RLT_TYPE  | varchar  | 255               | True                    |             |
| 24     | RLT2_TYPE | varchar  | 255               | True                    |             |
| 25     | QUAL_TYPE | varchar  | 255               | True                    |             |

## ANL\_MATRIX

### Analysis Matrix Details

### Primary Keys

- ACODE
- MATRIX

| Sr.No. | Name    | Type     | Size (Characters) | Allow Null (True/False) | Description        |
|--------|---------|----------|-------------------|-------------------------|--------------------|
| 1      | ACODE   | varchar  | 24                | False                   | Analysis Code      |
| 2      | MATRIX  | varchar  | 24                | False                   | Matrix Name        |
| 3      | MODDATE | datetime |                   | False                   | Last Modified Date |
| 4      | MODUSER | varchar  | 12                | True                    | Last Modified User |

|   |      |     |    |       |                 |
|---|------|-----|----|-------|-----------------|
| 5 | hSec | int | 10 | False | Security Handle |
|---|------|-----|----|-------|-----------------|

## ANLOBJECT

Table containing listing of analysis objects. – Data migrated to LabObjObjects in v 6.3

### Primary Keys

- SAMPNO
- ACODE
- OBJNUMB

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description                                     |
|--------|------------|----------|-------------------|-------------------------|---|
| 1      | SAMPNO     | varchar  | 7                 | False                   | Sample ID                                       |
| 2      | ACODE      | varchar  | 24                | False                   | Analysis Code                                   |
| 3      | OBJNUMB    | smallint |                   | False                   | Object Number (In sequence – unique for SampNo) |
| 4      | OBJDESCR   | varchar  | 255               | True                    | Description (physical path)                     |
| 5      | OBJSPEC    | varchar  | 255               | False                   | Specification (physical path)                   |
| 6      | COMPRESSED | smallint |                   | False                   | Compressed flag                                 |
| 7      | MODDATE    | datetime |                   | True                    | Last Modified Date                              |
| 8      | MODUSER    | varchar  | 12                | True                    | Last Modified User                              |
| 9      | OBJDATA    | image    | 2147483647        | True                    | Data for Object                                 |
| 10     | hSec       | int      | 10                | False                   | Security Handle                                 |

## ANLSUBST

Analyte substitutions listing for each Instrument Analyte

### Primary Keys

- INSTTYPE
- IANALYTE

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description        |
|--------|----------|---------|-------------------|-------------------------|--------------------|
| 1      | INSTTYPE | varchar | 16                | False                   | Instrument Type    |
| 2      | IANALYTE | varchar | 40                | False                   | Instrument Analyte |
| 3      | LANALYTE | varchar | 40                | False                   | Lab Analyte        |
| 4      | hSec     | int     | 10                | False                   | Security Handle    |

## ANLTESTS

Analysis Listing for each LABWORKS Analyst

### Primary Keys

- INITIALS
- ACODE

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description      |
|--------|----------|----------|-------------------|-------------------------|------------------|
| 1      | INITIALS | varchar  | 12                | False                   | Analyst Initials |
| 2      | ACODE    | varchar  | 24                | False                   | Analysis Code    |
| 3      | EXPDATE  | datetime |                   | True                    | Expiry Date      |
| 4      | SOP      | smallint |                   | False                   |                  |
| 5      | hSec     | int      | 10                | False                   | Security Handle  |

## APPPRIVS

### Primary Keys

| Sr.No. | Name        | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------------|---------|-------------------|-------------------------|-------------|
| 1      | URVALUE     | varchar | 16                | False                   |             |
| 2      | APPLICATION | varchar | 50                | True                    |             |

## AUDITTRAIL

The audit trail table contains information about changes to samples and results of analyses

### Primary Keys

- KEYCOUNTER

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description       |
|--------|------------------|----------|-------------------|-------------------------|-------------------|
| 1      | KEYCOUNTER       | int      | 10                | False                   | Serial Number     |
| 2      | OBJECTTYPE       | varchar  | 255               | True                    | Object Type       |
| 3      | OBJECTID         | varchar  | 255               | True                    | Object ID         |
| 4      | PROPERTYNAME     | varchar  | 255               | True                    | Name of Object    |
| 5      | USERID           | varchar  | 50                | True                    | User ID           |
| 6      | CHANGEDATETIME   | datetime |                   | True                    | Change Date       |
| 7      | PROPERTYDATATYPE | varchar  | 50                | True                    | Data Type         |
| 8      | OLDVALUETEXT     | varchar  | 4000              | True                    | Old Text Value    |
| 9      | NEWVALUETEXT     | varchar  | 4000              | True                    | New Text Value    |
| 10     | OLDVALUENUMBER   | float    |                   | True                    | Old Numeric Value |
| 11     | NEWVALUENU       | float    |                   | True                    | New Numeric       |

|    | MBER                  |          |            |       | Value               |
|----|-----------------------|----------|------------|-------|---------------------|
| 12 | OLDVALUEDATE          | datetime |            | True  | Old Date Value      |
| 13 | NEWVALUEDATE          | datetime |            | True  | New Date Value      |
| 14 | REASON                | varchar  | 255        | True  | Change Reason       |
| 15 | AdditionalInformation | text     | 2147483647 | True  | More Information    |
| 16 | hSec                  | int      | 10         | True  | Security Reference  |
| 17 | AUDITTYPE             | varchar  | 50         | True  | Type of Audit       |
| 18 | OLDLONGTEXT           | ntext    | 1073741823 | True  | Old Long text value |
| 19 | NEWLONGTEXT           | ntext    | 1073741823 | True  | New Long Text Value |
| 20 | AUDITCHECKSUM         | varchar  | 40         | True  | Checksum Value      |
| 21 | CHECKSUMVERSION       | int      | 10         | False | Checksum Version    |

## AUDTRAIL

The audit trail table contains information about changes to samples and results of analyses. – Moved to AUDITTRAIL in v 6.1

### Primary Keys

- KEYCOUNTER

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description             |
|--------|------------|----------|-------------------|-------------------------|-------------------------|
| 1      | SAMPNO     | varchar  | 7                 | False                   | Sample ID               |
| 2      | AUDTYPE    | varchar  | 2                 | False                   | Audit Type code         |
| 3      | AUDITEM1   | varchar  | 50                | False                   | Audit Item abbreviation |
| 4      | AUDITEM2   | varchar  | 50                | False                   | Audit Item description  |
| 5      | OLDVALUE   | varchar  | 50                | True                    | Old Value               |
| 6      | NEWVALUE   | varchar  | 50                | True                    | New Value               |
| 7      | CHANGEDATE | datetime |                   | True                    | Change Date             |
| 8      | CUSERINIT  | varchar  | 12                | True                    | User Initials           |
| 9      | CUSERNAME  | varchar  | 36                | True                    | User Name               |
| 10     | REASON     | varchar  | 255               | True                    | Change Reason           |
| 11     | KEYCOUNTER | int      | 10                | False                   | Serial Number           |
| 12     | hSec       | int      | 10                | False                   | Security Handle         |

## AUSERFLDS

The analysis user fields, AUSERFLDS, table stores user defined information common to all analysis codes

### Primary Keys

| Sr.No. | Name | Type | Size (Characters) | Allow Null (True/False) | Description |
|--------|------|------|-------------------|-------------------------|-------------|
|        |      |      |                   |                         |             |

|   |         |         |    |       |                    |
|---|---------|---------|----|-------|--------------------|
| 1 | OBJID   | varchar | 50 | False | Object ID          |
| 2 | OBJTYPE | varchar | 24 | False | Type               |
| 3 | HSEC    | int     | 10 | True  | Security Reference |

## BATCHHEAD

QA/QC Batch Header Details – 6.2 Batching

### Primary Keys

- BATCHID

| Sr.No. | Name          | Type     | Size (Characters) | Allow Null (True/False) | Description            |
|--------|---------------|----------|-------------------|-------------------------|------------------------|
| 1      | BATCHID       | varchar  | 40                | False                   | Batch ID               |
| 2      | BATCHDESCR    | varchar  | 60                | True                    | Batch Description      |
| 3      | TEMPLATENAME  | varchar  | 50                | False                   | Batch Template         |
| 4      | WORKFLOW      | varchar  | 50                | True                    | Batch Workflow         |
| 5      | ASSIGNANALYST | varchar  | 12                | True                    | Assigned Analyst       |
| 6      | ASSIGNINSTR   | varchar  | 24                | True                    | Assigned Instrument    |
| 7      | CURRENT_STATE | varchar  | 50                | False                   | Batch State            |
| 8      | MODUSER       | varchar  | 12                | True                    | Last Modified User     |
| 9      | MODDATE       | datetime |                   | True                    | Last Modification Date |
| 10     | CREATEDBY     | varchar  | 12                | True                    | Created User           |
| 11     | CREATEDATE    | datetime |                   | True                    | Creation Date          |
| 12     | eWorksheetId  | bigint   |                   | True                    | E worksheet Identifier |
| 13     | PREPDATE      | datetime |                   | True                    | Preparation DateTime   |

## BATCHITEMSTOCKS

### Primary Keys

- ID

| Sr.No. | Name        | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------------|---------|-------------------|-------------------------|-------------|
| 1      | ID          | int     | 10                | False                   |             |
| 2      | BatchName   | varchar | 40                | True                    |             |
| 3      | ItemStockID | int     | 10                | True                    |             |
| 4      | Quantity    | real    |                   | True                    |             |

## BATCHSAMPS

Samples associated with QA/QC Batches 6.2 Batching

### Primary Keys

- BATCH\_NAME
- BATCH\_INDEX

| Sr.No. | Name           | Type    | Size (Characters) | Allow Null (True/False) | Description         |
|--------|----------------|---------|-------------------|-------------------------|---------------------|
| 1      | BATCH_NAME     | varchar | 40                | False                   | Batch Name          |
| 2      | BATCH_INDEX    | int     | 10                | False                   | Index in Batch      |
| 3      | BATCH_SAMPNO   | varchar | 7                 | False                   | SampNo              |
| 4      | BATCH_ANALYSES | varchar | 4000              | True                    | Analyses for Sample |
| 5      | BATCH_SAMPTYPE | varchar | 50                | True                    | Sample Type         |
| 6      | hSec           | int     | 10                | False                   | Security Reference  |
| 7      | BATCH_SUBBATCH | varchar | 1                 | True                    | SubBatch            |

## BATCHTEMPLATE

QA/QC Batches Template 6.2 Batching

### Primary Keys

- BATCHID

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description                 |
|--------|----------|---------|-------------------|-------------------------|-----------------------------|
| 1      | BATCHID  | varchar | 40                | False                   | Batch ID                    |
| 2      | TEMPLATE | text    | 2147483647        | True                    | Xml description of template |

## BATHEAD

QA/QC Batch Header Details

### Primary Keys

- BATNAME

| Sr.No. | Name    | Type     | Size (Characters) | Allow Null (True/False) | Description  |
|--------|---------|----------|-------------------|-------------------------|--------------|
| 1      | BATNAME | varchar  | 40                | False                   | Batch Name   |
| 2      | BATNUMB | int      | 10                | False                   | Batch Number |
| 3      | BATTEST | varchar  | 24                | False                   | Batch Test   |
| 4      | BATDATE | datetime |                   | True                    | Batch Date   |
| 5      | BATUSER | varchar  | 12                | True                    | Batched User |
| 6      | QASAMP  | varchar  | 7                 | True                    | QA Sample    |

|   |      |     |    |       |                 |
|---|------|-----|----|-------|-----------------|
| 7 | hSec | int | 10 | False | Security Handle |
|---|------|-----|----|-------|-----------------|

## BATSAMPS

Samples associated with QA/QC Batches

### Primary Keys

- BATNAME
- BSAMPNO

| Sr.No. | Name    | Type    | Size (Characters) | Allow Null (True/False) | Description     |
|--------|---------|---------|-------------------|-------------------------|-----------------|
| 1      | BATNAME | varchar | 40                | False                   | Batch Name      |
| 2      | BSAMPNO | varchar | 7                 | False                   | Batch Sample    |
| 3      | hSec    | int     | 10                | False                   | Security Handle |

## BMESSAGEQUEUE

Messages used between programs and users

### Primary Keys

- MSGNUMBER

| Sr.No. | Name                 | Type     | Size (Characters) | Allow Null (True/False) | Description                |
|--------|----------------------|----------|-------------------|-------------------------|----------------------------|
| 1      | MSGNUMBER            | int      | 10                | False                   | Message ID                 |
| 2      | MSGTYPE              | varchar  | 32                | True                    | Message Type               |
| 3      | SENDER               | varchar  | 255               | True                    | Sender                     |
| 4      | DESTINATION          | varchar  | 255               | True                    | Destination                |
| 5      | MESSAGEBODY          | nvarchar | 2000              | True                    | Message                    |
| 6      | MessageObject        | text     | 2147483647        | True                    |                            |
| 7      | STATUS               | varchar  | 50                | True                    | Message Status             |
| 8      | DETAIL1              | varchar  | 64                | True                    | Field for message detail 1 |
| 9      | DETAIL2              | varchar  | 64                | True                    | Field for message detail 2 |
| 10     | DETAIL3              | varchar  | 64                | True                    | Field for message detail 3 |
| 11     | StatusUpdateDateTime | datetime |                   | True                    | Last update                |
| 12     | MsgLocked            | int      | 10                | True                    | Message is locked          |
| 13     | MsgLockDateTime      | datetime |                   | True                    | When message was locked    |
| 14     | CreateDateTime       | datetime |                   | True                    | When message was created   |
| 15     | CreateUserID         | varchar  | 50                | True                    | Who created message        |
| 16     | ModDateTime          | datetime |                   | True                    | Last record modification   |
| 17     | ModUserID            | varchar  | 12                | True                    | Last modification          |

|    |               |          |      |      |                                |
|----|---------------|----------|------|------|--------------------------------|
|    |               |          |      |      |                                |
| 18 | MoveToArchive | bigint   |      | True | user<br>Move record to archive |
| 19 | MessageText   | nvarchar | 2000 | True | Message Text                   |

## BMessageTypes

List of message types

### Primary Keys

| Sr.No. | Name           | Type    | Size (Characters) | Allow Null (True/False) | Description                       |
|--------|----------------|---------|-------------------|-------------------------|-----------------------------------|
| 1      | MsgTypeName    | varchar | 50                | True                    | Message Type                      |
| 2      | Description    | varchar | 50                | True                    | Message Type Description          |
| 3      | IsNotification | int     | 10                | True                    | Send notification on message type |

## BOTTLELIST

Bottle Label listing with Analysis

### Primary Keys

- ACODE
- BOTTLECODE

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description          |
|--------|-------------|----------|-------------------|-------------------------|----------------------|
| 1      | ACODE       | varchar  | 24                | False                   | Analysis Code        |
| 2      | BOTTLECODE  | varchar  | 24                | False                   | Bottle Label         |
| 3      | hSec        | int      | 10                | False                   | Security Handle      |
| 4      | DEFAULTBOTT | smallint |                   | False                   | Default Bottle Label |
|        | LECODE      |          |                   |                         |                      |

## CALCDEFS

Calculation Definition for Analysis

### Primary Keys

- ACODE

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description                  |
|--------|----------|----------|-------------------|-------------------------|------------------------------|
| 1      | ACODE    | varchar  | 24                | False                   | Analysis Code                |
| 2      | KEYTEST  | smallint |                   | False                   | Key Test Index               |
| 3      | CALCMDL  | smallint |                   | False                   | Calculated MDL               |
| 4      | NNOPTION | smallint |                   | False                   | Non Numeric Key value option |

|    |                |          |     |       |                             |
|----|----------------|----------|-----|-------|-----------------------------|
| 5  | INVAR1         | varchar  | 24  | True  | Input Parameter variable 1  |
| 6  | INVAR2         | varchar  | 24  | True  | Input Parameter variable 2  |
| 7  | INVAR3         | varchar  | 24  | True  | Input Parameter variable 3  |
| 8  | INVAR4         | varchar  | 24  | True  | Input Parameter variable 4  |
| 9  | INVAR5         | varchar  | 24  | True  | Input Parameter variable 5  |
| 10 | INVAR6         | varchar  | 24  | True  | Input Parameter variable 6  |
| 11 | INVAR7         | varchar  | 24  | True  | Input Parameter variable 7  |
| 12 | INVAR8         | varchar  | 24  | True  | Input Parameter variable 8  |
| 13 | INVAR9         | varchar  | 24  | True  | Input Parameter variable 9  |
| 14 | INVAR10        | varchar  | 24  | True  | Input Parameter variable 10 |
| 15 | CFUNCT         | varchar  | 128 | False | Calculation Function        |
| 16 | MODDATE        | datetime |     | True  | Modified Date               |
| 17 | MODUSER        | varchar  | 12  | True  | Modified User               |
| 18 | hSec           | int      | 10  | False | Security Handle             |
| 19 | DATETIMEOPTION | smallint |     | False |                             |

## CALCPARAMS

Listing of calculation parameters

### Primary Keys

- ACODE
- INVAR\_INDEX

| Sr.No. | Name        | Type    | Size (Characters) | Allow Null (True/False) | Description             |
|--------|-------------|---------|-------------------|-------------------------|-------------------------|
| 1      | ACODE       | varchar | 24                | False                   | Analysis Code           |
| 2      | INVAR       | varchar | 24                | False                   | Acode of Input variable |
| 3      | INVAR_INDEX | int     | 10                | False                   | Index of variable       |

## CBANLS

Analysis Listing for Certificate of Analysis Customer Base

### Primary Keys

- CUSTBASE
- COANAME

| Sr.No. | Name | Type | Size | Allow Null | Description |
|--------|------|------|------|------------|-------------|
|        |      |      |      |            |             |

|    |                  |          | <b>(Characters)</b> | <b>(True/False)</b> |                    |
|----|------------------|----------|---------------------|---------------------|--------------------|
| 1  | CUSTBASE         | varchar  | 24                  | False               | Customer Base Name |
| 2  | COANAME          | varchar  | 100                 | False               | COA Name           |
| 3  | COAUNIT          | varchar  | 14                  | True                | COA Unit           |
| 4  | COAFORMAT        | varchar  | 10                  | True                | COA Format         |
| 5  | ACODE            | varchar  | 24                  | True                | Analysis Code      |
| 6  | ANALYTE          | varchar  | 100                 | False               | Analyte            |
| 7  | CONVFACT         | real     |                     | True                | Conversion factor  |
| 8  | SPECTYPE         | varchar  | 3                   | False               | Spec Type          |
| 9  | VAL1             | varchar  | 14                  | True                | Value 1            |
| 10 | VAL2             | varchar  | 14                  | True                | Value 2            |
| 11 | WEIGHT           | smallint |                     | False               | Weight             |
| 12 | ANLNUMB          | smallint |                     | False               |                    |
| 13 | hSec             | int      | 10                  | False               | Security Handle    |
| 14 | MULTIVALE_OPTION | varchar  | 24                  | True                |                    |

## CBCHARTANL

SQC Charting Analyte specification for Certificate of Analysis Customer Base

### Primary Keys

- CUSTBASE
- COANAME
- CHARTTYPE

| <b>Sr.No.</b> | <b>Name</b> | <b>Type</b> | <b>Size (Characters)</b> | <b>Allow Null (True/False)</b> | <b>Description</b> |
|---------------|-------------|-------------|--------------------------|--------------------------------|--------------------|
| 1             | CUSTBASE    | varchar     | 24                       | False                          | Customer Base Name |
| 2             | COANAME     | varchar     | 100                      | False                          | COA Name           |
| 3             | CHARTTYPE   | varchar     | 8                        | False                          | Chart Type         |
| 4             | OUTPUT      | varchar     | 1                        | False                          | Output             |
| 5             | RANGETYPE   | varchar     | 1                        | False                          | Range Type         |
| 6             | YAXISMIN    | real        |                          | True                           | Y Axis Min value   |
| 7             | YAXISMAX    | real        |                          | True                           | Y Axis Max value   |
| 8             | CHARTNUM    | smallint    |                          | False                          | Chart number       |
| 9             | hSec        | int         | 10                       | False                          | Security Handle    |

## CBCHARTHEAD

SQC Charting specification for Certificate of Analysis Customer Base

### Primary Keys

- CUSTBASE

| <b>Sr.No.</b> | <b>Name</b> | <b>Type</b> | <b>Size (Characters)</b> | <b>Allow Null (True/False)</b> | <b>Description</b> |
|---------------|-------------|-------------|--------------------------|--------------------------------|--------------------|
| 1             | CUSTBASE    | varchar     | 24                       | False                          | Customer Base      |

|    |                |          |    |       | Name                                       |
|----|----------------|----------|----|-------|--|
| 2  | DATASELECTTYPE | varchar  | 1  | False | Data selection type                        |
| 3  | DSVAL1         | varchar  | 20 | True  | Data selection value 1                     |
| 4  | DSVAL2         | varchar  | 20 | True  | Data selection value 2                     |
| 5  | XAXISLABEL     | varchar  | 1  | False | X Axis Label                               |
| 6  | SUBGROUPBY     | varchar  | 1  | False | Sub group by                               |
| 7  | SUBGROUPSIZE   | smallint |    | False | Sub group size                             |
| 8  | LAYOUT         | varchar  | 4  | True  | Chart Layout                               |
| 9  | OVERWRITE      | smallint |    | False | overwrite header and run files option Flag |
| 10 | SHOWSPEC       | smallint |    | False | Use COA specs option flag                  |
| 11 | RUNRULES       | smallint |    | False | Use Pattern Rules option flag              |
| 12 | NONNUMERIC     | varchar  | 1  | True  | Non numeric result option                  |
| 13 | hSec           | int      | 10 | False | Security Handle                            |

## CBHEADER

Customer Base specification

### Primary Keys

- CUSTBASE

| Sr.No. | Name      | Type    | Size (Characters) | Allow Null (True/False) | Description         |
|--------|-----------|---------|-------------------|-------------------------|---------------------|
| 1      | CUSTBASE  | varchar | 24                | False                   | Customer Base Name  |
| 2      | PRODDESCR | varchar | 32                | True                    | Product Description |
| 3      | CUSTOMER  | varchar | 26                | True                    | Customer Name       |
| 4      | PRODID    | varchar | 16                | True                    | Product ID          |
| 5      | CUSTADsD1 | varchar | 30                | True                    | Customer Address 1  |
| 6      | CUSTADD2  | varchar | 30                | True                    | Customer Address 2  |
| 7      | CUSTADD3s | varchar | 30                | True                    | Customer Address 3  |
| 8      | CUSTADD4  | varchar | 30                | True                    | Customer Address 4  |
| 9      | CUSTADD5  | varchar | 30                | True                    | Customer Address 5  |
| 10     | ATTN1     | varchar | 30                | True                    | Attention Address 1 |
| 11     | ATTN2     | varchar | 30                | True                    | Attention Address 2 |
| 12     | ATTN3     | varchar | 30                | True                    | Attention Address 3 |
| 13     | ATTN4     | varchar | 30                | True                    | Attention Address 4 |

|    |           |          |     |       |                     |
|----|-----------|----------|-----|-------|---------------------|
| 14 | ATTN5     | varchar  | 30  | True  | Attention Address 5 |
| 15 | COPIES    | smallint |     | False | Copies to Print     |
| 16 | PROMPTGRP | varchar  | 8   | True  | Prompt Group name   |
| 17 | CUSTFORM  | varchar  | 100 | True  | Custom form name    |
| 18 | MODDATE   | datetime |     | True  | Modified Date       |
| 19 | MODUSER   | varchar  | 12  | True  | Modified User       |
| 20 | hSec      | int      | 10  | False | Security Handle     |

## CBPROMPT

Prompt Groups in Customer Base. This table contains, standard Prompt Groups such as Lot No., Carrier, Ship Date, Destination etc, and the fields which are relevant to shipment

### Primary Keys

- PROMPTGRP
- PRMTNUMB

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description         |
|--------|-----------|----------|-------------------|-------------------------|---------------------|
| 1      | PROMPTGRP | varchar  | 8                 | False                   | Prompt Group        |
| 2      | PRMTNUMB  | smallint |                   | False                   | Prompt Group Number |
| 3      | PRMTTEXT  | varchar  | 30                | True                    | Prompt Text         |
| 4      | hSec      | int      | 10                | False                   | Security Handle     |

## CBVARS

Custom form Layout variables in Customer Base

### Primary Keys

- CUSTBASE
- VARNUMB

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description                                     |
|--------|----------|----------|-------------------|-------------------------|---|
| 1      | CUSTBASE | varchar  | 24                | False                   | Customer Base                                   |
| 2      | VARNUMB  | smallint |                   | False                   | Variable Number (unique for each Customer Base) |
| 3      | VARCODE  | varchar  | 6                 | False                   | Variable Code                                   |
| 4      | VARCELL  | varchar  | 8                 | True                    |   |
| 5      | hSec     | int      | 10                | False                   | Security Handle                                 |

## CCHARTDATA

### Primary Keys

- CCGROUPNAME
- CCGROUPNUMBER
- SAMPNO

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description     |
|--------|------------------|----------|-------------------|-------------------------|-----------------|
| 1      | CCGROUPNAME      | varchar  | 55                | False                   |                 |
| 2      | CCGROUPNUMBER    | int      | 10                | False                   |                 |
| 3      | SAMPNO           | varchar  | 7                 | False                   | Sample ID       |
| 4      | VALIDATIONONDATE | datetime |                   | True                    | Validation Date |
| 5      | hSec             | int      | 10                | False                   | Security Handle |

## CCHARTHEADER

### Primary Keys

- CCGROUPNAME
- CCGROUPNUMBER
- MATRIX

| Sr.No. | Name          | Type     | Size (Characters) | Allow Null (True/False) | Description     |
|--------|---------------|----------|-------------------|-------------------------|-----------------|
| 1      | CCGROUPNAME   | varchar  | 50                | False                   |                 |
| 2      | CCGROUPNUMBER | int      | 10                | False                   |                 |
| 3      | ACODE         | varchar  | 24                | True                    | Analysis Code   |
| 4      | ANALYTE       | varchar  | 100               | True                    | Analyte         |
| 5      | MATRIX        | varchar  | 24                | False                   | Matrix          |
| 6      | CCGROUPDATE   | datetime |                   | True                    | Grouped Date    |
| 7      | hSec          | int      | 10                | False                   | Security Handle |
| 8      | MATRIX_INT    | int      | 10                | True                    |                 |

## CCHARTSETUP

### Primary Keys

- ACODE
- ANALYTE
- MATRIX

| Sr.No. | Name    | Type    | Size (Characters) | Allow Null (True/False) | Description   |
|--------|---------|---------|-------------------|-------------------------|---------------|
| 1      | ACODE   | varchar | 24                | False                   | Analysis Code |
| 2      | ANALYTE | varchar | 100               | False                   | Analyte       |

|    |                         |          |    |       |                 |
|----|-------------------------|----------|----|-------|-----------------|
| 3  | NPOINTS                 | int      | 10 | False |                 |
| 4  | ANUM                    | int      | 10 | False |                 |
| 5  | ANLNUM                  | int      | 10 | False |                 |
| 6  | STARTDATE               | datetime |    | True  | Start Date      |
| 7  | MATRIX                  | varchar  | 24 | False | Matrix          |
| 8  | hSec                    | int      | 10 | False | Security Handle |
| 9  | LASTUPDATED<br>DATETIME | datetime |    | True  |                 |
| 10 | MATRIX_INT              | int      | 10 | True  |                 |

## CIM\_Actions

### Primary Keys

- Id

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------------|----------|-------------------|-------------------------|-------------|
| 1      | Id          | int      | 10                | False                   |             |
| 2      | Name        | nvarchar | 255               | True                    |             |
| 3      | Description | nvarchar | 1024              | True                    |             |
| 4      | Manual      | smallint |                   | False                   |             |

## CIM\_AnlMethods

### Analysis Methods

### Primary Keys

- Initials
- Method

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------|----------|-------------------|-------------------------|-------------|
| 1      | Initials | varchar  | 12                | False                   | Initials    |
| 2      | Method   | varchar  | 255               | False                   | Method      |
| 3      | ExpDate  | datetime |                   | True                    | Expiry Date |

## CIM\_CAPAEffectChecks

### Primary Keys

- Id

| Sr.No. | Name          | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|---------------|----------|-------------------|-------------------------|-------------|
| 1      | Id            | int      | 10                | False                   |             |
| 2      | ReportId      | int      | 10                | False                   |             |
| 3      | Type          | varchar  | 255               | False                   |             |
| 4      | ScheduledDate | datetime |                   | True                    |             |

|    |                   |          |    |       |  |
|----|-------------------|----------|----|-------|--|
| 5  | StartSurpriseDate | datetime |    | True  |  |
| 6  | EndSurpriseDate   | datetime |    | True  |  |
| 7  | Complete          | smallint |    | False |  |
| 8  | CompleteDate      | datetime |    | True  |  |
| 9  | CreatedOn         | datetime |    | False |  |
| 10 | CreatedBy         | int      | 10 | False |  |
| 11 | UpdatedOn         | datetime |    | True  |  |
| 12 | UpdatedBy         | int      | 10 | True  |  |

## CIM\_CAPAReports

### Primary Keys

- Id

| Sr.No. | Name                | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|---------------------|----------|-------------------|-------------------------|-------------|
| 1      | Id                  | int      | 10                | False                   |             |
| 2      | ReportNumber        | nvarchar | 128               | False                   |             |
| 3      | ActionType          | nvarchar | 50                | False                   |             |
| 4      | AssignedUser        | varchar  | 12                | False                   |             |
| 5      | AssignedDate        | datetime |                   | False                   |             |
| 6      | DueDate             | datetime |                   | True                    |             |
| 7      | Status              | int      | 10                | False                   |             |
| 8      | Initiator           | varchar  | 12                | False                   |             |
| 9      | CreatedOn           | datetime |                   | False                   |             |
| 10     | CreatedBy           | int      | 10                | False                   |             |
| 11     | UpdatedOn           | datetime |                   | True                    |             |
| 12     | UpdatedBy           | int      | 10                | True                    |             |
| 13     | InvIssue            | nvarchar | 2000              | True                    |             |
| 14     | InvProcess          | nvarchar | 2000              | True                    |             |
| 15     | InvRootCauseDetails | nvarchar | 2000              | True                    |             |
| 16     | InvActions          | nvarchar | 2000              | True                    |             |
| 17     | InvDueDate          | datetime |                   | True                    |             |
| 18     | InvModDate          | datetime |                   | True                    |             |
| 19     | ImplVerifiedBy      | varchar  | 12                | True                    |             |
| 20     | ImplVerifiedDate    | datetime |                   | True                    |             |
| 21     | ImplAudit           | smallint |                   | False                   |             |
| 22     | ImplAuditDate       | datetime |                   | True                    |             |
| 23     | ImplDueDate         | datetime |                   | True                    |             |
| 24     | ImplState           | smallint |                   | False                   |             |
| 25     | ImplReason          | nvarchar | 2000              | True                    |             |
| 26     | ImplModDate         | datetime |                   | True                    |             |
| 27     | CheckPerformedBy    | varchar  | 12                | True                    |             |
| 28     | CheckIssueState     | nvarchar | 255               | True                    |             |
| 29     | CheckModDate        | datetime |                   | True                    |             |
| 30     | CheckDueDate        | datetime |                   | True                    |             |
| 31     | CheckFollowUp       | nvarchar | 2000              | True                    |             |
| 32     | CheckAction         | nvarchar | 2000              | True                    |             |
| 33     | SignUser            | int      | 10                | True                    |             |
| 34     | SignDate            | datetime |                   | True                    |             |
| 35     | SignReason          | nvarchar | 1024              | True                    |             |

## CIM\_CAPARootCauses

### Primary Keys

- Id

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-----------|----------|-------------------|-------------------------|-------------|
| 1      | Id        | int      | 10                | False                   |             |
| 2      | ReportId  | int      | 10                | False                   |             |
| 3      | ReportId  | int      | 10                | False                   |             |
| 4      | RootCause | nvarchar | 50                | False                   |             |
| 5      | CreatedOn | datetime |                   | False                   |             |
| 6      | CreatedBy | int      | 10                | False                   |             |
| 7      | UpdatedOn | datetime |                   | True                    |             |
| 8      | UpdatedBy | int      | 10                | True                    |             |

## CIM\_CAPAStepApprovers

### Primary Keys

- Id

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------------|----------|-------------------|-------------------------|-------------|
| 1      | Id          | int      | 10                | False                   |             |
| 2      | ReportId    | int      | 10                | False                   |             |
| 3      | ReportId    | int      | 10                | False                   |             |
| 4      | Step        | int      | 10                | False                   |             |
| 5      | Approver    | varchar  | 12                | False                   |             |
| 6      | ApproveDate | datetime |                   | True                    |             |
| 7      | CreatedOn   | datetime |                   | False                   |             |
| 8      | CreatedBy   | int      | 10                | False                   |             |
| 9      | UpdatedOn   | datetime |                   | True                    |             |
| 10     | UpdatedBy   | int      | 10                | True                    |             |

## CIM\_CollectionGroups

### Collection Groups

### Primary Keys

- Id

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------------|----------|-------------------|-------------------------|-------------|
| 1      | Id          | bigint   |                   | False                   | Id          |
| 2      | Name        | nvarchar | 255               | False                   | Name        |
| 3      | Description | nvarchar | 1024              | True                    | Description |
| 4      | OwnerId     | int      | 10                | True                    | Owner Id    |
| 5      | Report      | nvarchar | 255               | True                    | Report      |

|    |            |          |     |       |                 |
|----|------------|----------|-----|-------|-----------------|
| 6  | CreatedOn  | datetime |     | False | Created On      |
| 7  | CreatedBy  | int      | 10  | True  | Created By      |
| 8  | UpdatedOn  | datetime |     | True  | Updated On      |
| 9  | UpdatedBy  | int      | 10  | True  | Updated By      |
| 10 | CTReport   | nvarchar | 255 | True  |                 |
| 11 | IsReviewed | smallint |     | False | IsReviewed flag |

## CIM\_CollectionGroupSamples

Collection Group Samples

### Primary Keys

- CollectionGroupId
- SampNo

| Sr.No. | Name              | Type     | Size (Characters) | Allow Null (True/False) | Description  |
|--------|-------------------|----------|-------------------|-------------------------|--------------|
| 1      | CollectionGroupId | bigint   |                   | False                   | ID           |
| 2      | CollectionGroupId | bigint   |                   | False                   | ID           |
| 3      | SampNo            | varchar  | 7                 | False                   | Sample No    |
| 4      | SampNo            | varchar  | 7                 | False                   | Sample No    |
| 5      | SampOrder         | int      | 10                | False                   | Sample Order |
| 6      | Report            | nvarchar | 255               | True                    | Report       |
| 7      | CreatedOn         | datetime |                   | False                   |              |
| 8      | CreatedBy         | int      | 10                | False                   |              |
| 9      | UpdatedOn         | datetime |                   | True                    |              |
| 10     | UpdatedBy         | int      | 10                | True                    |              |
| 11     | CollectionStatus  | int      | 10                | False                   |              |
| 12     | SignUser          | int      | 10                | True                    |              |
| 13     | SignReason        | nvarchar | 1024              | True                    |              |
| 14     | SignDate          | datetime |                   | True                    |              |

## CIM\_InstMethods

Inst Methods

### Primary Keys

- InstCode
- Method

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------|----------|-------------------|-------------------------|-------------|
| 1      | InstCode | varchar  | 24                | False                   | Inst Code   |
| 2      | Method   | varchar  | 255               | False                   | Method      |
| 3      | ExpDate  | datetime |                   | True                    | Expiry Date |

## CIM\_NotificationActions

### Primary Keys

- NotificationId
- ActionId

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------------|----------|-------------------|-------------------------|-------------|
| 1      | NotificationId | bigint   |                   | False                   |             |
| 2      | NotificationId | bigint   |                   | False                   |             |
| 3      | ActionId       | int      | 10                | False                   |             |
| 4      | ActionId       | int      | 10                | False                   |             |
| 5      | Completed      | smallint |                   | False                   |             |

## CIM\_Notifications

### Primary Keys

- Id

| Sr.No. | Name               | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|--------------------|----------|-------------------|-------------------------|-------------|
| 1      | Id                 | bigint   |                   | False                   |             |
| 2      | Header             | nvarchar | 512               | False                   |             |
| 3      | Text               | nvarchar | 2000              | True                    |             |
| 4      | NotificationType   | int      | 10                | False                   |             |
| 5      | ObjectType         | int      | 10                | True                    |             |
| 6      | ObjectId           | varchar  | 255               | True                    |             |
| 7      | NotificationStatus | int      | 10                | False                   |             |
| 8      | RecipientUserId    | int      | 10                | True                    |             |
| 9      | RecipientGroupId   | varchar  | 24                | True                    |             |
| 10     | ApplicationId      | int      | 10                | True                    |             |
| 11     | CreatedOn          | datetime |                   | False                   |             |
| 12     | UpdatedOn          | datetime |                   | True                    |             |
| 13     | NotificationKey    | varchar  | 300               | True                    |             |

## CIM\_Project

### Primary Keys

- ID

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|--------------|----------|-------------------|-------------------------|-------------|
| 1      | ID           | int      | 10                | False                   |             |
| 2      | NAME         | nvarchar | 255               | False                   |             |
| 3      | DESCRIPTION  | nvarchar | 1024              | True                    |             |
| 4      | PROJECT_TYPE | varchar  | 50                | True                    |             |
| 5      | STARTDATE    | datetime |                   | True                    |             |

|    |                    |          |     |       |  |
|----|--------------------|----------|-----|-------|--|
| 6  | ENDDATE            | datetime |     | True  |  |
| 7  | CURRENT_STA<br>TE  | varchar  | 50  | True  |  |
| 8  | CUSTOMER           | nvarchar | 255 | True  |  |
| 9  | PARENTID           | int      | 10  | True  |  |
| 10 | SORTORDER          | int      | 10  | True  |  |
| 11 | CREATEDON          | datetime |     | False |  |
| 12 | CREATEDBY          | int      | 10  | True  |  |
| 13 | UPDATEDON          | datetime |     | True  |  |
| 14 | UPDATEDBY          | int      | 10  | True  |  |
| 15 | LEGACY_PROJ<br>ECT | varchar  | 24  | True  |  |

## CIM\_ProjectUserFields

### Primary Keys

- PROJECTID

| Sr.No. | Name      | Type | Size<br>(Characters) | Allow Null<br>(True/False) | Description |
|--------|-----------|------|----------------------|----------------------------|-------------|
| 1      | PROJECTID | int  | 10                   | False                      |             |
| 2      | PROJECTID | int  | 10                   | False                      |             |

## CIM\_SampleLog

### Primary Keys

- Id

| Sr.No. | Name         | Type     | Size<br>(Characters) | Allow Null<br>(True/False) | Description |
|--------|--------------|----------|----------------------|----------------------------|-------------|
| 1      | Id           | int      | 10                   | False                      |             |
| 2      | SampleId     | varchar  | 7                    | False                      |             |
| 3      | CurrentState | varchar  | 50                   | True                       |             |
| 4      | ChangedOn    | datetime |                      | False                      |             |

## CIM\_Schedule

### Primary Keys

- Id

| Sr.No. | Name          | Type    | Size<br>(Characters) | Allow Null<br>(True/False) | Description |
|--------|---------------|---------|----------------------|----------------------------|-------------|
| 1      | Id            | bigint  |                      | False                      |             |
| 2      | ApplicationId | int     | 10                   | True                       |             |
| 3      | ObjectType    | int     | 10                   | True                       |             |
| 4      | ObjectId      | varchar | 255                  | True                       |             |
| 5      | Type          | int     | 10                   | False                      |             |

|    |             |          |      |       |  |
|----|-------------|----------|------|-------|--|
| 6  | Active      | smallint |      | False |  |
| 7  | Text        | nvarchar | 2000 | True  |  |
| 8  | Header      | nvarchar | 512  | False |  |
| 9  | SendMail    | smallint |      | False |  |
| 10 | SendPush    | smallint |      | False |  |
| 11 | StartDate   | datetime |      | False |  |
| 12 | EndDate     | datetime |      | True  |  |
| 13 | Period      | int      | 10   | True  |  |
| 14 | PeriodType  | int      | 10   | False |  |
| 15 | LastRunTime | datetime |      | True  |  |
| 16 | CreatedBy   | int      | 10   | False |  |
| 17 | CreatedOn   | datetime |      | False |  |
| 18 | UpdatedBy   | int      | 10   | True  |  |
| 19 | UpdatedOn   | datetime |      | True  |  |

## CIM\_ScheduleAction

### Primary Keys

- ScheduleId
- ActionId

| Sr.No. | Name       | Type   | Size (Characters) | Allow Null (True/False) | Description |
|--------|------------|--------|-------------------|-------------------------|-------------|
| 1      | ScheduleId | bigint |                   | False                   |             |
| 2      | ScheduleId | bigint |                   | False                   |             |
| 3      | ActionId   | int    | 10                | False                   |             |
| 4      | ActionId   | int    | 10                | False                   |             |

## CIM\_ScheduledPrograms

### Primary Keys

- Id

| Sr.No. | Name          | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|---------------|----------|-------------------|-------------------------|-------------|
| 1      | Id            | int      | 10                | False                   |             |
| 2      | ScheduleId    | int      | 10                | False                   |             |
| 3      | Program       | varchar  | 4096              | False                   |             |
| 4      | ProgramParams | varchar  | 255               | True                    |             |
| 5      | RequiredTime  | datetime |                   | True                    |             |
| 6      | RunTime       | datetime |                   | True                    |             |

## CIM\_ScheduleRecipientGroup

### Primary Keys

- ScheduleId
- UserGroup

| Sr.No. | Name       | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|------------|---------|-------------------|-------------------------|-------------|
| 1      | ScheduleId | bigint  |                   | False                   |             |
| 2      | ScheduleId | bigint  |                   | False                   |             |
| 3      | UserGroup  | varchar | 24                | False                   |             |

## CIM\_ScheduleRecipientUser

### Primary Keys

- ScheduleId
- UserId

| Sr.No. | Name       | Type   | Size (Characters) | Allow Null (True/False) | Description |
|--------|------------|--------|-------------------|-------------------------|-------------|
| 1      | ScheduleId | bigint |                   | False                   |             |
| 2      | ScheduleId | bigint |                   | False                   |             |
| 3      | UserId     | int    | 10                | False                   |             |
| 4      | UserId     | int    | 10                | False                   |             |

## CIM\_Settings

### Primary Keys

- Key

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-----------|----------|-------------------|-------------------------|-------------|
| 1      | Key       | nvarchar | 255               | False                   |             |
| 2      | Value     | nvarchar | 2000              | True                    |             |
| 3      | CreatedOn | datetime |                   | False                   |             |
| 4      | CreatedBy | int      | 10                | True                    |             |
| 5      | UpdatedOn | datetime |                   | True                    |             |
| 6      | UpdatedBy | int      | 10                | True                    |             |

## CInv\_Analysis

Analysis details in Inventory Management

### Primary Keys

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description   |
|--------|-------------|----------|-------------------|-------------------------|---------------|
| 1      | SAMPNO      | varchar  | 7                 | False                   | Sample Number |
| 2      | ACODE       | varchar  | 24                | False                   | Analysis Code |
| 3      | ASTATUS     | smallint |                   | True                    | Status        |
| 4      | STATUSCOUNT | smallint |                   | True                    |               |
|        | ER          |          |                   |                         |               |

## CInv\_Certifications

Certifications in Inventory Management

### Primary Keys

- CertificationDate
- Transaction\_ID
- Item\_ID
- Lot\_No

| Sr.No. | Name                   | Type     | Size (Characters) | Allow Null (True/False) | Description             |
|--------|------------------------|----------|-------------------|-------------------------|-------------------------|
| 1      | CertificationDate      | datetime |                   | False                   | Certification Date      |
| 2      | Transaction_ID         | int      | 10                | False                   | Transaction Identifier  |
| 3      | Item_ID                | int      | 10                | False                   | Item Identifier         |
| 4      | Lot_No                 | varchar  | 24                | False                   | Lot number              |
| 5      | NextCertification Date | datetime |                   | False                   | Next certification date |
| 6      | CreationTime           | datetime |                   | False                   | Creation time           |
| 7      | Creator                | int      | 10                | False                   | Creator                 |

## CInv\_ItemAttachments

Item attachment details in Inventory Management

### Primary Keys

- Item\_ID
- Attachment\_Type
- Attachment\_ID

| Sr.No. | Name             | Type    | Size (Characters) | Allow Null (True/False) | Description           |
|--------|------------------|---------|-------------------|-------------------------|-----------------------|
| 1      | Item_ID          | int     | 10                | False                   | Item Identifier       |
| 2      | Attachment_Type  | varchar | 100               | False                   | Attachment Type       |
| 3      | Attachment_ID    | int     | 10                | False                   | Attachment Identifier |
| 4      | AttachedFileName | varchar | 1000              | True                    | Attached File name    |
| 5      | Comments         | varchar | 255               | True                    | Comments              |
| 6      | DeleteFlag       | varchar | 1                 | False                   | Start Date            |

## CInv\_ItemMixtureInst

Instrument details related to item mixture

### Primary Keys

- ID

- ItemMixtureMaster\_ID

| Sr.No. | Name                 | Type    | Size (Characters) | Allow Null (True/False) | Description                    |
|--------|----------------------|---------|-------------------|-------------------------|--------------------------------|
| 1      | ID                   | int     | 10                | False                   | Item Identifier                |
| 2      | ItemMixtureMaster_ID | int     | 10                | False                   | Item Mixture Master Identifier |
| 3      | InstrumentType       | varchar | 50                | False                   | Instrument Type                |

## CInv\_ItemMixtureMaster

Item mixture master details in Inventory Management

### Primary Keys

- ID
- Item\_ID

| Sr.No. | Name           | Type    | Size (Characters) | Allow Null (True/False) | Description             |
|--------|----------------|---------|-------------------|-------------------------|-------------------------|
| 1      | ID             | int     | 10                | False                   | Identifier              |
| 2      | MixtureItem_ID | int     | 10                | False                   | Mixture Item Identifier |
| 3      | Item_ID        | int     | 10                | False                   | Item Identifier         |
| 4      | Quantity       | real    |                   | False                   | Quantity                |
| 5      | Unit           | varchar | 50                | True                    | Unit                    |
| 6      | Detail1        | varchar | 4000              | True                    | Detail 1                |
| 7      | Detail2        | varchar | 4000              | True                    | Detail 2                |

## CInv\_Items

Item details in Inventory Management

### Primary Keys

- Item\_ID

| Sr.No. | Name               | Type    | Size (Characters) | Allow Null (True/False) | Description         |
|--------|--------------------|---------|-------------------|-------------------------|---------------------|
| 1      | Item_ID            | int     | 10                | False                   | Item Identifier     |
| 2      | Item_Code          | varchar | 24                | False                   | Item Code           |
| 3      | Item_Name          | varchar | 100               | False                   | Item Name           |
| 4      | Item_Description   | varchar | 255               | True                    | Item Description    |
| 5      | CASNumber          | varchar | 20                | True                    | CAS Number          |
| 6      | NeedsCertification | bit     |                   | False                   | Needs Certification |
| 7      | HasShelfLife       | bit     |                   | False                   | Has Shelf Life      |
| 8      | ShelfLife          | real    |                   | True                    | Shelf Life          |
| 9      | ShelfLifeUnit      | varchar | 50                | True                    | Shelf Life Unit     |
| 10     | Item_Type          | varchar | 50                | False                   | Item Type           |
| 11     | StorageUnit        | varchar | 50                | False                   | Storage Unit        |
| 12     | ConsumptionUnit    | varchar | 50                | False                   | Consumption Unit    |
| 13     | ConversionFactor   | real    |                   | False                   | Conversion          |

|    | r                     |          |      |       | Factor  |
|----|-----------------------|----------|------|-------|---|
| 14 | RecommendedStock      | real     |      | False | Recommended Stock                               |
| 15 | AllowableStock        | real     |      | False | Allowable Stock                                 |
| 16 | ThresholdValue        | real     |      | False | Threshold Value                                 |
| 17 | WarningDescription    | varchar  | 255  | True  | Warning Description                             |
| 18 | PrecautionDescription | varchar  | 255  | True  | Precaution Description                          |
| 19 | Manufacturer          | varchar  | 100  | True  | Manufacturer                                    |
| 20 | CreationTime          | datetime |      | True  | Creation Time                                   |
| 21 | Creator               | int      | 10   | False | Creator   |
| 22 | DeleteFlag            | bit      |      | False | Delete Flag                                     |
| 23 | Comments              | varchar  | 255  | True  | Comments  |
| 24 | MSDS_ID               | varchar  | 24   | True  | SDS Identifier                                  |
| 25 | MSDS_ReviewedDate     | datetime |      | True  | SDS Review Date                                 |
| 26 | MSDS_ExpiryDate       | datetime |      | True  | SDS Expiry Date                                 |
| 27 | MSDS_Location         | varchar  | 1000 | True  | SDS Location                                    |
| 28 | MSDS_Comments         | varchar  | 255  | True  | SDS Comments                                    |
| 29 | ExpiryAlertDays       | int      | 10   | True  | Expiry Alert Days                               |
| 30 | ExpiryDays            | int      | 10   | True  | Expiry Days                                     |
| 31 | IsMixture             | bit      |      | True  | Is Mixture                                      |
| 32 | SINFOFRM              | varchar  | 24   | True  | SI Info Form                                    |
| 33 | LabelFormatID         | int      | 10   | True  | Label Format Identifier                         |
| 34 | LabelPrefix           | varchar  | 50   | False | Label Prefix                                    |
| 35 | SOP                   | varchar  | 4000 | True  | SOP   |
| 36 | GRADE                 | varchar  | 40   | True  | Grade of an Item (Container, Batch or Material) |

## CInv\_ItemsSafetyInformation

Safety information for items details in Inventory Management

### Primary Keys

- ID
- Item\_ID

| Sr.No. | Name    | Type    | Size (Characters) | Allow Null (True/False) | Description     |
|--------|---------|---------|-------------------|-------------------------|-----------------|
| 1      | ID      | int     | 10                | False                   | Identifier      |
| 2      | Item_ID | int     | 10                | False                   | Item Identifier |
| 3      | Type    | varchar | 15                | False                   | Type            |
| 4      | Name    | varchar | 15                | False                   | Name            |
| 5      | Value   | bit     |                   | False                   | Value           |

## CInv\_ItemStock

Item stock details in Inventory Management

### Primary Keys

- ID

| Sr.No. | Name                          | Type     | Size (Characters) | Allow Null (True/False) | Description                      |
|--------|-------------------------------|----------|-------------------|-------------------------|----------------------------------|
| 1      | ID                            | int      | 10                | False                   | Identifier                       |
| 2      | Item_ID                       | int      | 10                | False                   | Item Identifier                  |
| 3      | SL_ID                         | int      | 10                | False                   | Storage Location Identifier      |
| 4      | Lot_No                        | varchar  | 24                | False                   | Lot Number                       |
| 5      | Batch_No                      | varchar  | 24                | True                    | Batch Number                     |
| 6      | Container_ID                  | varchar  | 24                | True                    | Container Identifier             |
| 7      | ExpiryDate                    | datetime |                   | True                    | Expiry Date                      |
| 8      | AvailableQuantity             | real     |                   | False                   | Available Quantity               |
| 9      | QuarantineQuantity            | real     |                   | False                   | Quarantine Quantity              |
| 10     | TotalQuantity                 | real     |                   | False                   | Total Quantity                   |
| 11     | ConsumedQuantity              | real     |                   | False                   | Consumed Quantity                |
| 12     | ReceivedQuantity              | real     |                   | False                   | Received Quantity                |
| 13     | ReconciledQuantity            | real     |                   | False                   | Reconciled Quantity              |
| 14     | Current_State                 | varchar  | 20                | False                   | Current State                    |
| 15     | IsQuarantined                 | bit      |                   | True                    | Is Quarantined                   |
| 16     | ScheduledExpiryDate           | datetime |                   | False                   | Scheduled Expiry date            |
| 17     | Barcode                       | varchar  | 50                | False                   | Barcode                          |
| 18     | Price                         | real     |                   | True                    | Price                            |
| 19     | QC_Sample                     | varchar  | 10                | True                    | QC Sample                        |
| 20     | VerifiedBy                    | varchar  | 20                | True                    | Verified By                      |
| 21     | VerifiedDate                  | datetime |                   | True                    | Verified Date                    |
| 22     | SDS                           | varchar  | 255               | True                    | SDS                              |
| 23     | EXT_Cert_Analysis             | varchar  | 255               | True                    | Ext Cert Analysis                |
| 24     | DeleteFlag                    | bit      |                   | True                    | Delete Flag                      |
| 25     | PhysicalReconcileVerifiedBy   | varchar  | 20                | True                    | Physical Reconcile Verified By   |
| 26     | PhysicalReconcileVerifiedDate | datetime |                   | True                    | Physical Reconcile Verified Date |
| 27     | PREPARED_BY                   | varchar  | 40                | True                    | Prepared By                      |
| 28     | SupplierID                    | int      | 10                | True                    | Supplier Id                      |
| 29     | PARENTSTOCK_ID                | int      | 10                | True                    |                                  |
| 30     | Manufacturer                  | varchar  | 100               | True                    | Manufacturer details             |
| 31     | DESCRIPTION                   | varchar  | 100               | True                    | Item Stock Description           |
| 32     | LASTUPDATED_DATE              | datetime |                   | True                    |                                  |

## CInv\_ItemStockMixture

Item stock mixture details in Inventory Management

### Primary Keys

- ID

| Sr.No. | Name               | Type    | Size (Characters) | Allow Null (True/False) | Description                   |
|--------|--------------------|---------|-------------------|-------------------------|-------------------------------|
| 1      | ID                 | int     | 10                | False                   | Identifier                    |
| 2      | MixtureItemStockID | int     | 10                | False                   | Mixture Item Stock Identifier |
| 3      | ItemStockID        | int     | 10                | False                   | Item Stock Identifier         |
| 4      | Quantity           | real    |                   | False                   | Quantity                      |
| 5      | Unit               | varchar | 50                | True                    | Unit                          |
| 6      | Detail1            | varchar | 4000              | True                    | Detail 1                      |
| 7      | Detail2            | varchar | 4000              | True                    | Detail 2                      |

## CInv\_ItemStockMixtureInst

Item stock mixture details in Inventory Management

### Primary Keys

- ID
- ItemStockMixtureID

| Sr.No. | Name               | Type    | Size (Characters) | Allow Null (True/False) | Description                   |
|--------|--------------------|---------|-------------------|-------------------------|-------------------------------|
| 1      | ID                 | int     | 10                | False                   | Identifier                    |
| 2      | ItemStockMixtureID | int     | 10                | False                   | Mixture Item Stock Identifier |
| 3      | InstCode           | varchar | 24                | False                   | Item Stock Identifier         |

## CInv\_ItemSuppliers

Item supplier details in Inventory Management

### Primary Keys

- ID
- Item\_ID
- Supplier\_ID

| Sr.No. | Name        | Type | Size (Characters) | Allow Null (True/False) | Description     |
|--------|-------------|------|-------------------|-------------------------|-----------------|
| 1      | ID          | int  | 10                | False                   | Identifier      |
| 2      | Item_ID     | int  | 10                | False                   | Item Identifier |
| 3      | Supplier_ID | int  | 10                | False                   | Supplier        |

|   |             |     |  |      | Identifier   |
|---|-------------|-----|--|------|--------------|
| 4 | DeleteFlag  | bit |  | True | Delete Flag  |
| 5 | IsPreferred | bit |  | True | Is Preferred |

## CInv\_KitItems

Items related to kit details in Inventory Management

### Primary Keys

- ID
- Kit\_ID
- Item\_ID

| Sr.No. | Name                | Type | Size (Characters) | Allow Null (True/False) | Description          |
|--------|---------------------|------|-------------------|-------------------------|----------------------|
| 1      | ID                  | int  | 10                | False                   | Identifier           |
| 2      | Kit_ID              | int  | 10                | False                   | Kit Identifier       |
| 3      | Item_ID             | int  | 10                | False                   | Item Identifier      |
| 4      | ConsumptionQuantity | real |                   | False                   | Consumption Quantity |
| 5      | DeleteFlag          | bit  |                   | False                   | Delete Flag          |

## CInv\_Kits

Kit details in Inventory Management

### Primary Keys

- Kit\_ID

| Sr.No. | Name            | Type     | Size (Characters) | Allow Null (True/False) | Description     |
|--------|-----------------|----------|-------------------|-------------------------|-----------------|
| 1      | Kit_ID          | int      | 10                | False                   | Kit identifier  |
| 2      | Kit_Code        | varchar  | 24                | False                   | Kit Code        |
| 3      | Kit_Name        | varchar  | 50                | False                   | Kit Name        |
| 4      | Kit_Description | varchar  | 255               | True                    | Kit Description |
| 5      | DeleteFlag      | bit      |                   | False                   | Delete Flag     |
| 6      | CreationTime    | datetime |                   | False                   | Creation time   |
| 7      | Creator         | int      | 10                | False                   | Creator         |

## CInv\_Picklists

Pick list details in Inventory Management

### Primary Keys

- PLName
- PLItemNo

| Sr.No. | Name | Type | Size | Allow Null | Description |
|--------|------|------|------|------------|-------------|
|        |      |      |      |            |             |

|   |          |         | <b>(Characters)</b> | <b>(True/False)</b> |                       |
|---|----------|---------|---------------------|---------------------|-----------------------|
| 1 | PLName   | varchar | 20                  | False               | Pick list name        |
| 2 | PLItemNo | int     | 10                  | False               | Pick list item number |
| 3 | PLItem   | varchar | 50                  | False               | Pick list item        |
| 4 | PLDescr  | varchar | 50                  | True                | Pick list description |
| 5 | hSec     | int     | 10                  | True                | Security Handle       |

## CInv\_PurchaseReq

Purchase Requisition in Inventory Management

### Primary Keys

- ID

| <b>Sr.No.</b> | <b>Name</b>         | <b>Type</b> | <b>Size (Characters)</b> | <b>Allow Null (True/False)</b> | <b>Description</b>          |
|---------------|---------------------|-------------|--------------------------|--------------------------------|-----------------------------|
| 1             | ID                  | int         | 10                       | False                          | Identifier                  |
| 2             | PRNO                | varchar     | 20                       | False                          | Purchase Requisition Number |
| 3             | RequestedBy         | varchar     | 12                       | True                           | Requested By                |
| 4             | RequestDate         | datetime    |                          | True                           | Request Date                |
| 5             | SpecialInstructions | varchar     | 4000                     | True                           | Special Instructions        |
| 6             | ExpectedReceiptDate | datetime    |                          | True                           | Expected Receipt Date       |
| 7             | EstimatedCost       | real        |                          | True                           | Estimated Cost              |
| 8             | CreationTime        | datetime    |                          | False                          | Creation Time               |
| 9             | Current_State       | varchar     | 20                       | True                           | Current State               |
| 10            | OrderNumber         | varchar     | 20                       | True                           | Order Number                |
| 11            | OrderDate           | datetime    |                          | True                           | Order Date                  |

## CInv\_PurchaseReqDet

Purchase Requisition details in Inventory Management

### Primary Keys

- ID
- PurchaseReqID
- Item\_ID
- SupplierID

| <b>Sr.No.</b> | <b>Name</b>   | <b>Type</b> | <b>Size (Characters)</b> | <b>Allow Null (True/False)</b> | <b>Description</b>              |
|---------------|---------------|-------------|--------------------------|--------------------------------|---------------------------------|
| 1             | ID            | int         | 10                       | False                          | Identifier                      |
| 2             | PurchaseReqID | int         | 10                       | False                          | Purchase Requisition Identifier |
| 3             | Item_ID       | int         | 10                       | False                          | Item Identifier                 |
| 4             | Lot_No        | varchar     | 24                       | True                           |                                 |

|   |                  |          |    |       |                     |
|---|------------------|----------|----|-------|---------------------|
| 5 | ReceivedQuantity | real     |    | True  | Received Quantity   |
| 6 | ExpectedQuantity | real     |    | True  | Expected Quantity   |
| 7 | SupplierID       | int      | 10 | False | Supplier Identifier |
| 8 | Status           | varchar  | 20 | True  | Status              |
| 9 | CreationTime     | datetime |    | False | Creation Time       |

## CInv\_ReceiptItemPrice

Receipt item price details in Inventory Management

### Primary Keys

- Transaction\_ID
- Item\_ID

| Sr.No. | Name           | Type | Size (Characters) | Allow Null (True/False) | Description            |
|--------|----------------|------|-------------------|-------------------------|------------------------|
| 1      | Transaction_ID | int  | 10                | False                   | Transaction Identifier |
| 2      | Item_ID        | int  | 10                | False                   | Item Identifier        |
| 3      | Price          | real |                   | False                   | Price                  |

## CInv\_Sample

Sample details in Inventory Management

### Primary Keys

- ID
- ItemStockID
- KitID

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description                 |
|--------|-------------|----------|-------------------|-------------------------|-----------------------------|
| 1      | ID          | int      | 10                | False                   | Identifier                  |
| 2      | SampleNo    | varchar  | 7                 | False                   | Sample Number               |
| 3      | ItemStockID | int      | 10                | False                   | Item Stock Identifier       |
| 4      | SL_ID       | int      | 10                | False                   | Storage Location Identifier |
| 5      | Lot_No      | varchar  | 24                | False                   | Lot Number                  |
| 6      | ACode       | varchar  | 24                | False                   | Analysis Code               |
| 7      | KitID       | int      | 10                | False                   | Kit Identifier              |
| 8      | CreateTime  | datetime |                   | False                   | Creation Time               |
| 9      | Quantity    | real     |                   | False                   | Quantity                    |

## CInv\_StorageLocations

Storage location details in Inventory Management

### Primary Keys

- SL\_ID

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description                        |
|--------|----------------|----------|-------------------|-------------------------|------------------------------------|
| 1      | SL_ID          | int      | 10                | False                   | Storage Location Identifier        |
| 2      | SL_Name        | varchar  | 50                | False                   | Storage Location Name              |
| 3      | SL_FullName    | varchar  | 1000              | False                   | Storage Location Full Name         |
| 4      | SL_Description | varchar  | 255               | True                    | Storage Location Description       |
| 5      | SL_ParentID    | int      | 10                | False                   | Storage Location Parent Identifier |
| 6      | CanConsume     | bit      |                   | True                    | Can consume                        |
| 7      | CreationTime   | datetime |                   | True                    | Creation Time                      |
| 8      | Creator        | int      | 10                | False                   | Creator                            |
| 9      | DeleteFlag     | bit      |                   | True                    | Delete Flag                        |

## CInv\_Suppliers

Supplier details in Inventory Management

### Primary Keys

- Supplier\_ID

| Sr.No. | Name          | Type     | Size (Characters) | Allow Null (True/False) | Description         |
|--------|---------------|----------|-------------------|-------------------------|---------------------|
| 1      | Supplier_ID   | int      | 10                | False                   | Supplier Identifier |
| 2      | Supplier_Code | varchar  | 24                | False                   | Supplier Code       |
| 3      | Supplier_Name | varchar  | 100               | True                    | Supplier Name       |
| 4      | Address1      | varchar  | 60                | True                    | Address 1           |
| 5      | Address2      | varchar  | 60                | True                    | Address 2           |
| 6      | City          | varchar  | 60                | True                    | City                |
| 7      | State         | varchar  | 60                | True                    | State               |
| 8      | Country       | varchar  | 60                | True                    | Country             |
| 9      | Zip           | varchar  | 15                | True                    | Zip                 |
| 10     | Telephone     | varchar  | 24                | True                    | Telephone           |
| 11     | Fax           | varchar  | 24                | True                    | Fax                 |
| 12     | Email         | varchar  | 100               | True                    | Email               |
| 13     | ContactPerson | varchar  | 100               | True                    | Contact Person      |
| 14     | CreationTime  | datetime |                   | True                    | Contact Time        |
| 15     | Creator       | int      | 10                | False                   | Creator             |
| 16     | DeleteFlag    | bit      |                   | False                   | Delete Flag         |

## CInv\_TestConfig

Test Config in Inventory Management

### Primary Keys

- Config\_ID

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description        |
|--------|--------------|----------|-------------------|-------------------------|--------------------|
| 1      | Config_ID    | int      | 10                | False                   | Config Identifier  |
| 2      | ACODE        | varchar  | 24                | False                   | Analysis Code      |
| 3      | Config_Code  | varchar  | 24                | False                   | Configuration Code |
| 4      | CreationTime | datetime |                   | False                   | Creation Time      |
| 5      | Creator      | int      | 10                | False                   | Creator            |
| 6      | DeleteFlag   | bit      |                   | False                   | Delete Flag        |

## CInv\_TestConfigDetails

Test Config details in Inventory Management

### Primary Keys

- ID
- Config\_ID
- Kit\_ID

| Sr.No. | Name       | Type | Size (Characters) | Allow Null (True/False) | Description        |
|--------|------------|------|-------------------|-------------------------|--------------------|
| 1      | ID         | int  | 10                | False                   | Config Identifier  |
| 2      | Config_ID  | int  | 10                | False                   | Analysis Code      |
| 3      | Kit_ID     | int  | 10                | False                   | Configuration Code |
| 4      | SL_ID      | int  | 10                | False                   |                    |
| 5      | DeleteFlag | bit  |                   | False                   | Delete Flag        |

## CInv\_Transaction

Transaction details in Inventory Management

### Primary Keys

- Transaction\_ID

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description            |
|--------|------------------|----------|-------------------|-------------------------|------------------------|
| 1      | Transaction_ID   | int      | 10                | False                   | Transaction Identifier |
| 2      | Transaction_Date | datetime |                   | False                   | Transaction Date       |
| 3      | TransactionType  | varchar  | 24                | False                   | Transaction Type       |

|    |                    |          |     |       |                            |
|----|--------------------|----------|-----|-------|----------------------------|
| 4  | VoucherCode        | varchar  | 24  | True  | Voucher Code               |
| 5  | IssuingAgentID     | int      | 10  | False | Issuing Agent Identifier   |
| 6  | IssuingAgentType   | varchar  | 150 | True  | Issuing Agent Type         |
| 7  | ReceivingAgentID   | int      | 10  | False | Receiving Agent Identifier |
| 8  | ReceivingAgentType | varchar  | 150 | True  | Receiving Agent Type       |
| 9  | Narration          | varchar  | 255 | True  | Narration                  |
| 10 | CreationTime       | datetime |     | False | Creation Time              |
| 11 | Creator            | int      | 10  | False | Creator                    |

## CInv\_TransactionItems

Items associated with transaction in Inventory Management

### Primary Keys

- ID
- Transaction\_ID

| Sr.No. | Name           | Type    | Size (Characters) | Allow Null (True/False) | Description            |
|--------|----------------|---------|-------------------|-------------------------|------------------------|
| 1      | ID             | int     | 10                | False                   | Identifier             |
| 2      | Transaction_ID | int     | 10                | False                   | Transaction Identifier |
| 3      | AgentType      | varchar | 150               | True                    | Agent Type             |
| 4      | AgentID        | int     | 10                | False                   | Agent Identifier       |
| 5      | ItemStockID    | int     | 10                | False                   | Item Stock Identifier  |
| 6      | Quantity       | real    |                   | False                   | Quantity               |

## CMDP\_EXPORT\_LOOKUP

Export Lookup details related to CMDP in Inventory Management

### Primary Keys

- ID

| Sr.No. | Name        | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------------|---------|-------------------|-------------------------|-------------|
| 1      | ID          | int     | 10                | False                   | Identifier  |
| 2      | Code        | varchar | 10                | False                   | Code        |
| 3      | Description | varchar | 500               | False                   | Description |

## COAANLS

Analytes listing for defined Certificate of Analysis

**Primary Keys**

- COANUMBER
- COAANALYTE

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description                                 |
|--------|------------|----------|-------------------|-------------------------|---|
| 1      | COANUMBER  | int      | 10                | False                   | COA Number                                  |
| 2      | COAANALYTE | varchar  | 40                | False                   | Analyte Abbreviation                        |
| 3      | ANLNUMB    | smallint |                   | False                   | Analyte Number (unique within a COA Number) |
| 4      | COARESULT  | varchar  | 20                | True                    | Result Status                               |
| 5      | COAUNIT    | varchar  | 14                | True                    | Unit  |
| 6      | COASPEC    | varchar  | 20                | True                    | Specification                               |
| 7      | SPECTYPE   | varchar  | 20                | False                   | Specification Type                          |
| 8      | VAL1       | varchar  | 14                | True                    | Value 1                                     |
| 9      | VAL2       | varchar  | 14                | True                    | Value 2                                     |
| 10     | INSPEC     | smallint |                   | False                   |   |
| 11     | ACODE      | varchar  | 24                | True                    | Analysis Code                               |
| 12     | ANALYTE    | varchar  | 100               | True                    | Analyte Name                                |
| 13     | METREF     | varchar  | 20                | True                    | Method Reference                            |
| 14     | hSec       | int      | 10                | False                   | Security Handle                             |

**COAHEAD**

Listing of all COA reports generated and its details

**Primary Keys**

- COANUMBER

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description         |
|--------|-----------|----------|-------------------|-------------------------|---------------------|
| 1      | COANUMBER | int      | 10                | False                   | COA Number          |
| 2      | COADATE   | datetime |                   | True                    | COA generation Date |
| 3      | COAUSER   | varchar  | 12                | True                    | COA generated User  |
| 4      | CUSTBASE  | varchar  | 24                | False                   | Customer Base       |
| 5      | SAMPNOS   | varchar  | 255               | True                    | Sample ID           |
| 6      | PASSED    | smallint |                   | False                   | Passed Flag         |
| 7      | SCORE     | int      | 10                | False                   | Evaluation Score    |
| 8      | PRODDESCR | varchar  | 32                | True                    | Product Description |
| 9      | CUSTOMER  | varchar  | 26                | True                    | Customer name       |
| 10     | PRODID    | varchar  | 16                | True                    | Product ID          |
| 11     | CUSTADD1  | varchar  | 30                | True                    | Customer Address 1  |
| 12     | CUSTADD2  | varchar  | 30                | True                    | Customer Address 2  |
| 13     | CUSTADD3  | varchar  | 30                | True                    | Customer Address 3  |
| 14     | CUSTADD4  | varchar  | 30                | True                    | Customer            |

|    |            |         |    |       | Address 4              |
|----|------------|---------|----|-------|------------------------|
| 15 | CUSTADD5   | varchar | 30 | True  | Customer Address 5     |
| 16 | ATTN1      | varchar | 30 | True  | Attention Address 1    |
| 17 | ATTN2      | varchar | 30 | True  | Attention Address 2    |
| 18 | ATTN3      | varchar | 30 | True  | Attention Address 3    |
| 19 | ATTN4      | varchar | 30 | True  | Attention Address 4    |
| 20 | ATTN5      | varchar | 30 | True  | Attention Address 5    |
| 21 | RTPROMPT1  | varchar | 30 | True  | Report Prompt 1        |
| 22 | RTVALUE1   | varchar | 30 | True  | Report Value 1         |
| 23 | RTPROMPT2  | varchar | 30 | True  | Report Prompt 2        |
| 24 | RTVALUE2   | varchar | 30 | True  | Report Value 2         |
| 25 | RTPROMPT3  | varchar | 30 | True  | Report Prompt 3        |
| 26 | RTVALUE3   | varchar | 30 | True  | Report Value 3         |
| 27 | RTPROMPT4  | varchar | 30 | True  | Report Prompt 4        |
| 28 | RTVALUE4   | varchar | 30 | True  | Report Value 4         |
| 29 | RTPROMPT5  | varchar | 30 | True  | Report Prompt 5        |
| 30 | RTVALUE5   | varchar | 30 | True  | Report Value 5         |
| 31 | RTPROMPT6  | varchar | 30 | True  | Report Prompt 6        |
| 32 | RTVALUE6   | varchar | 30 | True  | Report Value 6         |
| 33 | RTPROMPT7  | varchar | 30 | True  | Report Prompt 7        |
| 34 | RTVALUE7   | varchar | 30 | True  | Report Value 7         |
| 35 | RTPROMPT8  | varchar | 30 | True  | Report Prompt 8        |
| 36 | RTVALUE8   | varchar | 30 | True  | Report Value 8         |
| 37 | APPROVEDBY | varchar | 30 | True  | COA Approved by (user) |
| 38 | APPRVTITLE | varchar | 30 | True  | Approver Title         |
| 39 | OTHER1     | varchar | 80 | True  | Comments 1             |
| 40 | OTHER2     | varchar | 80 | True  | Comments 2             |
| 41 | OTHER3     | varchar | 80 | True  | Comments 3             |
| 42 | hSec       | int     | 10 | False | Security Handle        |

## COMMENTS

Sample / Analysis comments (The value of the field ACODE is “\_SAMPLE\_” for sample comments and the actual analysis code for analysis comments) - Moved to LabObjComments in 6.4

### Primary Keys

- SAMPNO
- ACODE

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description   |
|--------|----------|---------|-------------------|-------------------------|---|
| 1      | SAMPNO   | varchar | 7                 | False                   | Sample ID   |
| 2      | ACODE    | varchar | 24                | False                   | Analysis Code / “_SAMPLE_” specification – for Sample |
| 3      | COMMENTS | text    | 2147483647        | True                    | Comments  |
| 4      | hSec     | int     | 10                | False                   | Security Handle                                       |

## COMPONENT

### Primary Keys

- COMPONENT\_ID

| Sr.No. | Name          | Type    | Size (Characters) | Allow Null (True/False) | Description          |
|--------|---------------|---------|-------------------|-------------------------|----------------------|
| 1      | COMPONENT_ID  | varchar | 50                | False                   | Component Identifier |
| 2      | OWNER         | varchar | 50                | True                    | Owner                |
| 3      | ASSEMBLY_NAME | varchar | 255               | True                    | Assembly Name        |
| 4      | TYPE_NAME     | varchar | 255               | True                    | Type Name            |
| 5      | METHOD_NAME   | varchar | 255               | True                    | Method Name          |
| 6      | CREATED_BY    | varchar | 50                | True                    | Created By           |
| 7      | CREATED_ON    | varchar | 50                | True                    | Created On           |

## CONTAINER\_ANALYSIS

### Primary Keys

- CONT\_NO
- ACODE

| Sr.No. | Name    | Type    | Size (Characters) | Allow Null (True/False) | Description   |
|--------|---------|---------|-------------------|-------------------------|---------------|
| 1      | CONT_NO | bigint  |                   | False                   | Container No  |
| 2      | ACODE   | varchar | 24                | False                   | Analysis Code |

## CONTAINER\_HEADER

### Primary Keys

- CONT\_NO

| Sr.No. | Name          | Type     | Size (Characters) | Allow Null (True/False) | Description           |
|--------|---------------|----------|-------------------|-------------------------|-----------------------|
| 1      | CONT_NO       | bigint   |                   | False                   | Container Number      |
| 2      | OBJID         | varchar  | 50                | True                    | Object Identifier     |
| 3      | PSSAMPLEID    | bigint   |                   | True                    | PS Sample Identifier  |
| 4      | CONT_CODE     | nvarchar | 50                | True                    | Container Type        |
| 5      | CONT_DESC     | nvarchar | 60                | True                    | Container Description |
| 6      | CONT_PRESERVE | nvarchar | 50                | True                    | Container Preserve    |
| 7      | CONT_ID       | nvarchar | 50                | True                    | Container Identifier  |

|    |                    |          |    |       |   |
|----|--------------------|----------|----|-------|---|
| 8  | CONT_KIT           | nvarchar | 50 | True  | Container Kit                           |
| 9  | CONT_VOLUME        | nvarchar | 50 | True  | Container Volume                        |
| 10 | CONT_LOCATION      | nvarchar | 50 | True  | Container Location                      |
| 11 | CONT_DISPOSAL      | nvarchar | 50 | True  | Container Disposal                      |
| 12 | CONT_DISPOSAL_DATE | datetime |    | True  | Container Disposal Date                 |
| 13 | CONT_DISPOSED      | int      | 10 | True  | Container Disposed                      |
| 14 | CONT_LOCKED        | int      | 10 | True  | Container Locked                        |
| 15 | CONT_LOCKED_USER   | nvarchar | 50 | True  | Container Locked User                   |
| 16 | CONT_LOT_NUM       | nvarchar | 50 | True  | Container Lot Number                    |
| 17 | CONT_MFG_SEQUENCE  | nvarchar | 50 | True  | Container Manufacturing Sequence Number |
| 18 | MODDATE            | datetime |    | True  | ModDate                                 |
| 19 | OBJTYPE            | varchar  | 40 | False | Object Type                             |
| 20 | CONT_SIZE          | nvarchar | 50 | True  | Container Size                          |
| 21 | CONTTYPE           | nvarchar | 50 | True  | Container Type                          |

## CONTAINER\_HISTORY

### Primary Keys

- CONT\_KEY

| Sr.No. | Name                 | Type     | Size (Characters) | Allow Null (True/False) | Description                 |
|--------|----------------------|----------|-------------------|-------------------------|-----------------------------|
| 1      | CONT_KEY             | bigint   |                   | False                   | Container Key               |
| 2      | SAMPNO               | varchar  | 7                 | True                    | Sample Number               |
| 3      | PSSAMPLEID           | bigint   |                   | True                    | PS Sample Identifier        |
| 4      | CONT_NO              | bigint   |                   | True                    | Container Number            |
| 5      | CONT_LOCATION        | nvarchar | 50                | True                    | Container Location          |
| 6      | CONT_RELEASED_BY     | nvarchar | 50                | True                    | Container Released By       |
| 7      | CONT RECEIVED_BY     | nvarchar | 50                | True                    | Container Received By       |
| 8      | CONT_TRANSFER_DATE   | datetime |                   | True                    | Container Transfer Date     |
| 9      | CONT_TRANSFER_REASON | nvarchar | 50                | True                    | Container Transfer Reason   |
| 10     | CONT_MOVE_SIGNATURE  | bigint   |                   | True                    | Container Move Signature    |
| 11     | CONT_MOD_DATE        | datetime |                   | True                    | Container Modification Date |
| 12     | CONT_MOD_USER        | nvarchar | 50                | True                    | Container Modified by User  |

## DATASTORE

The DATASTORE table stores the configuration settings for the Labworks desktop as well as a number of the other programs. The actual configuration information is stored in the Data field as an XML string

### Primary Keys

- Key1
- Key2
- Key3
- Version

| Sr.No. | Name              | Type     | Size (Characters) | Allow Null (True/False) | Description                            |
|--------|-------------------|----------|-------------------|-------------------------|--|
| 1      | Key1              | varchar  | 50                | False                   |  |
| 2      | Key2              | varchar  | 50                | False                   |  |
| 3      | Key3              | varchar  | 50                | False                   |  |
| 4      | Version           | int      | 10                | False                   |  |
| 5      | Data              | text     | 2147483647        | True                    | XML string with configuration settings |
| 6      | DateTime_Created  | datetime |                   | True                    | Creation date/time                     |
| 7      | Created_By        | varchar  | 50                | True                    | Name of person who created the record  |
| 8      | DateTime_Modified | datetime |                   | True                    | Modification date/time                 |
| 9      | Modified_By       | varchar  | 50                | True                    | Name of person who modified the record |
| 10     | hSec              | int      | 10                | False                   | Security Handle                        |
| 11     | CURRENT_STATE     | varchar  | 50                | True                    | Object State                           |

## DCL\_ChartPoints

### Primary Keys

- ChartNumb
- SampleID
- ReplNumber
- PointDateTime

| Sr.No. | Name          | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|---------------|----------|-------------------|-------------------------|-------------|
| 1      | ChartNumb     | int      | 10                | False                   |             |
| 2      | SampleID      | varchar  | 7                 | False                   |             |
| 3      | ReplNumber    | int      | 10                | False                   |             |
| 4      | PointDateTime | datetime |                   | False                   |             |
| 5      | PointValue    | real     |                   | True                    |             |
| 6      | AnalystID     | varchar  | 12                | True                    |             |

|    |              |          |     |       |  |
|----|--------------|----------|-----|-------|--|
| 7  | AnalystName  | varchar  | 50  | True  |  |
| 8  | PointComment | varchar  | 255 | True  |  |
| 9  | ComtUserID   | varchar  | 12  | True  |  |
| 10 | ComtEditDate | datetime |     | True  |  |
| 11 | MODDATE      | datetime |     | True  |  |
| 12 | MODUSER      | varchar  | 12  | True  |  |
| 13 | hSec         | int      | 10  | False |  |

## DCL\_Charts

### Primary Keys

- ChartNumb

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------------|----------|-------------------|-------------------------|-------------|
| 1      | ChartNumb      | int      | 10                | False                   |             |
| 2      | TeamName       | varchar  | 50                | False                   |             |
| 3      | ACODE          | varchar  | 24                | False                   |             |
| 4      | ANLNAME        | varchar  | 100               | False                   |             |
| 5      | ChartType      | varchar  | 50                | True                    |             |
| 6      | ResultUnit     | varchar  | 14                | True                    |             |
| 7      | MaxPoints      | smallint |                   | False                   |             |
| 8      | ChartDateType  | varchar  | 8                 | False                   |             |
| 9      | ChartStatus    | varchar  | 12                | True                    |             |
| 10     | OpenDate       | datetime |                   | True                    |             |
| 11     | ApprID         | varchar  | 12                | True                    |             |
| 12     | ApprDate       | datetime |                   | True                    |             |
| 13     | ApprComment    | varchar  | 255               | True                    |             |
| 14     | MeanValue      | real     |                   | True                    |             |
| 15     | UpperCL        | real     |                   | True                    |             |
| 16     | UpperWL        | real     |                   | True                    |             |
| 17     | LowerCL        | real     |                   | True                    |             |
| 18     | LowerWL        | real     |                   | True                    |             |
| 19     | PriorMeanValue | real     |                   | True                    |             |
| 20     | PriorUpperCL   | real     |                   | True                    |             |
| 21     | PriorUpperWL   | real     |                   | True                    |             |
| 22     | PriorLowerCL   | real     |                   | True                    |             |
| 23     | PriorLowerWL   | real     |                   | True                    |             |
| 24     | MODDATE        | datetime |                   | True                    |             |
| 25     | MODUSER        | varchar  | 12                | True                    |             |
| 26     | hSec           | int      | 10                | False                   |             |

## DCL\_Template

### Primary Keys

- TeamName
- ACODE
- ANLNAME
- ChartType

| Sr.No. | Name | Type | Size | Allow Null | Description |
|--------|------|------|------|------------|-------------|
|--------|------|------|------|------------|-------------|

|    |               |          | <b>(Characters)</b> | <b>(True/False)</b> |  |
|----|---------------|----------|---------------------|---------------------|--|
| 1  | TeamName      | varchar  | 50                  | False               |  |
| 2  | ACODE         | varchar  | 24                  | False               |  |
| 3  | ANLNAME       | varchar  | 100                 | False               |  |
| 4  | ChartType     | varchar  | 50                  | False               |  |
| 5  | ResultUnit    | varchar  | 14                  | True                |  |
| 6  | MaxPoints     | smallint |                     | False               |  |
| 7  | CalcPoints    | smallint |                     | False               |  |
| 8  | ChartDateType | varchar  | 8                   | False               |  |
| 9  | MeanValue     | real     |                     | True                |  |
| 10 | MODDATE       | datetime |                     | True                |  |
| 11 | MODUSER       | varchar  | 12                  | True                |  |
| 12 | hSec          | int      | 10                  | False               |  |

## DCL\_TemplLimit

### Primary Keys

- TeamName
- ACODE
- ANLNAME
- ChartType
- LimitName

| Sr.No. | Name         | Type     | Size<br>(Characters) | Allow Null<br>(True/False) | Description |
|--------|--------------|----------|----------------------|----------------------------|-------------|
| 1      | TeamName     | varchar  | 50                   | False                      |             |
| 2      | ACODE        | varchar  | 24                   | False                      |             |
| 3      | ANLNAME      | varchar  | 100                  | False                      |             |
| 4      | ChartType    | varchar  | 50                   | False                      |             |
| 5      | LimitName    | varchar  | 50                   | False                      |             |
| 6      | Description  | varchar  | 50                   | True                       |             |
| 7      | LimitType    | varchar  | 10                   | False                      |             |
| 8      | RelationType | varchar  | 50                   | True                       |             |
| 9      | Value1       | varchar  | 24                   | True                       |             |
| 10     | Value2       | varchar  | 16                   | True                       |             |
| 11     | MODDATE      | datetime |                      | True                       |             |
| 12     | MODUSER      | varchar  | 12                   | True                       |             |
| 13     | hSec         | int      | 10                   | False                      |             |

## DCL\_TemplPoints

### Primary Keys

- TeamName
- ACODE
- ANLNAME
- ChartType
- SampleID
- ReplNumber

| Sr.No. | Name | Type | Size<br>(Characters) | Allow Null<br>(True/False) | Description |
|--------|------|------|----------------------|----------------------------|-------------|
|        |      |      |                      |                            |             |

|    |               |          |     |       |  |
|----|---------------|----------|-----|-------|--|
| 1  | TeamName      | varchar  | 50  | False |  |
| 2  | ACODE         | varchar  | 24  | False |  |
| 3  | ANLNAME       | varchar  | 100 | False |  |
| 4  | ChartType     | varchar  | 50  | False |  |
| 5  | SampleID      | varchar  | 7   | False |  |
| 6  | ReplNumber    | int      | 10  | False |  |
| 7  | PointDateTime | datetime |     | False |  |
| 8  | PointValue    | real     |     | True  |  |
| 9  | AnalystID     | varchar  | 12  | True  |  |
| 10 | AnalystName   | varchar  | 50  | True  |  |
| 11 | PointComment  | varchar  | 255 | True  |  |
| 12 | ComtUserID    | varchar  | 12  | True  |  |
| 13 | ComtEditDate  | datetime |     | True  |  |
| 14 | MODDATE       | datetime |     | True  |  |
| 15 | MODUSER       | varchar  | 12  | True  |  |
| 16 | hSec          | int      | 10  | False |  |

## DE\_HISTORY

### Primary Keys

- SAMPNO
- ACODE

| Sr.No. | Name                  | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-----------------------|----------|-------------------|-------------------------|-------------|
| 1      | SAMPNO                | varchar  | 7                 | False                   |             |
| 2      | ACODE                 | varchar  | 24                | False                   |             |
| 3      | EXPANSION_COUNT       | int      | 10                | True                    |             |
| 4      | EXPANSION_PREV_SAMPNO | varchar  | 7                 | True                    |             |
| 5      | MODDATE               | datetime |                   | True                    |             |

## DE\_SETUP

### Primary Keys

- EXPANSION\_CODE
- EXPANSION\_INDEX

| Sr.No. | Name            | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|-----------------|---------|-------------------|-------------------------|-------------|
| 1      | EXPANSION_CODE  | varchar | 24                | False                   |             |
| 2      | EXPANSION_INDEX | int     | 10                | False                   |             |
| 3      | EXPANSION_DESC  | varchar | 50                | True                    |             |
| 4      | EXPANSION_LINE  | varchar | 50                | True                    |             |
| 5      | EXPANSION_ACODE | varchar | 24                | True                    |             |

|    |                             |          |    |      |  |
|----|-----------------------------|----------|----|------|--|
| 6  | EXPANSION_ACTIVE            | int      | 10 | True |  |
| 7  | EXPANSION_FREQ              | int      | 10 | True |  |
| 8  | EXPANSION_COUNT             | int      | 10 | True |  |
| 9  | EXPANSION_RESET_TYPE        | varchar  | 24 | True |  |
| 10 | EXPANSION_RESET_PERIOD      | varchar  | 24 | True |  |
| 11 | EXPANSION_RESET_PERIOD_TIME | datetime |    | True |  |
| 12 | EXPANSION_RESET_FREQ        | int      | 10 | True |  |
| 13 | EXPANSION_RESET_TIME        | datetime |    | True |  |
| 14 | EXPANSION_RESET_DAY         | int      | 10 | True |  |
| 15 | EXPANSION_RESET_FIELD       | varchar  | 24 | True |  |
| 16 | EXPANSION_MATERIAL_FIELD    | varchar  | 24 | True |  |
| 17 | EXPANSION_MATERIAL_VALUE    | varchar  | 50 | True |  |
| 18 | EXPANSION_FILE_TYPE         | int      | 10 | True |  |
| 19 | EXPANSION_PREV_VALUE        | varchar  | 50 | True |  |
| 20 | EXPANSION_PREV_SAMPNO       | varchar  | 7  | True |  |
| 21 | EXPANSION_PREV_DATE         | datetime |    | True |  |
| 22 | MODUSER                     | varchar  | 12 | True |  |
| 23 | MODDATE                     | datetime |    | True |  |

## DE\_TRANSITION

### Primary Keys

- EXPANSION\_CODE
- EXPANSION\_LINE
- MATERIAL

| Sr.No. | Name           | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------------|---------|-------------------|-------------------------|-------------|
| 1      | EXPANSION_CODE | varchar | 24                | False                   |             |
| 2      | EXPANSION_LINE | varchar | 50                | False                   |             |
| 3      | MATERIAL       | varchar | 50                | False                   |             |
| 4      | FORCE_RESET    | int     | 10                | True                    |             |

## DLCOMMENTS

The DLCOMMENTS table stored the default comments for a location code. At the time of sample login the default comments for the location code are loaded so they can be edited and stored in the COMMENTS table after login is completed. Moved to LabObjComments in ver 6.4

### Primary Keys

- LOCCODE

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description     |
|--------|----------|---------|-------------------|-------------------------|-----------------|
| 1      | LOCCODE  | varchar | 24                | False                   | Location Code   |
| 2      | COMMENTS | text    | 2147483647        | True                    | Comments        |
| 3      | hSec     | int     | 10                | False                   | Security Handle |

## DOCREFERENCE

Listing of Document References (for Reference Maintenance Program)

### Primary Keys

- REFNAME
- REFTYPE
- CREATEDATE

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description                     |
|--------|------------|----------|-------------------|-------------------------|---------------------------------|
| 1      | REFNAME    | varchar  | 24                | False                   | Reference Name                  |
| 2      | REFTYPE    | varchar  | 8                 | False                   | Reference Type (MAP, MSDS, SOP) |
| 3      | CREATEDATE | datetime |                   | False                   | Creation Date                   |
| 4      | REFERENCE  | varchar  | 255               | True                    | Reference File specification    |
| 5      | REFTITLE   | varchar  | 60                | True                    | Reference Title                 |
| 6      | REMARKS    | varchar  | 255               | True                    | Remarks                         |
| 7      | CREATEINIT | varchar  | 12                | False                   | User Initial                    |
| 8      | CREATENAME | varchar  | 50                | True                    | User Name                       |
| 9      | hSec       | int      | 10                | False                   | Security Handle                 |

## DV\_NARRATIVE\_STATUS

DataViewer Narrative text status

### Primary Keys

| Sr.No. | Name       | Type    | Size (Characters) | Allow Null (True/False) | Description   |
|--------|------------|---------|-------------------|-------------------------|---------------|
| 1      | S_OPERATOR | varchar | 4000              | True                    | Operator Name |
| 2      | S_VALUE1   | real    |                   | True                    | Value 1       |
| 3      | S_VALUE2   | real    |                   | True                    | Value 2       |
| 4      | S_NAME     | varchar | 50                | True                    | Name          |

## DV\_NARRATIVE\_VALUES

DataViewer Narrative text values

### Primary Keys

- CODE

| Sr.No. | Name  | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------|---------|-------------------|-------------------------|-------------|
| 1      | CODE  | varchar | 10                | False                   | Code        |
| 2      | VALUE | text    | 2147483647        | True                    | Point Value |
| 3      | POINT | int     | 10                | True                    | Point Index |

## ERDETAIL

Exception Report Details

### Primary Keys

- ERNAME
- ITEMTYPE
- ITEMNUM

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description                          |
|--------|----------|----------|-------------------|-------------------------|--------------------------------------|
| 1      | ERNAME   | varchar  | 16                | False                   | Exception Report Name                |
| 2      | ITEMTYPE | varchar  | 8                 | False                   | Report Item Type                     |
| 3      | ITEMNUM  | smallint |                   | False                   | Item Number (unique for each Report) |
| 4      | ITEMVAL1 | varchar  | 80                | True                    | Value 1                              |
| 5      | ITEMVAL2 | varchar  | 80                | True                    | Value 2                              |
| 6      | hSec     | int      | 10                | False                   | Security Handle                      |

## ERHEADER

Exception Report Header details

### Primary Keys

- ERNAME

| Sr.No. | Name   | Type    | Size (Characters) | Allow Null (True/False) | Description           |
|--------|--------|---------|-------------------|-------------------------|-----------------------|
| 1      | ERNAME | varchar | 16                | False                   | Exception Report Name |
| 2      | DESCR  | varchar | 60                | True                    | Description           |

|    |            |          |    |       |   |
|----|------------|----------|----|-------|---|
| 3  | TIMEOPT    | varchar  | 8  | True  | Time Option                             |
| 4  | ENDTIME    | varchar  | 8  | True  | End Time                                |
| 5  | DURATION   | int      | 10 | False | Duration                                |
| 6  | SORTBY     | varchar  | 8  | True  | Sort By                                 |
| 7  | INCWARNING | smallint |    | False | Include Warnings violations option flag |
| 8  | VALOPTION  | varchar  | 8  | True  | Validation option                       |
| 9  | CREATEDATE | datetime |    | True  | Created Date                            |
| 10 | CREATEUSER | varchar  | 12 | True  | Created User                            |
| 11 | MODDATE    | datetime |    | True  | Last Modified Date                      |
| 12 | MODUSER    | varchar  | 12 | True  | Last Modified User                      |
| 13 | hSec       | int      | 10 | False | Security Handle                         |

## ErrorLog

Recorded Errors

### Primary Keys

- ErrorID

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description         |
|--------|------------------|----------|-------------------|-------------------------|---------------------|
| 1      | ErrorID          | int      | 10                | False                   | Error Index         |
| 2      | ErrorDescription | nvarchar | 2000              | True                    | Description         |
| 3      | ErrorDateTime    | datetime |                   | True                    | When error occurred |
| 4      | ErrorApplication | varchar  | 50                | True                    | Application         |
| 5      | UserID           | varchar  | 50                | True                    | User Index          |
| 6      | UserInitials     | varchar  | 50                | True                    | User Initials       |
| 7      | SecurityLevel    | varchar  | 50                | True                    | Security Level      |
| 8      | LogType          | varchar  | 50                | True                    | Error Type          |
| 9      | ErrorClass       | varchar  | 4000              | True                    | Error Class         |
| 10     | ErrorMethod      | varchar  | 4000              | True                    | Error Method        |
| 11     | ErrorAssembly    | varchar  | 4000              | True                    | Error Assembly      |
| 12     | AssemblyVersion  | varchar  | 4000              | True                    | Version             |
| 13     | WorkStationID    | varchar  | 50                | True                    | Workstation         |
| 14     | Detail1          | varchar  | 4000              | True                    | Error Details       |
| 15     | Detail2          | varchar  | 4000              | True                    | Error Details       |

## EWORKSHEETDATA

EWorksheet data

### Primary Keys

- ID

| Sr.No. | Name | Type | Size | Allow Null | Description |
|--------|------|------|------|------------|-------------|
|        |      |      |      |            |             |

|    |                |          | <b>(Characters)</b> | <b>(True/False)</b> |                   |
|----|----------------|----------|---------------------|---------------------|-------------------|
| 1  | ID             | bigint   |                     | False               | Identifier        |
| 2  | NAME           | varchar  | 40                  | False               | Name              |
| 3  | DESCRIPTION    | varchar  | 2000                | True                | Description       |
| 4  | TEMPLATE_NAME  | varchar  | 50                  | False               | Template Name     |
| 5  | SAMPLEOPTION   | int      | 10                  | False               | Sample Option     |
| 6  | CURRENT_STATUS | varchar  | 20                  | False               | Current Status    |
| 7  | CREATED_BY     | varchar  | 12                  | False               | Created By        |
| 8  | CREATED_DATE   | datetime |                     | False               | Created Date      |
| 9  | MODUSER        | varchar  | 12                  | True                | Modified by User  |
| 10 | MODDATE        | datetime |                     | True                | Modification Date |
| 11 | HSEC           | int      | 10                  | True                | Security Handle   |

## EWRKSHEETSAMPS

EWorksheet Samples

### Primary Keys

| Sr.No. | Name         | Type    | Size<br>(Characters) | Allow Null<br>(True/False) | Description   |
|--------|--------------|---------|----------------------|----------------------------|---------------|
| 1      | EWORKSHEETID | bigint  |                      | True                       | Identifier    |
| 2      | SAMPNO       | varchar | 7                    | True                       | Sample ID     |
| 3      | ACODE        | varchar | 24                   | True                       | Analysis Code |

## FileObjMgmt

Contains the list of file objects being managed

### Primary Keys

- ID

| Sr.No. | Name           | Type     | Size<br>(Characters) | Allow Null<br>(True/False) | Description       |
|--------|----------------|----------|----------------------|----------------------------|-------------------|
| 1      | ID             | int      | 10                   | False                      | Index             |
| 2      | ObjectDesc     | varchar  | 255                  | True                       | Description       |
| 3      | ObjectFileSpec | varchar  | 255                  | True                       | Location of file  |
| 4      | ObjectState    | varchar  | 255                  | True                       | Object State      |
| 5      | ObjectType     | varchar  | 255                  | True                       | Type              |
| 6      | Moduser        | varchar  | 12                   | True                       | Initials of User  |
| 7      | ModDate        | datetime |                      | True                       | Modification Date |
| 8      | FileObjectType | varchar  | 50                   | True                       | File Type         |
| 9      | CURRENT_STATUS | varchar  | 50                   | True                       | Object State      |
| 10     | ObjectVersion  | varchar  | 50                   | True                       | File Version      |
| 11     | FileCheckSum   | varchar  | 255                  | True                       | CheckSum of file  |

|    |            |         |    |      |             |
|----|------------|---------|----|------|-------------|
| 12 | SubFolder  | varchar | 50 | True | File Folder |
| 13 | FOWNER     | varchar | 24 | True | Full Owner  |
| 14 | FREADOWNER | varchar | 24 | True | Read Owner  |
| 15 | ReadOwner  | varchar | 50 | True | Read Owner  |
| 16 | FullOwner  | varchar | 50 | True | Full Owner  |

## GROUPHEADER

Persited Group Header

### Primary Keys

- GRPID

| Sr.No. | Name          | Type     | Size (Characters) | Allow Null (True/False) | Description      |
|--------|---------------|----------|-------------------|-------------------------|------------------|
| 1      | GRPID         | varchar  | 50                | False                   | Group ID         |
| 2      | GRPTYPE       | varchar  | 24                | False                   | Group Type       |
| 3      | TITLE         | varchar  | 128               | False                   | Group Title      |
| 4      | CREATEDATE    | datetime |                   | True                    | When Created     |
| 5      | CREATEDBY     | varchar  | 12                | True                    | Who Created      |
| 6      | CURRENT_STATE | varchar  | 40                | True                    | Object State     |
| 7      | MODUSER       | varchar  | 12                | True                    | Last Modified By |
| 8      | MODDATE       | datetime |                   | True                    | Last Modified    |

## GROUPMEMBERS

Persited Group Members

### Primary Keys

- GRPID
- MEMBTYP
- MEMBID

| Sr.No. | Name    | Type    | Size (Characters) | Allow Null (True/False) | Description  |
|--------|---------|---------|-------------------|-------------------------|--------------|
| 1      | MEMBNUM | int     | 10                | False                   | Member Index |
| 2      | GRPID   | varchar | 50                | False                   | Group ID     |
| 3      | MEMBTYP | varchar | 8                 | False                   | Member Type  |
| 4      | MEMBID  | varchar | 50                | False                   | Member ID    |

## GRUPPARAMS

Persited Group Parameters

### Primary Keys

- GRPID

- PARAMNAME

| Sr.No. | Name       | Type    | Size (Characters) | Allow Null (True/False) | Description              |
|--------|------------|---------|-------------------|-------------------------|--------------------------|
| 1      | GRPID      | varchar | 50                | False                   | Group ID                 |
| 2      | PARAMNAME  | varchar | 50                | False                   | Parameter Name           |
| 3      | PARAMNUMB  | int     | 10                | False                   | Parameter Index          |
| 4      | PARAMVALUE | varchar | 1024              | True                    | Value                    |
| 5      | TYPE       | varchar | 255               | True                    | Type                     |
| 6      | PICKLIST   | varchar | 20                | True                    | Paramenter Picklist Name |

## GROUPSIPROMPTS

Persited Group Special Info Prompts

### Primary Keys

- GRPID
- PROMPTNO

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description         |
|--------|----------|---------|-------------------|-------------------------|---------------------|
| 1      | GRPID    | varchar | 50                | False                   | Group ID            |
| 2      | PROMPTNO | int     | 10                | False                   | Prompt Index        |
| 3      | SIPROMPT | varchar | 50                | False                   | Special Info Prompt |
| 4      | SIFORM   | varchar | 24                | True                    | SI Form Name        |

## HOLIDAYS

List of Holidays

### Primary Keys

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|--------------|----------|-------------------|-------------------------|-------------|
| 1      | HOLIDAY_DATE | datetime |                   | False                   | Date        |
| 2      | DESCRIPTION  | varchar  | 50                | False                   | Description |

## I18NApplications

Contains the list of applications that have been internationalized

### Primary Keys

| Sr.No. | Name    | Type     | Size (Characters) | Allow Null (True/False) | Description             |
|--------|---------|----------|-------------------|-------------------------|-------------------------|
| 1      | AppID   | smallint |                   | True                    | Application code        |
| 2      | AppName | nvarchar | 50                | False                   | Name of the application |

|   |                |          |     |      |                                   |
|---|----------------|----------|-----|------|-----------------------------------|
| 3 | AppProjFile    | nvarchar | 255 | True | Application Project File Location |
| 4 | Appdescription | nvarchar | 100 | True | Description of the application    |
| 5 | hSec           | int      | 10  | True | Security Handle                   |

## I18NAppModules

Contains the list of modules that are used by an application

### Primary Keys

| Sr.No. | Name  | Type     | Size (Characters) | Allow Null (True/False) | Description      |
|--------|-------|----------|-------------------|-------------------------|------------------|
| 1      | AppID | smallint |                   | True                    | Application code |
| 2      | ModID | smallint |                   | True                    | Module code      |
| 3      | hSec  | int      | 10                | True                    | Security Handle  |

## I18NLanguages

Contains the list of the languages that can be used with this database

### Primary Keys

- LangID
- LangName

| Sr.No. | Name            | Type     | Size (Characters) | Allow Null (True/False) | Description                 |
|--------|-----------------|----------|-------------------|-------------------------|-----------------------------|
| 1      | LangID          | smallint |                   | False                   | Language Identifier         |
| 2      | LangName        | nvarchar | 50                | False                   | Name of the Language        |
| 3      | LangDescription | nvarchar | 80                | True                    | Description of the language |
| 4      | hSec            | int      | 10                | True                    | Security Handle             |

## I18NListStrings

There are places in Labworks where the strings originate from the database and are not part of the code base. The PRIVS table is one of the places where this occurs. This table is used as a reverse lookup table. It contains the name of the list and the string identification codes for the strings in the list

### Primary Keys

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------|----------|-------------------|-------------------------|-------------|
| 1      | ListName | nvarchar | 16                | True                    |             |
| 2      | StrID    | int      | 10                | True                    | String      |

|   |      |     |    |      |                     |
|---|------|-----|----|------|---------------------|
|   |      |     |    |      | identification code |
| 3 | hSec | int | 10 | True | Security Handle     |

## I18NLocalStrings

Contains the list of the localized strings

### Primary Keys

- StrID
- LangID

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description                       |
|--------|-----------|----------|-------------------|-------------------------|-----------------------------------|
| 1      | StrID     | bigint   |                   | False                   | String identification code        |
| 2      | LangID    | bigint   |                   | False                   | Language identification code      |
| 3      | LocalText | nvarchar | 255               | True                    | Localized text for User interface |
| 4      | hSec      | int      | 10                | True                    | Security Handle                   |

## I18NModStrings

Contains the list of modules and the strings that used for that module

### Primary Keys

| Sr.No. | Name  | Type     | Size (Characters) | Allow Null (True/False) | Description                |
|--------|-------|----------|-------------------|-------------------------|----------------------------|
| 1      | ModID | smallint |                   | True                    | Module code                |
| 2      | StrID | int      | 10                | True                    | String Identification Code |
| 3      | hSec  | int      | 10                | True                    | Security Handle            |

## I18NSourceModules

Contains the list of modules that have been internationalized

### Primary Keys

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description        |
|--------|----------------|----------|-------------------|-------------------------|--------------------|
| 1      | ModID          | smallint |                   | True                    | Module code        |
| 2      | ModSpec        | nvarchar | 255               | False                   | Path of the Module |
| 3      | ModDescription | nvarchar | 80                | True                    | Description of     |

|   |      |     |    |      |                 |
|---|------|-----|----|------|-----------------|
|   |      |     |    |      | the Module      |
| 4 | hSec | int | 10 | True | Security Handle |

## I18NStrings

Contains the list of the UI context for each of the strings

### Primary Keys

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description                       |
|--------|------------|----------|-------------------|-------------------------|-----------------------------------|
| 1      | StrID      | int      | 10                | False                   | String Identification Code        |
| 2      | StrContext | nvarchar | 120               | False                   | User Interface context for string |
| 3      | hSec       | int      | 10                | True                    | Security Handle                   |

## IMCINSTCALI

Instrument Calibration details

### Primary Keys

- InstCode
- CaliDate
- SampNo

| Sr.No. | Name                      | Type     | Size (Characters) | Allow Null (True/False) | Description                        |
|--------|---------------------------|----------|-------------------|-------------------------|------------------------------------|
| 1      | InstCode                  | varchar  | 24                | False                   | Instrument Code                    |
| 2      | CaliDate                  | datetime |                   | False                   | Calibration date                   |
| 3      | CaliUser                  | varchar  | 25                | True                    | Calibration User                   |
| 4      | SampNo                    | varchar  | 7                 | False                   | Sample ID                          |
| 5      | WorkDone                  | text     | 2147483647        | True                    |                                    |
| 6      | Completed                 | smallint |                   | False                   | Completed option flag              |
| 7      | hSec                      | int      | 10                | False                   | Security Handle                    |
| 8      | CALIB_EMAIL_WARN_DATETIME | datetime |                   | True                    | Calibration Email Warning DateTime |

## IMCINSTMAINT

Instrument Maintenance Details

### Primary Keys

- INSTCODE
- MAINTDATE

- TYPEOFWORK

| Sr.No. | Name                      | Type     | Size (Characters) | Allow Null (True/False) | Description                        |
|--------|---------------------------|----------|-------------------|-------------------------|------------------------------------|
| 1      | INSTCODE                  | varchar  | 24                | False                   | Instrument Code                    |
| 2      | MAINTDATE                 | datetime |                   | False                   |                                    |
| 3      | INSTDESC                  | text     | 2147483647        | True                    |                                    |
| 4      | DONEBY                    | varchar  | 25                | True                    |                                    |
| 5      | TYPEOFWORK                | varchar  | 50                | False                   |                                    |
| 6      | PONUMBER                  | varchar  | 35                | True                    | PO Number                          |
| 7      | COST                      | real     |                   | True                    |                                    |
| 8      | DOWNTIME                  | real     |                   | True                    |                                    |
| 9      | DOWNFROM                  | datetime |                   | True                    |                                    |
| 10     | DOWNT0                    | datetime |                   | True                    |                                    |
| 11     | COMPLETED                 | smallint |                   | False                   |                                    |
| 12     | SCHEDULEDATE              | datetime |                   | True                    |                                    |
| 13     | hSec                      | int      | 10                | False                   | Security Handle                    |
| 14     | MAINT_EMAIL_WARN_DATETIME | datetime |                   | True                    | Maintenance Email Warning DateTime |

## IMCPROCS

### Instrument Procedure Details

#### Primary Keys

- INSTCODE
- PROCTYPE

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description     |
|--------|----------|---------|-------------------|-------------------------|-----------------|
| 1      | INSTCODE | varchar | 24                | False                   | Instrument Code |
| 2      | PROCTYPE | varchar | 6                 | False                   | Procedure Type  |
| 3      | PROCTEXT | text    | 2147483647        | True                    | Procedure Text  |
| 4      | hSec     | int     | 10                | False                   | Security Handle |

## INSTLIST

### Instruments Listing

#### Primary Keys

- INSTCODE

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description       |
|--------|------------|----------|-------------------|-------------------------|-------------------|
| 1      | INSTCODE   | varchar  | 24                | False                   | Instrument Code   |
| 2      | INSTNAME   | varchar  | 100               | True                    | Procedure Type    |
| 3      | INSTSTATUS | smallint |                   | False                   | Procedure Text    |
| 4      | Manufactor | varchar  | 40                | True                    | Manufacturer Name |
| 5      | Installed  | datetime |                   | True                    | Installed Date    |

|    |                  |          |     |       |                                    |
|----|------------------|----------|-----|-------|------------------------------------|
| 6  | Serial_No        | varchar  | 40  | True  | Serial Number                      |
| 7  | hSec             | int      | 10  | False | Security Handle                    |
| 8  | INSTLOCATION     | varchar  | 24  | True  | Location/Room                      |
| 9  | INST_PROGRAM     | varchar  | 255 | True  | Program associated with instrument |
| 10 | INSTTYPE         | varchar  | 50  | True  | Type associated with instrument    |
| 11 | SOFTWARE_VERSION | varchar  | 50  | True  | Software Version                   |
| 12 | USE_SCHUMAKER    | bit      |     | True  |                                    |
| 13 | COMMENTTEXT      | nvarchar | -1  | True  |                                    |

## INSTTESTS

Analysis Listing for Instruments

### Primary Keys

- INSTCODE
- ACODE

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description              |
|--------|----------|----------|-------------------|-------------------------|--------------------------|
| 1      | INSTCODE | varchar  | 24                | False                   | Instrument Code          |
| 2      | ACODE    | varchar  | 24                | False                   | Analysis Code            |
| 3      | EXPDATE  | datetime |                   | True                    | Analysis Expiration Date |
| 4      | hSec     | int      | 10                | False                   | Security Handle          |

## INVCOMMENTS

Table listing Invoice Comments

### Primary Keys

- INVNO
- ACODE
- CMTLINE

| Sr.No. | Name    | Type     | Size (Characters) | Allow Null (True/False) | Description         |
|--------|---------|----------|-------------------|-------------------------|---------------------|
| 1      | INVNO   | int      | 10                | False                   | Instrument Code     |
| 2      | ACODE   | varchar  | 24                | False                   | Analysis Code       |
| 3      | CMTLINE | smallint |                   | False                   | Comment Line number |
| 4      | CMTTEXT | varchar  | 80                | True                    | Comment             |
| 5      | hSec    | int      | 10                | False                   | Security Handle     |

## INVDATA

Generated Invoice Details

### Primary Keys

- INVNO
- DETNUM

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description                               |
|--------|-------------|----------|-------------------|-------------------------|---|
| 1      | INVNO       | int      | 10                | False                   | Invoice Number                            |
| 2      | DETNUM      | smallint |                   | False                   | Invoice Details Line number               |
| 3      | DETTYPE     | varchar  | 8                 | False                   | Detail Type (TAX, DISCOUNT, ANALYSIS etc) |
| 4      | DESCRIPTION | varchar  | 40                | True                    | Description                               |
| 5      | QUANTITY    | smallint |                   | False                   | Quantity                                  |
| 6      | UNITPRICE   | real     |                   | True                    | Unit Price                                |
| 7      | TOTALPRICE  | real     |                   | True                    | Total Price                               |
| 8      | hSec        | int      | 10                | False                   | Security Handle                           |

## INVHEAD

Listing of Invoices generated in LABWORKS

### Primary Keys

- INVNO

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description            |
|--------|-----------|----------|-------------------|-------------------------|------------------------|
| 1      | INVNO     | int      | 10                | False                   | Invoice Number         |
| 2      | INVDATE   | datetime |                   | True                    | Invoice Date           |
| 3      | INVUSER   | varchar  | 12                | True                    | Invoice generated User |
| 4      | PRICETYPE | varchar  | 8                 | True                    | Price Type             |
| 5      | INVAPP    | varchar  | 50                | True                    |                        |
| 6      | SAMPNOS   | varchar  | 4000              | True                    | Sample ID              |
| 7      | INVADD1   | varchar  | 40                | True                    | Invoice Address 1      |
| 8      | INVADD2   | varchar  | 40                | True                    | Invoice Address 2      |
| 9      | INVADD3   | varchar  | 40                | True                    | Invoice Address 3      |
| 10     | INVADD4   | varchar  | 40                | True                    | Invoice Address 4      |
| 11     | INVADD5   | varchar  | 40                | True                    | Invoice Address 5      |
| 12     | INVNAME   | varchar  | 24                | True                    | Invoice Name           |
| 13     | BILLRATE  | real     |                   | False                   | Bill Rate              |
| 14     | PRICELIST | varchar  | 24                | True                    | Price List             |
| 15     | PONUMBER  | varchar  | 24                | True                    | PO Number              |
| 16     | PROJECT   | varchar  | 2000              | True                    | Project Name           |
| 17     | SSTATUS   | varchar  | 1                 | False                   | Sample status          |

|    |          |          |    |       |                      |
|----|----------|----------|----|-------|----------------------|
| 18 | LOCCODE  | varchar  | 24 | True  | Location Code        |
| 19 | LOCDESCR | varchar  | 60 | True  | Location Description |
| 20 | LOGBATCH | varchar  | 30 | True  | Log batch Name       |
| 21 | LOGUSER  | varchar  | 12 | True  | Log User             |
| 22 | SUBDATE  | datetime |    | True  | Submitted Date       |
| 23 | SAMPCOL  | varchar  | 24 | True  |                      |
| 24 | COLDATE  | datetime |    | True  | Collection Date      |
| 25 | RDUEDATE | datetime |    | True  |                      |
| 26 | DUEDATE  | datetime |    | True  | Due Date             |
| 27 | REPNAME  | varchar  | 24 | True  | Report Name          |
| 28 | REPDATE  | datetime |    | True  | Report Date          |
| 29 | REPADD1  | varchar  | 40 | True  | Report Address 1     |
| 30 | REPADD2  | varchar  | 40 | True  | Report Address 2     |
| 31 | REPADD3  | varchar  | 40 | True  | Report Address 3     |
| 32 | REPADD4  | varchar  | 40 | True  | Report Address 4     |
| 33 | REPADD5  | varchar  | 40 | True  | Report Address 5     |
| 34 | VALDATE  | datetime |    | True  | Validation Date      |
| 35 | VALUSER  | varchar  | 12 | True  | Validation User      |
| 36 | EXPDATE  | datetime |    | True  | Expiration Date      |
| 37 | MODDATE  | datetime |    | True  | Last Modified Date   |
| 38 | MODUSER  | varchar  | 12 | True  | Last Modified User   |
| 39 | hSec     | int      | 10 | False | Security Handle      |

## INVSPECINFO

Special Info field values associated with Invoice

### Primary Keys

- INVNO
- ACODE
- SIFLDNUM

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description                    |
|--------|----------|----------|-------------------|-------------------------|--------------------------------|
| 1      | INVNO    | int      | 10                | False                   | Invoice Number                 |
| 2      | ACODE    | varchar  | 24                | False                   | Analysis Code                  |
| 3      | SIFLDNUM | smallint |                   | False                   | Special Info (SI) Field Number |
| 4      | FLDTITLE | varchar  | 80                | True                    | SI Field Title                 |
| 5      | FLDVALUE | varchar  | 60                | True                    | SI Field Value                 |
| 6      | hSec     | int      | 10                | False                   | Security Handle                |

## INVUSRFLDS

User Field Values associated with Invoice

### Primary Keys

- INVNO
- UFLDNUM

| Sr.No. | Name    | Type     | Size (Characters) | Allow Null (True/False) | Description       |
|--------|---------|----------|-------------------|-------------------------|-------------------|
| 1      | INVNO   | int      | 10                | False                   | Invoice Number    |
| 2      | UFLDNUM | smallint |                   | False                   | User Field Number |
| 3      | UFVALUE | varchar  | 160               | True                    | User Field Value  |
| 4      | hSec    | int      | 10                | False                   | Security Handle   |

## IPP\_ACTION

Action Definitions of Industrial Pretreatment

### Primary Keys

- ACTIONNUM

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description                |
|--------|------------|----------|-------------------|-------------------------|----------------------------|
| 1      | LOCODE     | varchar  | 24                | False                   | Location Code              |
| 2      | ACTIONCODE | varchar  | 20                | False                   | Action Code                |
| 3      | INITDATE   | datetime |                   | True                    | Initiation Date            |
| 4      | DUEDATE    | datetime |                   | True                    | Action Completion Due Date |
| 5      | CLOSEDATE  | datetime |                   | True                    | Close Date                 |
| 6      | INITBY     | varchar  | 50                | False                   | Initialized by             |
| 7      | CLOSEBY    | varchar  | 50                | True                    | Close by                   |
| 8      | ACTIONNUM  | int      | 10                | False                   | Action Number              |
| 9      | NOTES      | text     | 2147483647        | True                    | Notes                      |
| 10     | CREATEDATE | datetime |                   | True                    | Creation Date              |
| 11     | CREATEUSER | varchar  | 12                | True                    | Created User               |
| 12     | MODDATE    | datetime |                   | True                    | Last Modified Date         |
| 13     | MODUSER    | varchar  | 12                | True                    | Last Modified User         |
| 14     | hSec       | int      | 10                | False                   | Security Handle            |

## IPP\_PERMIT

Permit definitions of Industrial Pretreatment Program

### Primary Keys

- PERMITNO

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description          |
|--------|------------|----------|-------------------|-------------------------|----------------------|
| 1      | PERMITNO   | varchar  | 20                | False                   | Permit Number        |
| 2      | IUNAME     | varchar  | 50                | True                    | Industrial User Name |
| 3      | CONTACT    | varchar  | 40                | True                    | Contact Person       |
| 4      | CTITLE     | varchar  | 40                | True                    | Title                |
| 5      | ADD1       | varchar  | 40                | True                    | Address 1            |
| 6      | ADD2       | varchar  | 40                | True                    | Address 2            |
| 7      | CITY       | varchar  | 40                | True                    | City                 |
| 8      | STATE      | varchar  | 2                 | True                    | State                |
| 9      | ZIP        | varchar  | 10                | True                    | Zip                  |
| 10     | PHONE      | varchar  | 20                | True                    | Phone                |
| 11     | FAX        | varchar  | 20                | True                    | Fax                  |
| 12     | EMAIL      | varchar  | 50                | True                    | Email                |
| 13     | URL        | varchar  | 128               | True                    | Url                  |
| 14     | MUNICODE   | varchar  | 16                | False                   | Municipality Code    |
| 15     | CAREP      | varchar  | 40                | True                    | Representative       |
| 16     | CAREPTITLE | varchar  | 40                | True                    | Representative Title |
| 17     | ISSUEDATE  | datetime |                   | True                    | Issue Date           |
| 18     | EFFDATE    | datetime |                   | True                    | Effective Date       |
| 19     | EXPDATE    | datetime |                   | True                    | Expiration Date      |
| 20     | FEEAMT     | real     |                   | True                    | Fee Amount           |
| 21     | FEEPERIOD  | varchar  | 1                 | True                    | Fee Period           |
| 22     | COMMENTS   | varchar  | 255               | True                    | Comments             |
| 23     | MODDATE    | datetime |                   | True                    | Last Modified Date   |
| 24     | MODUSER    | varchar  | 12                | True                    | Last Modified User   |
| 25     | hSec       | int      | 10                | False                   | Security Handle      |

## IPP2LWANLS

Industrial Pretreatment Program (IPP) to LABWORKS Analyte Reference

### Primary Keys

- IANALYTE
- ACODE
- ANALYTE

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description        |
|--------|----------|----------|-------------------|-------------------------|--------------------|
| 1      | IANALYTE | varchar  | 40                | False                   | Analysis Name      |
| 2      | ACODE    | varchar  | 24                | False                   | Analysis Code      |
| 3      | ANALYTE  | varchar  | 40                | False                   | Analysis Name      |
| 4      | CONVFACT | real     |                   | True                    | Conversion factor  |
| 5      | RANK     | smallint |                   | False                   | Rank               |
| 6      | ANLNUMB  | smallint |                   | False                   | Analysis Number    |
| 7      | MODDATE  | datetime |                   | True                    | Last Modified Date |
| 8      | MODUSER  | varchar  | 12                | True                    | Last Modified User |
| 9      | hSec     | int      | 10                | False                   | Security Handle    |

## IPPLIMITS

Site IPP limits of Industrial Pretreatment Program

### Primary Keys

- LOCCODE
- IANALYTE
- LIMITTYPE
- EFFDATE

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description        |
|--------|-----------|----------|-------------------|-------------------------|--------------------|
| 1      | LOCCODE   | varchar  | 24                | False                   | Location Code      |
| 2      | IANALYTE  | varchar  | 40                | False                   | Analyte Name       |
| 3      | IUNIT     | varchar  | 16                | True                    |                    |
| 4      | LIMITTYPE | varchar  | 16                | False                   | Limit Type         |
| 5      | VALUE     | varchar  | 16                | False                   | Value              |
| 6      | EFFDATE   | datetime |                   | False                   | Effective Date     |
| 7      | EXPDATE   | datetime |                   | True                    | Expiration Date    |
| 8      | VERSION   | int      | 10                | False                   | Version            |
| 9      | MODDATE   | datetime |                   | True                    | Last Modified Date |
| 10     | MODUSER   | varchar  | 12                | True                    | Last Modified User |
| 11     | hSec      | int      | 10                | False                   | Security Handle    |

## IPPMUNI

Municipality listing of Industrial Pretreatment Program

### Primary Keys

- MUNICODE

| Sr.No. | Name      | Type    | Size (Characters) | Allow Null (True/False) | Description       |
|--------|-----------|---------|-------------------|-------------------------|-------------------|
| 1      | MUNICODE  | varchar | 16                | False                   | Municipality Code |
| 2      | MUNINAME  | varchar | 60                | True                    | Municipality Name |
| 3      | ADD1      | varchar | 40                | True                    | Address 1         |
| 4      | ADD2      | varchar | 40                | True                    | Address 2         |
| 5      | CITY      | varchar | 30                | True                    | City              |
| 6      | STATE     | varchar | 2                 | True                    | State             |
| 7      | ZIP       | varchar | 10                | True                    | Zip               |
| 8      | FAX       | varchar | 20                | True                    | Fax               |
| 9      | PHONE     | varchar | 20                | True                    | Phone             |
| 10     | EMAIL     | varchar | 60                | True                    | Email             |
| 11     | URL       | varchar | 80                | True                    | Url               |
| 12     | CONTACT   | varchar | 40                | True                    | Contact           |
| 13     | CTITLE    | varchar | 40                | True                    | Title             |
| 14     | VOLCHRGIN | real    |                   | True                    |                   |

|    |            |         |     |       |                 |
|----|------------|---------|-----|-------|-----------------|
| 15 | VOLCHRGOUT | real    |     | True  |                 |
| 16 | COMMENTS   | varchar | 255 | True  | Comments        |
| 17 | hSec       | int     | 10  | False | Security Handle |

## IPPSAMPFREQ

Site Sample Frequencies of Industrial Pretreatment Program

### Primary Keys

- LOCCODE
- IANALYTE
- EFFDATE

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description        |
|--------|--------------|----------|-------------------|-------------------------|--------------------|
| 1      | LOCCODE      | varchar  | 24                | False                   | Location Code      |
| 2      | IANALYTE     | varchar  | 40                | False                   | Analyte Name       |
| 3      | EFFDATE      | datetime |                   | False                   | Effective date     |
| 4      | EXPDATE      | datetime |                   | True                    | Expiration Date    |
| 5      | POTWFREQ     | smallint |                   | False                   | POTW Frequency     |
| 6      | POTWTIMEUNIT | varchar  | 1                 | False                   | POTW Interval      |
| 7      | SELFFREQ     | smallint |                   | False                   | Self Frequency     |
| 8      | SELFTIMEUNIT | varchar  | 1                 | False                   | Self Interval      |
| 9      | MODDATE      | datetime |                   | True                    | Last Modified Date |
| 10     | MODUSER      | varchar  | 12                | True                    | Last Modified User |
| 11     | hSec         | int      | 10                | False                   | Security Handle    |

## IPPSTATUS

Site Compliance status of Industrial Pretreatment Program

### Primary Keys

- LOCCODE
- STARTDATE

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description      |
|--------|-----------|----------|-------------------|-------------------------|------------------|
| 1      | LOCCODE   | varchar  | 24                | False                   | Location Code    |
| 2      | STARTDATE | datetime |                   | False                   | Start Date       |
| 3      | STATUS    | varchar  | 3                 | False                   | Status           |
| 4      | CALCDATE  | datetime |                   | True                    | Calculation Date |
| 5      | CALCUSER  | varchar  | 12                | True                    | Calculation User |
| 6      | hSec      | int      | 10                | False                   | Security Handle  |

## IPPVIOLS

Site Violation Details of Industrial Pretreatment Program

### Primary Keys

- LOCCODE
- VIOLTYPE
- VIOLDATE
- IANALYTE

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description           |
|--------|-----------|----------|-------------------|-------------------------|-----------------------|
| 1      | LOCCODE   | varchar  | 24                | False                   | Location Code         |
| 2      | VIOLTYPE  | varchar  | 50                | False                   | Violation Type        |
| 3      | VIOLDATE  | datetime |                   | False                   | Violation Date        |
| 4      | IANALYTE  | varchar  | 40                | False                   | Analyte               |
| 5      | VIOLDESCR | varchar  | 50                | False                   | Violation Description |
| 6      | CALCDATE  | datetime |                   | True                    |                       |
| 7      | CALCUSER  | varchar  | 12                | True                    |                       |
| 8      | hSec      | int      | 10                | False                   | Security Handle       |

## LABOBJCOMMENTS

Comments

### Primary Keys

- OBJID
- OBJTYPE
- COMMENTNUMB

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description        |
|--------|-------------|----------|-------------------|-------------------------|--------------------|
| 1      | OBJID       | varchar  | 100               | False                   | Object ID          |
| 2      | OBJTYPE     | varchar  | 40                | False                   | Type               |
| 3      | COMMENTNUMB | int      | 10                | False                   | Index              |
| 4      | COMMENTTEXT | varchar  | 4000              | True                    | Comment            |
| 5      | MODDATE     | datetime |                   | False                   | Last Modified      |
| 6      | MODUSER     | varchar  | 12                | False                   | Last Modified By   |
| 7      | HSEC        | int      | 10                | False                   | Security Reference |

## LABOBJMAILLIST

Comments

### Primary Keys

- OBJID

- OBJTYPE
- MLREFERENCE
- OBJNUMB

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description         |
|--------|----------------|----------|-------------------|-------------------------|---------------------|
| 1      | OBJID          | varchar  | 50                | False                   | Object ID           |
| 2      | OBJTYPE        | varchar  | 40                | False                   | Type                |
| 3      | MLREFERENCE    | varchar  | 24                | False                   | Reference to Parent |
| 4      | OBJNUMB        | int      | 10                | False                   | Index               |
| 5      | DOCTYPE        | varchar  | 24                | False                   | Document Type       |
| 6      | ADDRTYPE       | varchar  | 24                | False                   | Address Type        |
| 7      | PRIMARY        | smallint |                   | False                   |                     |
| 8      | ADDRESSEE      | varchar  | 50                | True                    |                     |
| 9      | STREET1        | varchar  | 50                | True                    |                     |
| 10     | STREET2        | varchar  | 50                | True                    |                     |
| 11     | CITY           | varchar  | 50                | True                    |                     |
| 12     | STATE          | varchar  | 50                | True                    |                     |
| 13     | POST_CODE      | varchar  | 20                | True                    |                     |
| 14     | COUNTRY        | varchar  | 50                | True                    |                     |
| 15     | PHONE_NUM      | varchar  | 30                | True                    |                     |
| 16     | FAX_NUM        | varchar  | 50                | True                    |                     |
| 17     | EMAIL_ADDR     | varchar  | 50                | True                    |                     |
| 18     | CONTACT        | varchar  | 50                | True                    |                     |
| 19     | CONTACT_PHO NE | varchar  | 50                | True                    |                     |
| 20     | CONTACT_EMA IL | varchar  | 50                | True                    |                     |
| 21     | MODUSER        | varchar  | 12                | False                   | Last Modified By    |
| 22     | MODDate        | datetime |                   | True                    | Last Modified       |
| 23     | hsec           | int      | 10                | False                   | Security Reference  |

## LABOBJOBJECTS

Comments

### Primary Keys

- OBJID
- OBJTYPE
- OBJNUMB

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description        |
|--------|----------|----------|-------------------|-------------------------|--------------------|
| 1      | OBJID    | varchar  | 50                | False                   | Object ID          |
| 2      | OBJTYPE  | varchar  | 40                | False                   | Type               |
| 3      | OBJNUMB  | int      | 10                | False                   | Index              |
| 4      | OBJDESCR | varchar  | 255               | True                    | Description        |
| 5      | OBJSPEC  | varchar  | 255               | True                    | File Specification |
| 6      | MODDATE  | datetime |                   | False                   | Last Modified      |
| 7      | MODUSER  | varchar  | 12                | False                   | Last Modified By   |
| 8      | OBJDATA  | image    | 2147483647        | True                    | Object Data        |
| 9      | HSEC     | int      | 10                | False                   | Security Reference |

## LABOJSPECINFO

### Comments

#### Primary Keys

- OBJID
- OBJTYPE
- SIFLDNAME
- FORMNO

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description      |
|--------|------------|----------|-------------------|-------------------------|------------------|
| 1      | OBJID      | varchar  | 50                | False                   | Object ID        |
| 2      | OBJTYPE    | varchar  | 40                | False                   | Type             |
| 3      | SIFLDNAME  | varchar  | 80                | False                   | Field Name       |
| 4      | FORMNO     | int      | 10                | False                   | Form Index       |
| 5      | SIFORMNAME | varchar  | 24                | False                   | Form Name        |
| 6      | FIELDNUM   | int      | 10                | False                   | Field Number     |
| 7      | FLDVALUE   | varchar  | 60                | True                    | Field Value      |
| 8      | FLDPROMPT  | varchar  | 80                | True                    | Field Prompt     |
| 9      | MODDATE    | datetime |                   | False                   | Last Modified    |
| 10     | MODUSER    | varchar  | 12                | False                   | Last Modified By |

## LICENSEKEYINFO

#### Primary Keys

- APP\_NAME
- LIC\_KEY

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------|---------|-------------------|-------------------------|-------------|
| 1      | APP_NAME | varchar | 255               | False                   |             |
| 2      | LIC_KEY  | varchar | 50                | False                   |             |

## LOCLIST

### Location Code Listing

#### Primary Keys

- LOCCODE

| Sr.No. | Name    | Type    | Size (Characters) | Allow Null (True/False) | Description          |
|--------|---------|---------|-------------------|-------------------------|----------------------|
| 1      | LOCCODE | varchar | 24                | False                   | Location Code        |
| 2      | DESCR   | varchar | 60                | True                    | Location Description |
| 3      | OWNER   | varchar | 24                | True                    | Location Owner       |
| 4      | PROJECT | varchar | 24                | True                    | Project Account      |

|    |                   |          |    |       | Code  |
|----|-------------------|----------|----|-------|---|
| 5  | REPNAME           | varchar  | 24 | True  | Report Name   |
| 6  | INVNAME           | varchar  | 24 | True  | Invoice Name  |
| 7  | USERPROG          | varchar  | 12 | True  | User Program<br>for sample login                    |
| 8  | PRICELIST         | varchar  | 24 | True  | List Price, basic<br>Price per<br>Analysis          |
| 9  | REPADD1           | varchar  | 40 | True  | Report Address<br>1                                 |
| 10 | REPADD2           | varchar  | 40 | True  | Report Address<br>2                                 |
| 11 | REPADD3           | varchar  | 40 | True  | Report Address<br>3                                 |
| 12 | REPADD4           | varchar  | 40 | True  | Report Address<br>4                                 |
| 13 | REPADD5           | varchar  | 40 | True  | Report Address<br>5                                 |
| 14 | INVADD1           | varchar  | 40 | True  | Invoice Address<br>1                                |
| 15 | INVADD2           | varchar  | 40 | True  | Invoice Address<br>2                                |
| 16 | INVADD3           | varchar  | 40 | True  | Invoice Address<br>3                                |
| 17 | INVADD4           | varchar  | 40 | True  | Invoice Address<br>4                                |
| 18 | INVADD5           | varchar  | 40 | True  | Invoice Address<br>5                                |
| 19 | DOINV             | smallint |    | False | Do Invoice<br>Option Flag                           |
| 20 | DOVAL             | smallint |    | False | Do Validation<br>Option Flag                        |
| 21 | DOSPEC            | smallint |    | False | Do Specification<br>Option Flag                     |
| 22 | DCOPY             | smallint |    | False | Disk Copy Final<br>Report option<br>flag            |
| 23 | REPCOPIES         | smallint |    | False | Number of<br>Report Copies                          |
| 24 | BILLRATE          | real     |    | False | Percentage List<br>Price                            |
| 25 | CHOLDMINS         | int      | 10 | False | Analysis Hold<br>Minutes                            |
| 26 | RHOLDMINS         | int      | 10 | False | Result Hold<br>Minutes                              |
| 27 | DUEOPT            | varchar  | 1  | True  | Due Date Base<br>Option for Due<br>Date calculation |
| 28 | COMTMASK          | varchar  | 24 | True  | Comment Mask  |
| 29 | MODDATE           | datetime |    | True  | Last Modification<br>Date                           |
| 30 | MODUSER           | varchar  | 12 | True  | Last Modified<br>User                               |
| 31 | hSec              | int      | 10 | False | Security Handle                                     |
| 32 | CURRENT_STA<br>TE | varchar  | 50 | True  | Object State  |
| 33 | LREADOWNER        | varchar  | 24 | True  | Location<br>ReadOwner                               |
| 34 | LSAMPOWNER        | varchar  | 24 | True  | Created Sample<br>Owner                             |
| 35 | LATITUDE          | decimal  |    | True  | Latitude  |

|    |              |         |     |      |           |
|----|--------------|---------|-----|------|-----------|
| 36 | LONGITUDE    | decimal |     | True | Longitude |
| 37 | ADDRESS      | varchar | 255 | True | Address   |
| 38 | LW_PROJECTID | int     | 10  | True |           |

## LOCTESTS

Analysis List associated with Location Code

### Primary Keys

- LOCCODE
- ACODE

| Sr.No. | Name            | Type     | Size (Characters) | Allow Null (True/False) | Description   |
|--------|-----------------|----------|-------------------|-------------------------|---|
| 1      | LOCCODE         | varchar  | 24                | False                   | Location Code   |
| 2      | ACODE           | varchar  | 24                | False                   | Analysis Code   |
| 3      | CHOLDMINS       | int      | 10                | False                   | Analysis Hold Minutes   |
| 4      | RHOLDMINS       | int      | 10                | False                   | Result Hold Minutes   |
| 5      | LTESTNUM        | smallint |                   | False                   | Number of Tests for Location  |
| 6      | hSec            | int      | 10                | False                   | Security Handle   |
| 7      | NOOFREPLICATES  | int      | 10                | False                   | Number of replicates  |
| 8      | REPLICATEMETHOD | varchar  | 20                | True                    | Replicate method. Content of the field can be null or one of the following:MIN, MAX, AVERAGE                |
| 9      | AREF            | varchar  | 50                | True                    | Analysis Reference method   |
| 10     | REPSELECTION    | varchar  | 15                | True                    | Replicate selection on. Content of the field can be null or one of the following: ALL_REPLICATES, MDL_RANGE |

## LWObjects

Object Type Properties

### Primary Keys

- Object\_Name

| Sr.No. | Name                           | Type    | Size (Characters) | Allow Null (True/False) | Description                                  |
|--------|--------------------------------|---------|-------------------|-------------------------|--|
| 1      | Object_Name                    | varchar | 50                | False                   | Name   |
| 2      | Object_Description             | varchar | 50                | True                    | Description                                  |
| 3      | Is_Audit_Trail_Required        | int     | 10                | False                   | Audit Trailed?                               |
| 4      | Is_Audit_From_Null_Transaction | int     | 10                | False                   | Audit Creation                               |
| 5      | DialogType                     | varchar | 50                | True                    | Type of Audit Prompt                         |
| 6      | ObjectTableName                | varchar | 50                | True                    | Primary Table                                |
| 7      | Display_Audit_Reason           | int     | 10                | False                   | Display audit prompt to user to enter reason |
| 8      | Object_DisplayName             | varchar | 50                | True                    | Object Display Name                          |

## MDLCALCHEADER

### Primary Keys

- GROUPNAME
- GROUPNUMBER
- MATRIX

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description   |
|--------|-------------|----------|-------------------|-------------------------|---------------|
| 1      | GROUPNAME   | varchar  | 50                | False                   | Group Name    |
| 2      | GROUPNUMBER | int      | 10                | False                   | Group Number  |
| 3      | ACODE       | varchar  | 24                | True                    | Analysis Code |
| 4      | ANALYTE     | varchar  | 100               | True                    | Analyte Name  |
| 5      | MATRIX      | varchar  | 24                | False                   |               |
| 6      | GROUPDATE   | datetime |                   | True                    |               |
| 7      | hSec        | int      | 10                | False                   |               |

## MDLCALCSETUP

### Primary Keys

- ACODE
- ANALYTE

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description   |
|--------|-----------|----------|-------------------|-------------------------|---------------|
| 1      | ACODE     | varchar  | 24                | False                   | Analysis Code |
| 2      | ANALYTE   | varchar  | 100               | False                   | Analyte Name  |
| 3      | NPOINTS   | int      | 10                | False                   |               |
| 4      | ANUM      | int      | 10                | False                   |               |
| 5      | ANLNUM    | int      | 10                | False                   |               |
| 6      | STARTDATE | datetime |                   | True                    |               |
| 7      | ENDDATE   | datetime |                   | True                    |               |

|    |                      |          |     |       |  |
|----|----------------------|----------|-----|-------|--|
| 8  | RULESET              | varchar  | 24  | True  |  |
| 9  | BLANKACODE           | varchar  | 24  | True  |  |
| 10 | BLANKANALYTE         | varchar  | 100 | True  |  |
| 11 | hSec                 | int      | 10  | False |  |
| 12 | LASTUPDATED DATETIME | datetime |     | True  |  |

## MDLCHARTDATA

### Primary Keys

- GROUPNAME
- GROUPNUMBER
- SAMPNO

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description  |
|--------|------------------|----------|-------------------|-------------------------|--------------|
| 1      | GROUPNAME        | varchar  | 55                | False                   | Group Name   |
| 2      | GROUPNUMBER      | int      | 10                | False                   | Group Number |
| 3      | SAMPNO           | varchar  | 7                 | False                   | Sample ID    |
| 4      | VALIDATIONONDATE | datetime |                   | True                    |              |
| 5      | hSec             | int      | 10                | False                   |              |

## MESSAGEQUEUE

This table is used by Labworks applications to send messages within Labworks. It is used to alert other applications of tasks that need to be done

### Primary Keys

- MsgNumber

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description                             |
|--------|------------------|----------|-------------------|-------------------------|---|
| 1      | MsgNumber        | int      | 10                | False                   |   |
| 2      | MsgType          | varchar  | 25                | False                   | Send Confirm/Send Results               |
| 3      | Detail1          | varchar  | 40                | True                    | for email app, confirm#                 |
| 4      | Detail2          | varchar  | 40                | True                    | for email app, confirm+batch+increment  |
| 5      | Detail3          | varchar  | 40                | True                    |   |
| 6      | DispositionState | varchar  | 25                | True                    | Complete/Partial Complete               |
| 7      | DispositionTime  | datetime |                   | True                    | date/time last report sent out          |
| 8      | MsgLocked        | smallint |                   | False                   | Flag if record locked, -1 = locked, 0 = |

|    |              |          |    |       |  |
|----|--------------|----------|----|-------|--|
|    |              |          |    |       | unlocked                                 |
| 9  | MsgLockTime  | datetime |    | True  | Empty if not locked                      |
| 10 | CreateDate   | datetime |    | False | Date / time message created              |
| 11 | CreateUserID | varchar  | 12 | True  |  |
| 12 | ModDate      | datetime |    | True  | Date / time of last message modification |
| 13 | ModUserID    | varchar  | 12 | True  |  |
| 14 | hSec         | int      | 10 | False | Security Handle                          |

## MLADDRESSES

This table stores preconfigured groups of client information records called client (or mail list) references

### Primary Keys

- MLREFERENCE
- MLRNUM

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description  |
|--------|-------------|----------|-------------------|-------------------------|--|
| 1      | MLREFERENCE | varchar  | 24                | False                   | Mail list reference  |
| 2      | MLRNUM      | smallint |                   | False                   | Mail list row ordinal for reference                                    |
| 3      | DOCTYPE     | varchar  | 24                | False                   | Mail list document type (FinalReport / Invoice / All)                  |
| 4      | ADDRTYPE    | varchar  | 24                | False                   | Mail list address type (Postal / Email / Fax / All)                    |
| 5      | PRIMARY     | smallint |                   | False                   | Address is primary for its doc type and addr type ( 0=false else=true) |
| 6      | ADDRESSEE   | varchar  | 50                | True                    | Name of addressee  |
| 7      | STREET1     | varchar  | 50                | True                    | First street address line  |
| 8      | STREET2     | varchar  | 50                | True                    | Second street address line   |
| 9      | CITY        | varchar  | 50                | True                    | City   |
| 10     | STATE       | varchar  | 50                | True                    | State or province  |
| 11     | POST_CODE   | varchar  | 20                | True                    | Postal code (zip)  |
| 12     | COUNTRY     | varchar  | 50                | True                    | Country  |
| 13     | PHONE_NUM   | varchar  | 30                | True                    | Phone number   |
| 14     | FAX_NUM     | varchar  | 30                | True                    | Fax number   |
| 15     | EMAIL_ADDR  | varchar  | 50                | True                    | Email address  |
| 16     | CONTACT     | varchar  | 50                | True                    | Name of contact  |
| 17     | CONTACT_PHO | varchar  | 30                | True                    | Phone number   |

|    |               |          |    |       |                       |
|----|---------------|----------|----|-------|-----------------------|
|    | NE            |          |    |       | for contact           |
| 18 | CONTACT_EMAIL | varchar  | 50 | True  | Contact email address |
| 19 | MODUSER       | varchar  | 12 | True  | Row modified by       |
| 20 | MODDATE       | datetime |    | True  | Row modified on       |
| 21 | hSec          | int      | 10 | False | Security Handle       |

## MORDETAIL

Monthly Operations Report Definition Details

### Primary Keys

- MORCODE
- MORCELL
- MORSHEETNAME

| Sr.No. | Name         | Type    | Size (Characters) | Allow Null (True/False) | Description   |
|--------|--------------|---------|-------------------|-------------------------|---|
| 1      | MORCODE      | varchar | 16                | False                   | Monthly Operations Report Code  |
| 2      | MORLOCCODE   | varchar | 24                | True                    | MOR Location Code   |
| 3      | MORACODE     | varchar | 24                | True                    | MOR Analysis Code   |
| 4      | MORANALYTE   | varchar | 100               | True                    | MOR Analyte Initials  |
| 5      | CALC_TYPE    | varchar | 5                 | True                    | Defines type of MOR – Monthly, Daily, Annual by week, Annual by Month |
| 6      | MORCELL      | varchar | 12                | False                   | MOR Cell  |
| 7      | MORSHEETNAME | varchar | 31                | False                   | MOR Sheet name  |
| 8      | hSec         | int     | 10                | False                   | Security Handle   |

## MORHEADER

Monthly Operations Report (MOR) Definitions

### Primary Keys

- MORCODE

| Sr.No. | Name             | Type    | Size (Characters) | Allow Null (True/False) | Description                    |
|--------|------------------|---------|-------------------|-------------------------|--------------------------------|
| 1      | MORCODE          | varchar | 16                | False                   | Monthly Operations Report Code |
| 2      | MORDESC          | varchar | 50                | True                    | MOR Description                |
| 3      | MOREXCELFILENAME | varchar | 40                | True                    | MOR Excel File Name            |

|    |                  |          |     |       |  |
|----|------------------|----------|-----|-------|--|
| 4  | MORDATE          | varchar  | 10  | True  | Full date for MOR  |
| 5  | MORMONT          | varchar  | 10  | True  | MOR Month Specification  |
| 6  | MORDAY           | varchar  | 10  | True  | Day of the month (number)  |
| 7  | MORYEAR          | varchar  | 10  | True  | MOR Year Specification   |
| 8  | MORTYPE          | varchar  | 10  | True  | MOR Type   |
| 9  | MORROWLIMIT S    | smallint |     | False | Switch that changes the report format – on produces one sample per row |
| 10 | hSec             | int      | 10  | False | Security Handle  |
| 11 | WSMACRO          | varchar  | 50  | True  |  |
| 12 | CROSSREFSEA RCH  | varchar  | 50  | True  | Cross Reference Search name  |
| 13 | EXPORTFORMAT     | varchar  | 50  | True  | Export format  |
| 14 | EXPORTSHEET NAME | varchar  | 31  | True  | Export Excel sheet name  |
| 15 | EXPORTSTART CELL | varchar  | 12  | True  | Starting address of Export cell  |
| 16 | SELECTIONTYPE    | varchar  | 40  | True  |  |
| 17 | SEARCHROUTE      | varchar  | 100 | True  |  |

## NTRLTS

### Narrative Text Results

#### Primary Keys

- SAMPNO
- ACODE

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description             |
|--------|----------------|----------|-------------------|-------------------------|-------------------------|
| 1      | SAMPNO         | varchar  | 7                 | False                   | Sample Number           |
| 2      | ACODE          | varchar  | 24                | False                   | Analysis Code           |
| 3      | NTRESULT       | text     | 2147483647        | True                    | Narrative Text Result   |
| 4      | hSec           | int      | 10                | False                   | Security Handle         |
| 5      | RESULTCHECKSUM | varchar  | 40                | True                    | CheckSum                |
| 6      | CHECKSUMVERS   | int      | 10                | False                   | CheckSum Version        |
| 7      | AREF           | varchar  | 50                | True                    | Result method reference |
| 8      | RMODDATE       | datetime |                   | True                    |                         |

## NTTEXT

Default Text Result Description for Narrative Tests

### Primary Keys

- ACODE

| Sr.No. | Name     | Type    | Size (Characters) | Allow Null (True/False) | Description           |
|--------|----------|---------|-------------------|-------------------------|-----------------------|
| 1      | ACODE    | varchar | 24                | False                   | Analysis Code         |
| 2      | NTRESULT | text    | 2147483647        | True                    | Narrative Text Result |
| 3      | hSec     | int     | 10                | False                   | Security Handle       |

## OGROUPS

Owner Group Details

### Primary Keys

- GROUPNAME

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description                       |
|--------|------------|----------|-------------------|-------------------------|-----------------------------------|
| 1      | GROUPNAME  | varchar  | 24                | False                   | Owner Group Name                  |
| 2      | GROUPDESCR | varchar  | 40                | True                    | Owner Group Description           |
| 3      | ACTIVE     | smallint |                   | True                    | Has Active Properties flag option |
| 4      | MODDATE    | datetime |                   | True                    | Last Modified Date                |
| 5      | MODUSER    | varchar  | 12                | True                    | Last Modified User                |
| 6      | hSec       | int      | 10                | False                   | Security Handle                   |

## OGRPMEMBS

Owner Group Members Listing Information

### Primary Keys

- GROUPNAME
- LASTNAME
- FIRSTNAME

| Sr.No. | Name      | Type    | Size (Characters) | Allow Null (True/False) | Description               |
|--------|-----------|---------|-------------------|-------------------------|---------------------------|
| 1      | GROUPNAME | varchar | 24                | False                   | Owner Group Name          |
| 2      | LASTNAME  | varchar | 20                | False                   | Owner Group member's last |

|    |           |          |    |       |                           |
|----|-----------|----------|----|-------|---------------------------|
|    |           |          |    |       | name                      |
| 3  | FIRSTNAME | varchar  | 20 | False | Group member's first name |
| 4  | TITLE     | varchar  | 8  | True  | Group Title               |
| 5  | INITIALS  | varchar  | 12 | False | Group member's Initial    |
| 6  | PASSWORD  | varchar  | 12 | False | Group member's Password   |
| 7  | LEADER    | smallint |    | True  | Group Leader Option       |
| 8  | MODDATE   | datetime |    | True  | Last Modified date        |
| 9  | MODUSER   | varchar  | 12 | True  | Last Modified User        |
| 10 | hSec      | int      | 10 | False | Security Handle           |

## OGRPPERMIT

Owner Group's Permit Group Details

### Primary Keys

- GROUPNAME
- PERMITGROUP

| Sr.No. | Name        | Type    | Size (Characters) | Allow Null (True/False) | Description   |
|--------|-------------|---------|-------------------|-------------------------|---|
| 1      | GROUPNAME   | varchar | 24                | False                   | Owner Group Name  |
| 2      | PERMITGROUP | varchar | 24                | False                   | Trusted Group or Permitted groups to access Group owned samples |
| 3      | hSec        | int     | 10                | False                   | Security Handle   |

## OLDMESSAGEQUEUE

Old Privileges Listing for Individuals Primary Keys (Not used 6.0+)

### Primary Keys

| Sr.No. | Name             | Type          | Size (Characters) | Allow Null (True/False) | Description |
|--------|------------------|---------------|-------------------|-------------------------|-------------|
| 1      | MsgNumber        | int           | 10                | True                    |             |
| 2      | MsgType          | nvarchar      | 25                | False                   |             |
| 3      | Sender           | nvarchar      | 50                | True                    |             |
| 4      | Destination      | nvarchar      | 50                | True                    |             |
| 5      | MessageBody      | ntext         | 1073741823        | True                    |             |
| 6      | Status           | nvarchar      | 50                | True                    |             |
| 7      | Detail1          | nvarchar      | 40                | True                    |             |
| 8      | Detail2          | nvarchar      | 40                | True                    |             |
| 9      | Detail3          | nvarchar      | 40                | True                    |             |
| 10     | StatusUpdateDate | smalldatetime |                   | True                    |             |

|    |                 |               |    |       |  |
|----|-----------------|---------------|----|-------|--|
| 11 | MsgLocked       | smallint      |    | True  |  |
| 12 | MsgLockDateTime | smalldatetime |    | True  |  |
| 13 | CreateDateTime  | smalldatetime |    | False |  |
| 14 | CreateUserID    | nvarchar      | 12 | True  |  |
| 15 | ModDateTime     | smalldatetime |    | True  |  |
| 16 | ModUserID       | nvarchar      | 12 | True  |  |
| 17 | MoveToArchive   | int           | 10 | True  |  |

## PASSHISTORY

Table to track password changes for each user. (Not used in 6.0+)

### Primary Keys

- UNNUMBER

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description                  |
|--------|-------------|----------|-------------------|-------------------------|------------------------------|
| 1      | UNNUMBER    | int      | 10                | False                   | User ID                      |
| 2      | OLDPASSWORD | varchar  | 11                | False                   | Old Password                 |
| 3      | LOCKOUT     | smallint |                   | False                   | Password Lockout option flag |
| 4      | MODDATE     | datetime |                   | True                    | Last Modified Date           |
| 5      | hSec        | int      | 10                | False                   | Security Handle              |

## PICKLISTS

Pick List Maintenance table

### Primary Keys

- PLNAME
- PLITEMNO

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description                |
|--------|----------|----------|-------------------|-------------------------|----------------------------|
| 1      | PLNAME   | varchar  | 20                | False                   | Pick List Name             |
| 2      | PLITEMNO | smallint |                   | False                   | Pick List Item Number      |
| 3      | PLITEM   | varchar  | 50                | False                   | Pick List Item Name        |
| 4      | PLDESCR  | varchar  | 50                | True                    | Pick List Item Description |
| 5      | hSec     | int      | 10                | False                   | Security Handle            |
| 6      | MODDATE  | datetime |                   | True                    | ModDate                    |

## PRIVS

System Privileges list that can be assigned/ revoked to each LABWORKS user

### Primary Keys

- URVALUE

| Sr.No. | Name      | Type    | Size (Characters) | Allow Null (True/False) | Description           |
|--------|-----------|---------|-------------------|-------------------------|-----------------------|
| 1      | URVALUE   | varchar | 16                | False                   | User ID               |
| 2      | PRIVDESCR | varchar | 50                | False                   | Privilege Description |

## PSAUDIT

Audit Trail details for Process Scheduler

### Primary Keys

- AUDITID

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description                  |
|--------|-------------|----------|-------------------|-------------------------|------------------------------|
| 1      | AUDITID     | int      | 10                | False                   | Audit Trail ID               |
| 2      | PSSAMPLEID  | int      | 10                | True                    | Process Scheduler Sample ID  |
| 3      | PSAUDITITEM | varchar  | 50                | True                    | Process Scheduler Audit Item |
| 4      | PSAUDITTIME | datetime |                   | True                    | Process Scheduler Audit Time |
| 5      | PSMACHINEID | varchar  | 60                | True                    | Process Scheduler Machine ID |
| 6      | PSUSER      | varchar  | 24                | True                    | Process Scheduler User       |
| 7      | hSec        | int      | 10                | False                   | Security Handle              |
| 8      | PSSAMPNO    | varchar  | 7                 | True                    | PS Sample ID                 |

## PSCONTAINER

Audit Trail details for Process Scheduler

### Primary Keys

- ID

| Sr.No. | Name       | Type | Size (Characters) | Allow Null (True/False) | Description       |
|--------|------------|------|-------------------|-------------------------|-------------------|
| 1      | PSSAMPLEID | int  | 10                | True                    | Process Scheduler |

|   |                     |         |      |       | Sample Identifier                       |
|---|---------------------|---------|------|-------|---|
| 2 | PSCONTAINERINDEX    | int     | 10   | False | Process Scheduler Container Index       |
| 3 | PSCONTAINERNLABELS  | int     | 10   | False | Process Scheduler Container Labels      |
| 4 | PSCONTAINERDESC     | varchar | 20   | True  | Process Scheduler Container Description |
| 5 | PSCONTAINERANALYSES | varchar | 4096 | True  | Process Scheduler Container Analysis    |
| 6 | PSCONTAINERCOMMENT  | varchar | 30   | True  | Process Scheduler Container Comment     |
| 7 | hSec                | int     | 10   | False | Security Handle                         |
| 8 | PSSAMPNO            | varchar | 7    | True  |   |
| 9 | ID                  | int     | 10   | False |   |

## PSCONTAINER\_PRELOG

Table is used to schedule samples from the Process Scheduler module

### Primary Keys

- PSID
- PSTIME
- PSLOCCODE
- PSINTERVALTYPE
- PSCONTAINERINDEX

| Sr.No. | Name                | Type     | Size (Characters) | Allow Null (True/False) | Description     |
|--------|---------------------|----------|-------------------|-------------------------|-----------------|
| 1      | PSID                | varchar  | 20                | False                   |                 |
| 2      | PSTIME              | datetime |                   | False                   |                 |
| 3      | PSLOCCODE           | varchar  | 24                | False                   |                 |
| 4      | PSINTERVALTYPE      | varchar  | 10                | False                   |                 |
| 5      | PSCONTAINERINDEX    | int      | 10                | False                   |                 |
| 6      | PSCONTAINERNLABELS  | int      | 10                | False                   |                 |
| 7      | PSCONTAINERDESC     | varchar  | 20                | True                    |                 |
| 8      | PSCONTAINERANALYSES | varchar  | 4096              | True                    |                 |
| 9      | PSCONTAINERCOMMENT  | varchar  | 30                | True                    |                 |
| 10     | hSec                | int      | 10                | False                   | Security Handle |

## PSPRIORIT Y

User-defined Priority Definitions for Process Scheduler associated with priority number. No user-interface available for this table in LABWORKS

### Primary Keys

- PSLPRIORITY

| Sr.No. | Name             | Type    | Size (Characters) | Allow Null (True/False) | Description                             |
|--------|------------------|---------|-------------------|-------------------------|---|
| 1      | PSLPRIORITY      | int     | 10                | False                   | Process Scheduler Priority              |
| 2      | PSPRIORITYAB REV | varchar | 10                | True                    | Process Scheduler Priority Abbreviation |
| 3      | PSPRIORITYDE SCR | varchar | 50                | True                    | Process Scheduler Priority Description  |
| 4      | hSec             | int     | 10                | False                   | Security Handle                         |

## PSSCHEDULE

Scheduled Samples for Process Scheduler

### Primary Keys

- PSSAMPLEID

| Sr.No. | Name              | Type     | Size (Characters) | Allow Null (True/False) | Description          |
|--------|-------------------|----------|-------------------|-------------------------|----------------------|
| 1      | PSSAMPLEID        | int      | 10                | False                   | Scheduler Sample ID  |
| 2      | PSSAMPNO          | varchar  | 7                 | True                    | LABWORKS Sample ID   |
| 3      | PSPRIORITY        | int      | 10                | False                   | Scheduler Priority   |
| 4      | PSOWNER           | varchar  | 24                | True                    | Scheduler Owner      |
| 5      | PSLOCODE          | varchar  | 24                | False                   | Location code        |
| 6      | PSLOCDESCR        | varchar  | 60                | True                    | Location Description |
| 7      | PSLOCOWNER        | varchar  | 24                | True                    | Location Owner       |
| 8      | PSNUMBEROFL ABELS | smallint |                   | False                   | Number of Labels     |
| 9      | PSSTATUS          | varchar  | 20                | True                    | Sample Status        |
| 10     | PSREQTIME         | datetime |                   | True                    | Request Time         |
| 11     | PSCOLOKTIME       | datetime |                   | True                    | Collection OK Time   |
| 12     | PSCOLTIME         | datetime |                   | True                    | Collection Time      |
| 13     | PSSUBTIME         | datetime |                   | True                    | Submittal Time       |
| 14     | PSANLDONETI ME    | datetime |                   | True                    | Analysis done time   |
| 15     | PSLABRELEAS       | datetime |                   | True                    |                      |

|    | ETIME           |          |      |       |                                   |
|----|-----------------|----------|------|-------|-----------------------------------|
| 16 | PSPRODUCTOKTIME | datetime |      | True  | Production OK Time                |
| 17 | PSPARENTID      | varchar  | 10   | True  |                                   |
| 18 | PSPAUSED        | smallint |      | False | Paused option flag                |
| 19 | PSANALYSES      | varchar  | 4096 | True  | Analyses list                     |
| 20 | PSANALYSES2     | varchar  | 255  | True  |                                   |
| 21 | PSCOMMENT       | varchar  | 255  | True  | Comments                          |
| 22 | PSSPARETIME     | datetime |      | True  |                                   |
| 23 | PSCUSTOMER      | varchar  | 50   | True  | Customer                          |
| 24 | PSSHIPTIME      | datetime |      | True  | Ship Time                         |
| 25 | PSDISABLED      | smallint |      | False | Scheduler Disable Option flag     |
| 26 | PSOKTOCOLLECT   | smallint |      | False | Ok to Collect Status Option       |
| 27 | PSUSER1         | varchar  | 50   | True  |                                   |
| 28 | PSUSER2         | varchar  | 50   | True  |                                   |
| 29 | PSUSER3         | varchar  | 50   | True  |                                   |
| 30 | PSUSER4         | varchar  | 50   | True  |                                   |
| 31 | PSUSERNUMBER1   | real     |      | True  |                                   |
| 32 | PSUSERNUMBERT2  | real     |      | True  |                                   |
| 33 | PSPRELOGBATCH   | varchar  | 30   | True  | Login Batch                       |
| 34 | PSORIGINALTIME  | datetime |      | True  | Original schedule time for sample |
| 35 | hSec            | int      | 10   | False | Security Handle                   |
| 36 | PSMODDATE       | datetime |      | True  |                                   |

## PSSHelfLife

Help File for Process Scheduler

### Primary Keys

- PSSHelfLifeID

| Sr.No. | Name               | Type     | Size (Characters) | Allow Null (True/False) | Description                            |
|--------|--------------------|----------|-------------------|-------------------------|--|
| 1      | PSSHelfLifeID      | int      | 10                | False                   | Process Scheduler Help File Identifier |
| 2      | PSSAMPLEID         | int      | 10                | True                    | Process Scheduler Sample Identifier    |
| 3      | PSSAMPNO           | nvarchar | 7                 | True                    | Process Scheduler Sample Number        |
| 4      | PSID               | nvarchar | 50                | True                    | Process Scheduler Identifier           |
| 5      | PSSHelfLife_Offset | real     |                   | True                    | Process Scheduler Help                 |

|   |                   |          |      |      | File Offset                         |
|---|-------------------|----------|------|------|-------------------------------------|
| 6 | PSANALYSES        | varchar  | 4096 | True | Process Scheduler Analysis          |
| 7 | PSCOMMENT         | nvarchar | 50   | True | Process Scheduler Comment           |
| 8 | PSMASTERTEM PLATE | int      | 10   | True | Process Scheduler Master Template   |
| 9 | PSMASTERID        | int      | 10   | True | Process Scheduler Master Identifier |

## PSTIMEHEAD

Timed Sample detailed information for Process Scheduler

### Primary Keys

- PSTIMEHEADID

| Sr.No. | Name              | Type     | Size (Characters) | Allow Null (True/False) | Description                  |
|--------|-------------------|----------|-------------------|-------------------------|------------------------------|
| 1      | PSTIMEHEADID      | int      | 10                | False                   | Auto key for table           |
| 2      | PSID              | varchar  | 20                | False                   | Process Scheduler Group ID   |
| 3      | PSTIME            | datetime |                   | False                   | Schedule Time                |
| 4      | PSLOCODE          | varchar  | 24                | False                   | Location Code                |
| 5      | PSINTERVALTY PE   | varchar  | 10                | False                   | s                            |
| 6      | PSLOCDESCR        | varchar  | 60                | True                    | Location Description         |
| 7      | PSLOCOWNER        | varchar  | 24                | True                    | s                            |
| 8      | PSNUMBEROFL ABELS | smallint |                   | False                   | Number of Labels             |
| 9      | PSPRIORITY        | int      | 10                | False                   | s                            |
| 10     | PSOWNER           | varchar  | 24                | True                    | Schedule Owner               |
| 11     | PSCOMMENT         | varchar  | 255               | True                    | Comments                     |
| 12     | PSANALYSES        | varchar  | 4096              | True                    | Scheduler command            |
| 13     | PSANALYSES2       | varchar  | 255               | True                    | Scheduler command parameters |
| 14     | PSEVENT           | smallint |                   | False                   | Scheduler Event              |
| 15     | PSCUSTOMER        | varchar  | 50                | True                    | Customer                     |
| 16     | PSOKTOCOLLE CT    | int      | 10                | False                   | OK to collect                |
| 17     | PSUSER1           | varchar  | 50                | True                    |                              |
| 18     | PSUSER2           | varchar  | 50                | True                    |                              |
| 19     | PSUSER3           | varchar  | 50                | True                    |                              |
| 20     | PSUSER4           | varchar  | 50                | True                    |                              |
| 21     | PSUSERNUMB ER1    | real     |                   | True                    |                              |
| 22     | PSUSERNUMB        | real     |                   | True                    |                              |

|    |                   |          |     |       |                 |
|----|-------------------|----------|-----|-------|-----------------|
|    | ER2               |          |     |       |                 |
| 23 | PSPRELOGBAT<br>CH | varchar  | 30  | True  |                 |
| 24 | hSec              | int      | 10  | False | Security Handle |
| 25 | PSACTIVEFRO<br>M  | datetime |     | True  |                 |
| 26 | PSACTIVETO        | datetime |     | True  |                 |
| 27 | PRINTERNAME       | varchar  | 100 | True  |                 |
| 28 | LABELNAME         | varchar  | 100 | True  |                 |
| 29 | LW_PROJECTI<br>D  | int      | 10  | True  |                 |

## PSTIMEHEADEXTENSION

### Primary Keys

- PSTIMEEXTID

| Sr.No. | Name               | Type    | Size<br>(Characters) | Allow Null<br>(True/False) | Description |
|--------|--------------------|---------|----------------------|----------------------------|-------------|
| 1      | PSTIMEEXTID        | int     | 10                   | False                      |             |
| 2      | PSTIMEHEADID       | int     | 10                   | False                      |             |
| 3      | PSINTERVALTY<br>PE | varchar | 10                   | False                      |             |
| 4      | PSINTERVAL         | varchar | 20                   | False                      |             |
| 5      | PSANALYSES         | varchar | 4000                 | False                      |             |

## PSTIMEMAIN

Timed Samples listing in Process Scheduler

### Primary Keys

- PSID
- PSTIME
- PSINTERVALTYPE

| Sr.No. | Name               | Type     | Size<br>(Characters) | Allow Null<br>(True/False) | Description                |
|--------|--------------------|----------|----------------------|----------------------------|----------------------------|
| 1      | PSID               | varchar  | 20                   | False                      | Process Scheduler Group ID |
| 2      | PSTIME             | datetime |                      | False                      | Schedule Time              |
| 3      | PSINTERVAL         | varchar  | 20                   | True                       | Interval                   |
| 4      | PSINTERVALTY<br>PE | varchar  | 10                   | False                      | Interval Type              |
| 5      | PSSTARTTIME        | datetime |                      | True                       | Schedule Start Time        |
| 6      | PSENDTIME          | datetime |                      | True                       | Schedule End Time          |
| 7      | PSENABLED          | smallint |                      | False                      | Schedule Enable Option     |
| 8      | hSec               | int      | 10                   | False                      | Security Handle            |
| 9      | LW_PROJECTO        | smallint |                      | True                       |                            |

|    |              |     |    |      |  |
|----|--------------|-----|----|------|--|
|    | VVERRIDE     |     |    |      |  |
| 10 | LW_PROJECTID | int | 10 | True |  |

## PTExperience

Experience of each Personal Training Analysts configured in LABWORKS Personal Training module

### Primary Keys

- Initials
- Lab
- StartDate

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description             |
|--------|------------|----------|-------------------|-------------------------|-------------------------|
| 1      | Initials   | varchar  | 50                | False                   | Analyst Initials        |
| 2      | Lab        | varchar  | 40                | False                   | Laboratory name         |
| 3      | StartDate  | datetime |                   | False                   | Training Start Date     |
| 4      | EndDate    | datetime |                   | True                    | Training End Date       |
| 5      | Position   | varchar  | 30                | True                    | Position of the Analyst |
| 6      | Experience | varchar  | 255               | True                    | Experience in years     |
| 7      | hSec       | int      | 10                | False                   | Security Handle         |

## PTLicense

License details of each Personal Training Analyst of LABWORKS

### Primary Keys

- Initials
- License
- Granted

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description             |
|--------|-----------|----------|-------------------|-------------------------|-------------------------|
| 1      | Initials  | varchar  | 50                | False                   | Analyst Initials        |
| 2      | License   | varchar  | 40                | False                   | License                 |
| 3      | Granted   | datetime |                   | False                   | License Grant Date      |
| 4      | Expire    | datetime |                   | True                    | License Expiration Date |
| 5      | LicenseNo | varchar  | 30                | True                    | License Number          |
| 6      | hSec      | int      | 10                | False                   | Security Handle         |

## PTSchools

Defined Schools in Personal Training module of LABWORKS

### Primary Keys

- SchoolType

| Sr.No. | Name       | Type    | Size (Characters) | Allow Null (True/False) | Description        |
|--------|------------|---------|-------------------|-------------------------|--------------------|
| 1      | SchoolType | varchar | 25                | False                   | School Type        |
| 2      | SchoolDesc | varchar | 40                | True                    | School Description |
| 3      | hSec       | int     | 10                | False                   | Security Handle    |

## PTTraining

List of defined Personal Training Analysts in Personal Training module of LABWORKS. The user is referenced from LABWORKS User list

### Primary Keys

- Initials
- SchoolType
- DateAttended

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description      |
|--------|--------------|----------|-------------------|-------------------------|------------------|
| 1      | Initials     | varchar  | 50                | False                   | Analyst Initials |
| 2      | SchoolType   | varchar  | 25                | False                   | School Type      |
| 3      | DateAttended | datetime |                   | False                   | Attended Date    |
| 4      | DateEnded    | datetime |                   | True                    | End Date         |
| 5      | SchoolName   | varchar  | 40                | True                    | School Name      |
| 6      | hSec         | int      | 10                | False                   | Security Handle  |
| 7      | SchoolDesc   | varchar  | 40                | True                    |                  |

## QUALIFIERS

Qualifiers

### Primary Keys

- equationname

| Sr.No. | Name         | Type    | Size (Characters) | Allow Null (True/False) | Description   |
|--------|--------------|---------|-------------------|-------------------------|---------------|
| 1      | equationname | varchar | 50                | False                   | Equation Name |
| 2      | equation     | varchar | 200               | True                    | Equation      |
| 3      | qualifier    | varchar | 5                 | True                    | Qualifier     |
| 4      | acode        | varchar | 24                | True                    | Analysis Code |

## REASONMASTER

AuditTrail Reasons

### Primary Keys

- ReasonID

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description  |
|--------|--------------|----------|-------------------|-------------------------|--------------|
| 1      | ReasonID     | int      | 10                | False                   | Reason Index |
| 2      | ReasonDesc   | varchar  | 255               | True                    | Description  |
| 3      | UseTimeStamp | datetime |                   | True                    | Last Used    |
| 4      | REASONORDER  | int      | 10                | False                   | Sort Order   |

## REPLICATEGRAPHCONFIG

This is the Replicate configuration table. It stores replicate configuration Sample, Analysis code and Analyte in xml format

### Primary Keys

- SAMPNO
- ACODE
- ANALYTE

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description                           |
|--------|--------------|----------|-------------------|-------------------------|---------------------------------------|
| 1      | SAMPNO       | varchar  | 7                 | False                   | Sample ID                             |
| 2      | ACODE        | varchar  | 24                | False                   | Analysis Code                         |
| 3      | ANALYTE      | varchar  | 100               | False                   | Analyte Name                          |
| 4      | GRAPHCONFIG  | text     | 2147483647        | True                    | Replicate configuration in xml format |
| 5      | CREATED_BY   | varchar  | 12                | True                    | Created user                          |
| 6      | CREATED_DATE | datetime |                   | True                    | Creation date                         |
| 7      | MODUSER      | varchar  | 12                | True                    | Last modified user                    |
| 8      | MODDATE      | datetime |                   | True                    | Last modified date                    |
| 9      | HSEC         | int      | 10                | True                    | Security Handle                       |

## REPORTHEAD

### Primary Keys

- REPORTNUMBER

| Sr.No. | Name       | Type | Size (Characters) | Allow Null (True/False) | Description |
|--------|------------|------|-------------------|-------------------------|-------------|
| 1      | REPORTNUMB | int  | 10                | False                   |             |

|   |                       |          |    |      |  |
|---|-----------------------|----------|----|------|--|
|   | ER                    |          |    |      |  |
| 2 | REPORTTYPE            | varchar  | 24 | True |  |
| 3 | REPORTDESC<br>RIPTION | varchar  | 60 | True |  |
| 4 | REPORTDATE            | datetime |    | True |  |
| 5 | REPORTUSER            | varchar  | 12 | True |  |
| 6 | hSec                  | int      | 10 | True |  |

## REPORTSAMPS

### Primary Keys

- REPORTNUMBER
- RSAMPNO

| Sr.No. | Name             | Type    | Size<br>(Characters) | Allow Null<br>(True/False) | Description |
|--------|------------------|---------|----------------------|----------------------------|-------------|
| 1      | REPORTNUMB<br>ER | int     | 10                   | False                      |             |
| 2      | RSAMPNO          | varchar | 7                    | False                      |             |

## RESULT

This is the main results table. It stores results and violation information. For single component tests, the Analysis Name (not code) and ANALYTE field are the same. For multi-component tests, the ACODE and ANALYTE fields contain their described values

### Primary Keys

- SAMPNO
- ACODE
- ANALYTE
- RESULTPART
- REPLNUM

| Sr.No. | Name      | Type     | Size<br>(Characters) | Allow Null<br>(True/False) | Description             |
|--------|-----------|----------|----------------------|----------------------------|-------------------------|
| 1      | SAMPNO    | varchar  | 7                    | False                      | Sample ID               |
| 2      | ACODE     | varchar  | 24                   | False                      | Analysis Code           |
| 3      | ANALYTE   | varchar  | 100                  | False                      | Analyte Name            |
| 4      | RESULT    | varchar  | 14                   | True                       | Result 1                |
| 5      | RESULT2   | varchar  | 14                   | True                       | Result 2                |
| 6      | QUALIFY   | varchar  | 14                   | True                       |                         |
| 7      | MDL       | varchar  | 14                   | True                       | Minimum Detection Limit |
| 8      | VIOLTYPE  | smallint |                      | False                      | Violation Type          |
| 9      | VIOLVALUE | varchar  | 14                   | True                       | Violation Value         |
| 10     | VIOLDATE  | datetime |                      | True                       | Violation Date          |
| 11     | VIOLUSER  | varchar  | 12                   | True                       | Violation User          |
| 12     | RLTNUM    | smallint |                      | False                      | Result Number           |
| 13     | RMODDATE  | datetime |                      | True                       | Result Modified Date    |
| 14     | RMODUSER  | varchar  | 12                   | True                       | Result Modified         |

|    |                 |          |     |       | User                    |
|----|-----------------|----------|-----|-------|-------------------------|
| 15 | DILFACTOR       | real     |     | False | Dilution Factor         |
| 16 | RAWRESULT       | varchar  | 14  | True  | Raw Result              |
| 17 | STARTDATE       | datetime |     | True  | Start Date              |
| 18 | ENDDATE         | datetime |     | True  | End Date                |
| 19 | ANALYST         | varchar  | 12  | True  | Analyst                 |
| 20 | hSec            | int      | 10  | False | Security Handle         |
| 21 | PQL             | varchar  | 16  | True  | PQL                     |
| 22 | RAWMDL          | varchar  | 16  | True  | Untreated MDL           |
| 23 | RAWPQL          | varchar  | 16  | True  | Untreated PQL           |
| 24 | RLTUNIT         | varchar  | 16  | True  | Units for Result        |
| 25 | RLTSOURCE       | varchar  | 255 | True  | Soure of result         |
| 26 | RESULTPART      | varchar  | 8   | False | Type of Result          |
| 27 | REPLNUM         | int      | 10  | False | Replicate Number        |
| 28 | RESULTCHECKSUM  | varchar  | 40  | True  | CheckSum                |
| 29 | CHECKSUMVERSION | int      | 10  | False | CheckSum Version        |
| 30 | AREF            | varchar  | 50  | True  | Result method reference |

## RESULTSPECS

Specifications for Results

### Primary Keys

- OBJECTTYPE
- OBJECTID
- SPECNAME
- ANALYSISISCODE
- ANALYTENAME
- RESULTPART

| Sr.No. | Name           | Type    | Size (Characters) | Allow Null (True/False) | Description     |
|--------|----------------|---------|-------------------|-------------------------|-----------------|
| 1      | OBJECTTYPE     | varchar | 12                | False                   | Type            |
| 2      | OBJECTID       | varchar | 24                | False                   | Identifier      |
| 3      | SPECNAME       | varchar | 24                | False                   | Type of Spec    |
| 4      | ANALYSISISCODE | varchar | 24                | False                   | Analysis Code   |
| 5      | ANALYTENAME    | varchar | 100               | False                   | Analyte Name    |
| 6      | RESULTPART     | varchar | 12                | False                   | Result Part     |
| 7      | NUMVALUE1      | varchar | 14                | True                    | Spec Value 1    |
| 8      | NUMVALUE2      | varchar | 14                | True                    | Spec Value 2    |
| 9      | TEXTVALUE      | varchar | 1024              | True                    | Text Value      |
| 10     | HSEC           | bigint  |                   | False                   | Security Handle |

## RLDEFANL

Reporting Limit Default Analytes listing for Project Analyte Management (PAM) Groups

### Primary Keys

- RLGROUP
- ACODE
- ANALYTE

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description                |
|--------|-------------|----------|-------------------|-------------------------|----------------------------|
| 1      | RLGROUP     | varchar  | 16                | False                   | Report Limiting Group Name |
| 2      | ACODE       | varchar  | 24                | False                   | Analysis Code              |
| 3      | ANALYTE     | varchar  | 100               | False                   | Analyte                    |
| 4      | REPLIMIT    | real     |                   | False                   | Report Limit               |
| 5      | LTRLRESULT  | varchar  | 14                | True                    |                            |
| 6      | LTRLQUAL    | varchar  | 6                 | True                    |                            |
| 7      | GTRLQUAL    | varchar  | 6                 | True                    |                            |
| 8      | LTMDLRESULT | varchar  | 14                | True                    |                            |
| 9      | LTMDLQUAL   | varchar  | 6                 | True                    |                            |
| 10     | ANLNUM      | smallint |                   | False                   | Analyte Number             |
| 11     | hSec        | int      | 10                | False                   | Security Handle            |

## RLDEFHED

Reporting Limit Project Analyte Management Group listing

### Primary Keys

- RLGROUP

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description                       |
|--------|--------------|----------|-------------------|-------------------------|-----------------------------------|
| 1      | RLGROUP      | varchar  | 16                | False                   | Report Limiting Group Name        |
| 2      | RLDESCR      | varchar  | 40                | True                    | Report Limiting Group Description |
| 3      | MODDATE      | datetime |                   | True                    | Last Modified Date                |
| 4      | MODUSER      | varchar  | 12                | True                    | Last Modified User                |
| 5      | hSec         | int      | 10                | False                   | Security Handle                   |
| 6      | LW_PROJECTID | int      | 10                | True                    |                                   |

## RLSMPANL

Reporting Limit Sample Analyte details for Project Analyte Management Module

### Primary Keys

- SAMPNO
- ACODE
- ANALYTE

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description     |
|--------|-------------|----------|-------------------|-------------------------|-----------------|
| 1      | SAMPNO      | varchar  | 7                 | False                   | Sample ID       |
| 2      | ACODE       | varchar  | 24                | False                   | Analysis Code   |
| 3      | ANALYTE     | varchar  | 100               | False                   | Analyte         |
| 4      | REPLIMIT    | real     |                   | False                   | Reporting Limit |
| 5      | LTRLRESULT  | varchar  | 14                | True                    |                 |
| 6      | LTRLQUAL    | varchar  | 6                 | True                    |                 |
| 7      | GTRLQUAL    | varchar  | 6                 | True                    |                 |
| 8      | LTMDLRESULT | varchar  | 14                | True                    |                 |
| 9      | LTMDLQUAL   | varchar  | 6                 | True                    |                 |
| 10     | ANLNUM      | smallint |                   | False                   | Analyte Number  |
| 11     | DILFACTOR   | real     |                   | False                   | Dilution Factor |
| 12     | hSec        | int      | 10                | False                   | Security Handle |

## RLSMPHED

Reporting Limit Sample Header details for Project Analyte Management Module

### Primary Keys

- SAMPNO

| Sr.No. | Name    | Type     | Size (Characters) | Allow Null (True/False) | Description                       |
|--------|---------|----------|-------------------|-------------------------|-----------------------------------|
| 1      | SAMPNO  | varchar  | 7                 | False                   | Sample ID                         |
| 2      | RLGROUP | varchar  | 16                | False                   | Reporting Limit Group Name        |
| 3      | RLDESCR | varchar  | 40                | True                    | Reporting Limit Group Description |
| 4      | MODDATE | datetime |                   | True                    | Last Modified Date                |
| 5      | MODUSER | varchar  | 12                | True                    | Last Modified User                |
| 6      | hSec    | int      | 10                | False                   | Security Handle                   |

## RLTSPECS

Reporting Limit Specifications for Project Analyte Management Module. (Migrated to ResultSpecs in 6.2)

### Primary Keys

- LOCCODE
- ACODE
- ANLNAME

| Sr.No. | Name    | Type    | Size (Characters) | Allow Null (True/False) | Description         |
|--------|---------|---------|-------------------|-------------------------|---------------------|
| 1      | LOCCODE | varchar | 24                | False                   | Location Code       |
| 2      | ACODE   | varchar | 24                | False                   | Analysis Code       |
| 3      | ANLNAME | varchar | 40                | False                   | Analyte Name        |
| 4      | LSPEC   | varchar | 14                | True                    | Lower Specification |

|    |         |          |    |       | Limit                     |
|----|---------|----------|----|-------|---------------------------|
| 5  | LWARN   | varchar  | 14 | True  | Lower Warning Limit       |
| 6  | TARGET  | varchar  | 14 | True  | Target Value              |
| 7  | UWARN   | varchar  | 14 | True  | Upper Warning Limit       |
| 8  | USPEC   | varchar  | 14 | True  | Upper Specification Limit |
| 9  | MODDATE | datetime |    | False | Last Modified Date        |
| 10 | MODUSER | varchar  | 12 | False | Last Modified User        |
| 11 | hSec    | int      | 10 | False | Security Handle           |

## SAMPLE

The SAMPLE table stores data about logged in samples. As a sample is logged in, a unique SampleID is generated and stored in the SAMPNO field. The LOCCODE information is copied into the SAMPLE table with the ability to modify the LOCLIST table during the login process

### Primary Keys

- SAMPNO

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description                |
|--------|-----------|----------|-------------------|-------------------------|----------------------------|
| 1      | SAMPNO    | varchar  | 7                 | False                   | Sample ID                  |
| 2      | OWNER     | varchar  | 24                | True                    | Sample Owner               |
| 3      | SSTATUS   | varchar  | 1                 | False                   | Sample Status              |
| 4      | LOCCODE   | varchar  | 24                | True                    | Sample Point Code          |
| 5      | LOCDESCR  | varchar  | 60                | True                    | Sample Point Description   |
| 6      | LOGBATCH  | varchar  | 300               | True                    | Login Batch Name           |
| 7      | LOGUSER   | varchar  | 12                | True                    | Login User                 |
| 8      | SUBDATE   | datetime |                   | True                    | Sample Submission Date     |
| 9      | SAMPCOL   | varchar  | 24                | True                    | Sample Collector           |
| 10     | COLDATE   | datetime |                   | True                    | Sample Collection Date     |
| 11     | RDUEDATE  | datetime |                   | True                    | Due Date                   |
| 12     | DUEDATE   | datetime |                   | True                    | Sample Due Date            |
| 13     | DOVAL     | smallint |                   | False                   | Do Validation Option Value |
| 14     | VALUSER   | varchar  | 12                | True                    | Sample Validator           |
| 15     | VALDATE   | datetime |                   | True                    | Sample Validation Date     |
| 16     | REPNAME   | varchar  | 24                | True                    | Report Name                |
| 17     | REPCOPIES | smallint |                   | False                   | Report Copies              |
| 18     | DCOPY     | smallint |                   | False                   | Do Disk Copy Option Value  |
| 19     | REPDATE   | datetime |                   | True                    | Report Date                |
| 20     | REPADD1   | varchar  | 40                | True                    | Report Address Line 1      |

|    |                   |          |      |       |   |
|----|-------------------|----------|------|-------|---|
| 21 | REPADD2           | varchar  | 40   | True  | Report Address Line 2                                 |
| 22 | REPADD3           | varchar  | 40   | True  | Report Address Line 3                                 |
| 23 | REPADD4           | varchar  | 40   | True  | Report Address Line 4                                 |
| 24 | REPADD5           | varchar  | 40   | True  | Report Address Line 5                                 |
| 25 | DOINV             | smallint |      | False | Do Invoicing Option Value                             |
| 26 | INVNAME           | varchar  | 24   | True  | Invoice Name  |
| 27 | BILLRATE          | real     |      | False | Percentage of List price used for calculating charges |
| 28 | PRICELIST         | varchar  | 24   | True  | Price List Name                                       |
| 29 | INVDATE           | datetime |      | True  | Invoice Date  |
| 30 | INVNO             | int      | 10   | False | Invoice Number  |
| 31 | INVADD1           | varchar  | 40   | True  | Invoice Address Line 1                                |
| 32 | INVADD2           | varchar  | 40   | True  | Invoice Address Line 2                                |
| 33 | INVADD3           | varchar  | 40   | True  | Invoice Address Line 3                                |
| 34 | INVADD4           | varchar  | 40   | True  | Invoice Address Line 4                                |
| 35 | INVADD5           | varchar  | 40   | True  | Invoice Address Line 5                                |
| 36 | PONUMBER          | varchar  | 24   | True  | Purchase Order Number                                 |
| 37 | PROJECT           | varchar  | 24   | True  | Project Code  |
| 38 | DOSPEC            | smallint |      | False | Do Specification Check Option Value                   |
| 39 | COMTMASK          | varchar  | 24   | True  |   |
| 40 | EXPDATE           | datetime |      | True  | Expiration Date                                       |
| 41 | MODDATE           | datetime |      | True  | Last Modified Date                                    |
| 42 | MODUSER           | varchar  | 12   | True  | Last Modified User                                    |
| 43 | hSec              | int      | 10   | False | Security Handle                                       |
| 44 | CURRENT_STATE     | varchar  | 50   | True  | Sample Current State                                  |
| 45 | SREADOWNER        | varchar  | 24   | True  | Sample Read Owner                                     |
| 46 | LATITUDEREAL      | decimal  |      | True  | LATITUDEREAL  |
| 47 | LONGITUDEREAL     | decimal  |      | True  | LONGITUDEREAL   |
| 48 | LATITUDEEXPECTED  | decimal  |      | True  | LATITUDEEXPECTED                                      |
| 49 | LONGITUDEEXPECTED | decimal  |      | True  | LONGITUDEEXPECTED                                     |
| 50 | COLDUEDATE        | datetime |      | True  | Collection Due Date                                   |
| 51 | ADDRESS           | varchar  | 255  | True  | Address   |
| 52 | ADDRESSREAL       | varchar  | 255  | True  | Real Address  |
| 53 | IsReviewed        | smallint |      | False | Is reviewed   |
| 54 | SignUser          | int      | 10   | True  | Sign User Id  |
| 55 | SignDate          | datetime |      | True  | Sign Date   |
| 56 | SignReason        | nvarchar | 1024 | True  | Sign Reason   |

|    |                |          |     |       |                                   |
|----|----------------|----------|-----|-------|-----------------------------------|
| 57 | CTReport       | nvarchar | 255 | True  | Custody Tracking report path      |
| 58 | SPRIORITY      | int      | 10  | True  | Sample Priority                   |
| 59 | DEPARTMENT     | varchar  | 24  | True  | Department                        |
| 60 | NUMBEROFLABELS | int      | 10  | True  | Number of Labels                  |
| 61 | PSSTATUS       | varchar  | 20  | True  | Sample Status                     |
| 62 | REQTIME        | datetime |     | True  | Request Time                      |
| 63 | COLOKTIME      | datetime |     | True  | Collection OK Time                |
| 64 | LABRELEASETIME | datetime |     | True  | Date/Time                         |
| 65 | PRODUCTOKTIME  | datetime |     | True  | Production OK Time                |
| 66 | PARENTID       | varchar  | 10  | True  |                                   |
| 67 | PAUSED         | smallint |     | True  | Paused option flag                |
| 68 | CUSTOMER       | varchar  | 50  | True  | Customer                          |
| 69 | SHIPTIME       | datetime |     | True  | Ship Time                         |
| 70 | DISABLED       | smallint |     | False | Scheduler Disable Option flag     |
| 71 | OKTOCOLLECT    | smallint |     | True  | Ok to Collect Status Option       |
| 72 | ORIGINALTIME   | datetime |     | True  | Original schedule time for sample |
| 73 | CREATEDATE     | datetime |     | True  | Create date time                  |
| 74 | COMPLETEDDATE  | datetime |     | True  | Complete date time                |
| 75 | INITIALSTATE   | varchar  | 50  | True  | Initial State of sample           |
| 76 | LW_PROJECTID   | int      | 10  | True  |                                   |

## SAMPLELOGINGROUP

Prelogin Group Information

### Primary Keys

- GroupName

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description       |
|--------|------------------|----------|-------------------|-------------------------|-------------------|
| 1      | GroupName        | varchar  | 50                | False                   | Name              |
| 2      | GroupDescription | varchar  | 50                | True                    | Description       |
| 3      | GroupType        | varchar  | 50                | True                    | Type              |
| 4      | GroupXML         | text     | 2147483647        | True                    | XML Data          |
| 5      | MODDATE          | datetime |                   | False                   | Last Modified     |
| 6      | MODUSER          | varchar  | 50                | True                    | Last Modified By  |
| 7      | hSec             | int      | 10                | False                   | Security Handle   |
| 8      | TotalSamples     | int      | 10                | True                    | Number of Samples |

## SAMPMAILLIST

This table stores client (or mail list) data records associated with specific samples

### Primary Keys

- SAMPNO
- MLRNUM

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description  |
|--------|----------------|----------|-------------------|-------------------------|--|
| 1      | SAMPNO         | varchar  | 7                 | False                   | Sample ID  |
| 2      | MLRNUM         | smallint |                   | False                   | Mail list row ordinal for reference                                    |
| 3      | DOCTYPE        | varchar  | 24                | False                   | Mail list document type (FinalReport / Invoice / All)                  |
| 4      | ADDRTYPE       | varchar  | 24                | False                   | Mail list address type (Postal / Email / Fax / All)                    |
| 5      | PRIMARY        | smallint |                   | False                   | Address is primary for its doc type and addr type ( 0=false else=true) |
| 6      | ADDRESSEE      | varchar  | 50                | True                    | Name of addresses  |
| 7      | STREET1        | varchar  | 50                | True                    | First street address line  |
| 8      | STREET2        | varchar  | 50                | True                    | Second street address line   |
| 9      | CITY           | varchar  | 50                | True                    | City   |
| 10     | STATE          | varchar  | 50                | True                    | State State or province  |
| 11     | POST_CODE      | varchar  | 20                | True                    | Postal code (zip)  |
| 12     | COUNTRY        | varchar  | 50                | True                    | Country  |
| 13     | PHONE_NUM      | varchar  | 30                | True                    | Phone number   |
| 14     | FAX_NUM        | varchar  | 30                | True                    | Fax number   |
| 15     | EMAIL_ADDR     | varchar  | 50                | True                    | Email address  |
| 16     | CONTACT        | varchar  | 50                | True                    | Name of contact  |
| 17     | CONTACT_PHO NE | varchar  | 30                | True                    | Phone number for contact   |
| 18     | CONTACT_EMA IL | varchar  | 50                | True                    | Contact email address  |
| 19     | MODUSER        | varchar  | 12                | True                    | Row modified by  |
| 20     | MODDATE        | datetime |                   | True                    | Row modified on  |
| 21     | hSec           | int      | 10                | False                   | Security Handle  |

## SAMPRELOGINGRP

Prelogin Group Information

**Primary Keys**

- PreLogGroupName

| Sr.No. | Name                | Type     | Size (Characters) | Allow Null (True/False) | Description              |
|--------|---------------------|----------|-------------------|-------------------------|--------------------------|
| 1      | PreLogGroupName     | varchar  | 50                | False                   | Name                     |
| 2      | PreLogGroupXML      | text     | 2147483647        | True                    | XML Data                 |
| 3      | MODDATE             | datetime |                   | False                   | Last Modified            |
| 4      | MODUSER             | varchar  | 50                | True                    | Last Modified By         |
| 5      | hSec                | int      | 10                | False                   | Security Handle          |
| 6      | DESCRIPTION         | varchar  | 2000              | True                    | Group description        |
| 7      | STATUS              | varchar  | 20                | True                    | Group status             |
| 8      | PRELOGGROUPID       | numeric  |                   | False                   | Pre Login Group ID       |
| 9      | PreLogGroupCategory | varchar  | 50                | True                    | Pre Login Group Category |

**SECURITY\_EVENT****Primary Keys**

- SecEventID

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|----------------|----------|-------------------|-------------------------|-------------|
| 1      | SecEventID     | int      | 10                | False                   |             |
| 2      | SecPointID     | int      | 10                | False                   |             |
| 3      | Context        | varchar  | 50                | True                    |             |
| 4      | DateTime_Event | datetime |                   | True                    |             |
| 5      | Event_Machine  | varchar  | 50                | True                    |             |
| 6      | Event_UserID   | varchar  | 50                | True                    |             |
| 7      | Event_hSec     | int      | 10                | False                   |             |
| 8      | Detail1        | varchar  | 50                | True                    |             |
| 9      | Detail2        | varchar  | 50                | True                    |             |

**SECURITYLIC**

Security License table tracking down each machine ID

**Primary Keys**

- hLic

| Sr.No. | Name       | Type    | Size (Characters) | Allow Null (True/False) | Description             |
|--------|------------|---------|-------------------|-------------------------|-------------------------|
| 1      | hLic       | int     | 10                | False                   | Security License Number |
| 2      | MACHINE_ID | varchar | 40                | False                   | Machine ID              |
| 3      | USERID     | varchar | 40                | False                   | User ID                 |
| 4      | LIC_TYPE   | varchar | 16                | False                   | License Type            |

|   |            |          |  |       |                      |
|---|------------|----------|--|-------|----------------------|
| 5 | RENEW_DATE | datetime |  | False | License Renewal Date |
|---|------------|----------|--|-------|----------------------|

## SECURITYLOG

Session tracking details of LABWORKS.

### Primary Keys

- hSecLog

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description               |
|--------|----------------|----------|-------------------|-------------------------|---------------------------|
| 1      | hSecLog        | int      | 10                | False                   | Security Log ID           |
| 2      | EVENT_TYPE     | varchar  | 16                | False                   | Event Type                |
| 3      | EVENT_DATE     | datetime |                   | False                   | Event Date                |
| 4      | MACHINE_ID     | varchar  | 60                | True                    | Machine ID                |
| 5      | PROGRAM_ID     | varchar  | 40                | True                    | Program ID                |
| 6      | USERID         | varchar  | 40                | True                    | User ID                   |
| 7      | DETAIL1        | varchar  | 255               | True                    | Session event description |
| 8      | DETAIL2        | varchar  | 255               | True                    | Event action code         |
| 9      | ACTIVESESSIONS | int      | 10                | False                   | Active Sessions           |

## SESSIONPROCESSES

Session process details of LABWORKS

### Primary Keys

- WorkstationID
- ApplicationName

| Sr.No. | Name             | Type     | Size (Characters) | Allow Null (True/False) | Description            |
|--------|------------------|----------|-------------------|-------------------------|------------------------|
| 1      | WorkstationID    | nvarchar | 50                | False                   | WorkStation Identifier |
| 2      | ApplicationName  | nvarchar | 50                | False                   | Application Name       |
| 3      | ProcessName      | nvarchar | 50                | True                    | Process Name           |
| 4      | IsLoggedIn       | int      | 10                | True                    | Is Loggedin            |
| 5      | ProcessStartTime | datetime |                   | True                    | Process start time     |

## SESSIONS

Session details of LABWORKS

### Primary Keys

- WorkstationID

| Sr.No. | Name               | Type     | Size (Characters) | Allow Null (True/False) | Description            |
|--------|--------------------|----------|-------------------|-------------------------|------------------------|
| 1      | WorkstationID      | nvarchar | 50                | False                   | WorkStation Identifier |
| 2      | SessionType        | nvarchar | 50                | False                   | Session Type           |
| 3      | OpenDateTime       | datetime |                   | True                    | Open Date Time         |
| 4      | ActivityNotifyDate | datetime |                   | True                    | Activity Notify Date   |
| 5      | UserId             | int      | 10                | True                    | User Identifier        |

## SFRANGES

Ranges for rounding

### Primary Keys

- ACODE
- ANLNAME

| Sr.No. | Name    | Type    | Size (Characters) | Allow Null (True/False) | Description            |
|--------|---------|---------|-------------------|-------------------------|------------------------|
| 1      | ACODE   | varchar | 24                | False                   | Analysis Code          |
| 2      | ANLNAME | varchar | 100               | False                   | Analyte Name           |
| 3      | MRL     | real    |                   | False                   | Method Reporting Limit |
| 4      | XVAL    | varchar | 24                | False                   | Replacement Value      |
| 5      | RANGES  | text    | 2147483647        | True                    | XML Range Data         |

## SGTESTS

The SGTESTS table stores lists of analyses in sample analyses groups (#XXXXXX)

### Primary Keys

- ACODE
- SGACODE

| Sr.No. | Name    | Type     | Size (Characters) | Allow Null (True/False) | Description             |
|--------|---------|----------|-------------------|-------------------------|-------------------------|
| 1      | ACODE   | varchar  | 24                | False                   | Analysis Code           |
| 2      | SGACODE | varchar  | 24                | False                   | Study Group Test Code   |
| 3      | SGANUM  | smallint |                   | False                   | Study Group Test Number |
| 4      | hSec    | int      | 10                | False                   | Security Handle         |

## SIADEFLT

The Special Analysis Info Default (SIADEFLT) table stores information used with special information forms. An analysis special information form permits the creating of a data structure, which is specific to one or more analysis codes. The defaults for the special information form are stored in this table. (Moved to LabObjSpecInfo)

### Primary Keys

- ACODE
- SIFLDNUM

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description                  |
|--------|----------|----------|-------------------|-------------------------|------------------------------|
| 1      | ACODE    | varchar  | 24                | False                   | Analysis Code                |
| 2      | SIFLDNUM | smallint |                   | False                   | Special Information Field ID |
| 3      | FLDTITLE | varchar  | 80                | True                    | Default Field Name           |
| 4      | FLDVALUE | varchar  | 60                | True                    | Default Field Value          |
| 5      | MODDATE  | datetime |                   | True                    | Last Modified Date           |
| 6      | MODUSER  | varchar  | 12                | True                    | Last Modified User           |
| 7      | hSec     | int      | 10                | False                   | Security Handle              |

## SIDEFLT

Special Info default values for fields listing available in the Special Info form template definition.(Moved to LabObjSpecInfo)

### Primary Keys

- LOCCODE
- SIFLDNUM

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description                  |
|--------|----------|----------|-------------------|-------------------------|------------------------------|
| 1      | LOCCODE  | varchar  | 24                | False                   | Location Code                |
| 2      | SIFLDNUM | smallint |                   | False                   | Special Information Field ID |
| 3      | FLDTITLE | varchar  | 80                | True                    | Default Field Name           |
| 4      | FLDVALUE | varchar  | 60                | True                    | Default Field Value          |
| 5      | MODDATE  | datetime |                   | True                    | Last Modified Date           |
| 6      | MODUSER  | varchar  | 12                | True                    | Last Modified User           |
| 7      | hSec     | int      | 10                | False                   | Security Handle              |

## SIFORMDEF

Special Info Fields definition for each form

### Primary Keys

- SINFOFRM
- SIFLDNAME

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description  |
|--------|--------------|----------|-------------------|-------------------------|--|
| 1      | SINFOFRM     | varchar  | 24                | False                   | Special Information Form Name                            |
| 2      | FIELDNUM     | smallint |                   | False                   | Field ID   |
| 3      | FLDPROMPT    | varchar  | 80                | True                    | Field Prompt   |
| 4      | FLDTYPE      | varchar  | 2                 | True                    | Field Type   |
| 5      | FLDMAXCHARS  | smallint |                   | False                   | Maximum Characters for Field                             |
| 6      | FLDTOP       | int      | 10                | False                   | Top Coordinate for the Field                             |
| 7      | FLDLEFT      | int      | 10                | False                   | Left Coordinate for the Field                            |
| 8      | FLDFONTSIZE  | smallint |                   | False                   | Field Font Size  |
| 9      | FLDFONTPROPS | smallint |                   | False                   | Font Properties  |
| 10     | FLDFONTCOLOR | int      | 10                | False                   | Field Font Color   |
| 11     | FLDREQUIRED  | smallint |                   | False                   | Field Mandatory Flag                                     |
| 12     | FLDFONTNAME  | varchar  | 65                | True                    | Field Font Name  |
| 13     | CTLLENGTH    | int      | 10                | False                   | Field length   |
| 14     | FLDOOTHER    | varchar  | 20                | True                    | Other value associated with a field (ex: a picture file) |
| 15     | TABORDER     | smallint |                   | False                   | Tab Order for the Field                                  |
| 16     | hSec         | int      | 10                | False                   | Security Handle  |
| 17     | SIFLDNAME    | nvarchar | 85                | False                   | FieldName  |

## SIGNATURE\_OBJ

### Primary Keys

- SIGNATURE\_ID

| Sr.No. | Name             | Type   | Size (Characters) | Allow Null (True/False) | Description |
|--------|------------------|--------|-------------------|-------------------------|-------------|
| 1      | SIGNATURE_ID     | bigint |                   | False                   |             |
| 2      | SIGNATURE_OBJECT | image  | 2147483647        | True                    |             |

## SPECIALPRICELIST

Special Pricing

### Primary Keys

- PRICELIST\_NAME
- ACODE

| Sr.No. | Name           | Type    | Size (Characters) | Allow Null (True/False) | Description   |
|--------|----------------|---------|-------------------|-------------------------|---------------|
| 1      | PRICELIST_NAME | varchar | 24                | False                   | PriceList     |
| 2      | ACODE          | varchar | 24                | False                   | Analysis Code |
| 3      | APRICE         | float   |                   | False                   | Price         |

## SPECINFO

This table stores information from the special information fields. (Moved to LabObjSpecInfo)

### Primary Keys

- SAMPNO
- ACODE
- SIFLDNUM

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description                     |
|--------|----------|----------|-------------------|-------------------------|---------------------------------|
| 1      | SAMPNO   | varchar  | 7                 | False                   | Sample ID                       |
| 2      | ACODE    | varchar  | 24                | False                   | Analysis Code                   |
| 3      | SIFLDNUM | smallint |                   | False                   | Special Information Field ID    |
| 4      | FLDTITLE | varchar  | 80                | True                    | Special Information Field Name  |
| 5      | FLDVALUE | varchar  | 60                | True                    | Special Information Field Value |
| 6      | MODDATE  | datetime |                   | True                    | Last Modified Date              |
| 7      | MODUSER  | varchar  | 12                | True                    | Last Modified User              |
| 8      | hSec     | int      | 10                | False                   | Security Handle                 |

## SPECMASTER

Specification Definition

### Primary Keys

- SPECNAME
- VIOLTYPE

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description            |
|--------|----------------|----------|-------------------|-------------------------|------------------------|
| 1      | SPECNAME       | varchar  | 24                | False                   | Specification Name     |
| 2      | SPECTYPE       | varchar  | 12                | False                   | Type                   |
| 3      | UIDESCRIPTIION | varchar  | 40                | False                   | Description            |
| 4      | PRIORITY       | smallint |                   | False                   | Evaluation Priority    |
| 5      | SEVERITY       | varchar  | 1                 | False                   | Compatibility Severity |
| 6      | VIOLTYPE       | int      | 10                | False                   | Type                   |
| 7      | VIOLTYPE       | int      | 10                | False                   | Type                   |

## State\_Location

State Location

### Primary Keys

- Object\_Name
- State

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------------|----------|-------------------|-------------------------|-------------|
| 1      | Object_Name | nvarchar | 50                | False                   | Object Name |
| 2      | State       | nvarchar | 50                | False                   | State       |
| 3      | XLocation   | int      | 10                | True                    | X location  |
| 4      | YLocation   | int      | 10                | True                    | Y Location  |

## StateMaster

State Definitions

### Primary Keys

- StateName
- ObjectType

| Sr.No. | Name       | Type    | Size (Characters) | Allow Null (True/False) | Description                     |
|--------|------------|---------|-------------------|-------------------------|---------------------------------|
| 1      | StateName  | varchar | 50                | False                   | Name                            |
| 2      | StateType  | varchar | 50                | True                    | Type                            |
| 3      | StateDescr | varchar | 80                | True                    | Description                     |
| 4      | ObjectType | varchar | 50                | False                   | Object Type                     |
| 5      | Active     | int     | 10                | True                    | Is Active                       |
| 6      | Color      | int     | 10                | True                    | Color of the state              |
| 7      | SortOrder  | int     | 10                | True                    | Sort Order                      |
| 8      | SSTATUS    | varchar | 1                 | True                    | Sample Status                   |
| 9      | PSSTATUS   | varchar | 20                | True                    | Process Scheduler sample Status |

## StateTransitions

### State Definitions

#### Primary Keys

- ObjectType
- StartState
- EndState
- TransMode
- AutoPriority

| Sr.No. | Name              | Type    | Size (Characters) | Allow Null (True/False) | Description                   |
|--------|-------------------|---------|-------------------|-------------------------|-------------------------------|
| 1      | ObjectType        | varchar | 50                | False                   | Type                          |
| 2      | StartState        | varchar | 50                | False                   | Start                         |
| 3      | EndState          | varchar | 50                | False                   | End                           |
| 4      | TransMode         | varchar | 50                | False                   | Transition Type               |
| 5      | AutoPriority      | int     | 10                | False                   | Priority for AutoTransistions |
| 6      | AutoRules         | varchar | 255               | True                    | Method for evaluation         |
| 7      | ManualPrvs        | varchar | 255               | True                    | Prvs Required                 |
| 8      | ManualESignDialog | varchar | 255               | True                    | Auth Dialog                   |
| 9      | NotifyType        | varchar | 50                | True                    | Notify                        |
| 10     | NotifyTarget      | varchar | 255               | True                    | Notify Target                 |
| 11     | Comments          | varchar | 255               | True                    | Comments                      |
| 12     | ActionCode        | varchar | 50                | True                    | Action                        |
| 13     | ActionLabel       | varchar | 50                | True                    | Descriptive Label             |
| 14     | TempRowOrder      | int     | 10                | True                    | Index                         |

## SUSERFLDS

The sample user fields, SUSERFLDS, table stores user defined information common to all location codes and samples. The USERFLDS table stores the default user field data for a location code, and the SUSERFLDS stores the User Field data associated with a sample. The function can handle up to 50 user defined fields

#### Primary Keys

- SAMPNO

| Sr.No. | Name       | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|------------|---------|-------------------|-------------------------|-------------|
| 1      | SAMPNO     | varchar | 7                 | False                   |             |
| 2      | MYSAMPNO   | varchar | 50                | True                    |             |
| 3      | MYUSER2    | varchar | 50                | True                    |             |
| 4      | hSec       | int     | 10                | False                   |             |
| 5      | DV_STATUS  | varchar | 50                | True                    |             |
| 6      | SAMPLER_ID | varchar | 50                | True                    |             |

## SYSMGR

System Manager Parameter listing and their values (settings).

### Primary Keys

- SYSMGROPT

| Sr.No. | Name         | Type     | Size (Characters) | Allow Null (True/False) | Description                          |
|--------|--------------|----------|-------------------|-------------------------|--------------------------------------|
| 1      | SYSMGROPT    | varchar  | 100               | False                   | System Manager Setting               |
| 2      | SYSMGRVAL    | varchar  | 100               | True                    | System Manager Setting String Value  |
| 3      | SYSMGRVAL    | int      | 10                | False                   | System Manager Setting Long Value    |
| 4      | SYSMGRBVAL   | smallint |                   | False                   | System Manager Setting Boolean Value |
| 5      | SYSFIELDTYPE | varchar  | 2                 | True                    | System Manager Setting Type          |
| 6      | hSec         | int      | 10                | False                   | Security Handle                      |

## TPHEADER

Trend Plot Group Definition

### Primary Keys

- TGRPNAME

| Sr.No. | Name        | Type    | Size (Characters) | Allow Null (True/False) | Description              |
|--------|-------------|---------|-------------------|-------------------------|--------------------------|
| 1      | TGRPNAME    | varchar | 20                | False                   | Trend Plot Group Name    |
| 2      | TGRPTITLE   | varchar | 80                | True                    | Trend Plot Group Title   |
| 3      | LAYOUT      | varchar | 4                 | True                    | Trend Plot Layout Option |
| 4      | PAGESECS    | int     | 10                | False                   | Paging Rate              |
| 5      | REFRESHMINS | int     | 10                | False                   | Data Refresh Rate        |
| 6      | hSec        | int     | 10                | False                   | Security Handle          |

## TPPLOT

Trend Plot Definition

### Primary Keys

- TGRPNAME
- PLOTPNUM

| Sr.No. | Name      | Type     | Size (Characters) | Allow Null (True/False) | Description                                 |
|--------|-----------|----------|-------------------|-------------------------|---|
| 1      | TGRPNAME  | varchar  | 20                | False                   | Trend Plot Group Name                       |
| 2      | LOCODE    | varchar  | 24                | True                    | Location Code                               |
| 3      | ACODE     | varchar  | 24                | False                   | Analysis Code                               |
| 4      | ANALYTE   | varchar  | 100               | True                    | Analyte Name                                |
| 5      | COLOR     | int      | 10                | False                   | Color Code for the Lines                    |
| 6      | YMAX      | varchar  | 14                | True                    | Maximum on Y-Axis                           |
| 7      | YMIN      | varchar  | 14                | True                    | Minimum on Y-Axis                           |
| 8      | YGRID     | varchar  | 10                | True                    | Y-Axis Increment Value                      |
| 9      | XLABELOPT | varchar  | 4                 | True                    | X-Axis Label Option Code                    |
| 10     | XSORTOPT  | varchar  | 4                 | True                    | X-Axis Sort Option Code                     |
| 11     | POINTS    | smallint |                   | False                   | Number of points to be Plotted              |
| 12     | SHOWUSPC  | smallint |                   | False                   | Option to Display Upper Specification Limit |
| 13     | SHOWUWAR  | smallint |                   | False                   | Option to Display Upper Warning Limit       |
| 14     | SHOWTARG  | smallint |                   | False                   | Option to Display Target Value              |
| 15     | SHOWLWAR  | smallint |                   | False                   | Option to Display Lower Warning Limit       |
| 16     | SHOWLSPC  | smallint |                   | False                   | Option to Display Lower Specification Limit |
| 17     | PLOTPNUM  | smallint |                   | False                   | Plot Number                                 |
| 18     | hSec      | int      | 10                | False                   | Security Handle                             |
| 19     | YLABELOPT | varchar  | 4                 | True                    | Y-Axis Label Option Code                    |

## Transition\_Location

### Primary Keys

- Object\_Name
- Transition

| Sr.No. | Name        | Type     | Size (Characters) | Allow Null (True/False) | Description |
|--------|-------------|----------|-------------------|-------------------------|-------------|
| 1      | Object_Name | nvarchar | 50                | False                   |             |
| 2      | StartState  | nvarchar | 50                | True                    |             |
| 3      | EndState    | nvarchar | 50                | True                    |             |
| 4      | Transition  | nvarchar | 50                | False                   |             |
| 5      | XLocation   | int      | 10                | True                    |             |
| 6      | YLocation   | int      | 10                | True                    |             |

## URESOURCE

Resource to Privilege mapping. Each resource will have a row entry for each of the privilege type it is associated with.

### Primary Keys

- UNNUMBER
- URTYPE
- URVALUE

| Sr.No. | Name     | Type     | Size (Characters) | Allow Null (True/False) | Description         |
|--------|----------|----------|-------------------|-------------------------|---------------------|
| 1      | UNNUMBER | int      | 10                | False                   | User ID             |
| 2      | URTYPE   | varchar  | 8                 | False                   | User Resource Type  |
| 3      | URVALUE  | varchar  | 24                | False                   | User Resource Value |
| 4      | UMODDATE | datetime |                   | True                    | Last Modified Date  |
| 5      | hSec     | int      | 10                | False                   | Security Handle     |
| 6      | URDATA   | text     | 2147483647        | True                    |                     |

## USERFLDS

Table to store User Field Names, this table must have the matching field in exactly the same sequence as in SUSERFLDS table. This table contains default values for each user field for all location codes. The function can handle up to 50 user defined fields

### Primary Keys

- LOCCODE

| Sr.No. | Name       | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|------------|---------|-------------------|-------------------------|-------------|
| 1      | LOCCODE    | varchar | 24                | False                   |             |
| 2      | MYSAMPNO   | varchar | 50                | True                    |             |
| 3      | MYUSER2    | varchar | 50                | True                    |             |
| 4      | hSec       | int     | 10                | False                   |             |
| 5      | DV_STATUS  | varchar | 50                | True                    |             |
| 6      | SAMPLER_ID | varchar | 50                | True                    |             |

## USERHEAD

LABWORKS User Table

### Primary Keys

- UNNUMBER

| Sr.No. | Name           | Type     | Size (Characters) | Allow Null (True/False) | Description          |
|--------|----------------|----------|-------------------|-------------------------|----------------------|
| 1      | UNNUMBER       | int      | 10                | False                   | User ID              |
| 2      | LASTNAME       | varchar  | 20                | False                   | User Last Name       |
| 3      | FIRSTNAME      | varchar  | 20                | True                    | User First Name      |
| 4      | TITLE          | varchar  | 8                 | True                    | User Title           |
| 5      | INITIALS       | varchar  | 12                | False                   | User Initials        |
| 6      | PASSWORD       | varchar  | 11                | False                   | User Password        |
| 7      | MODDATE        | datetime |                   | True                    | Last Modified Date   |
| 8      | hSec           | int      | 10                | False                   | Security Handle      |
| 9      | UGROUP         | varchar  | 24                | True                    | Grouping             |
| 10     | EMAIL_ADDRESS  | varchar  | 80                | True                    | Email                |
| 11     | CURRENT_STATUS | varchar  | 50                | True                    | Active/Suspended     |
| 12     | USER_SITE      | varchar  | 50                | False                   | License Site         |
| 13     | USER_CLASS     | int      | 10                | False                   | User License Type    |
| 14     | ENCRYPT_PWD    | varchar  | 40                | True                    | Hash of Password     |
| 15     | LDAPUSERID     | varchar  | 256               | True                    | LDAP User Identifier |

## VIOLATIONREORDERDETAILS

Sequential Testing Configuration. This table is used by new Violation reorder application for storing configured rules

### Primary Keys

- ID
- VIOLID

| Sr.No. | Name                 | Type     | Size (Characters) | Allow Null (True/False) | Description                |
|--------|----------------------|----------|-------------------|-------------------------|----------------------------|
| 1      | ID                   | int      | 10                | False                   | Unique ID                  |
| 2      | VIOLID               | int      | 10                | False                   | Violation Master ID        |
| 3      | FIELD                | varchar  | 15                | True                    | Field name                 |
| 4      | VALUE                | varchar  | 24                | True                    | Field Value                |
| 5      | ADDASREPLICATE       | smallint |                   | False                   | Add as a replicate setting |
| 6      | ANUM                 | smallint |                   | True                    | Analysis sequence number   |
| 7      | ONLYVIOLATEDANALYTES | smallint |                   | True                    | Violated Analytes          |

## VIOLATIONREORDERMASTER

Sequential Testing Configuration. This table is used by new Violation reorder application for storing configured rules

### Primary Keys

- ID

| Sr.No. | Name               | Type     | Size (Characters) | Allow Null (True/False) | Description                           |
|--------|--------------------|----------|-------------------|-------------------------|---------------------------------------|
| 1      | ID                 | int      | 10                | False                   | Unique ID                             |
| 2      | ANALYSISRULE NAME  | varchar  | 50                | False                   | Name of the analysis rule             |
| 3      | ACODE              | varchar  | 24                | False                   | Analysis Code                         |
| 4      | ANLNAME            | varchar  | 100               | True                    | Analyte Name                          |
| 5      | LOCCODE            | varchar  | 40                | False                   | Location Code                         |
| 6      | ANLDUEOPT          | char     | 1                 | True                    | Analysis due date calculation options |
| 7      | TRIGGEREXE         | nvarchar | 250               | True                    |                                       |
| 8      | TRIGGERARGS        | nvarchar | 2000              | True                    |                                       |
| 9      | TRIGGERONLY ONVIOL | smallint |                   | True                    |                                       |

## VIOLREORDER

Sequential Testing Configuration. This table is only used by legacy application

### Primary Keys

- ACODE
- ANLNAME
- ANUM
- LOCCODE

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description                         |
|--------|------------|----------|-------------------|-------------------------|-------------------------------------|
| 1      | ACODE      | nvarchar | 24                | False                   | Analysis Code                       |
| 2      | ANLNAME    | nvarchar | 100               | False                   | Analyte Name                        |
| 3      | ANUM       | int      | 10                | False                   | Analysis Index                      |
| 4      | LOCCODE    | nvarchar | 24                | False                   | Location Code                       |
| 5      | DUEOPT     | nvarchar | 1                 | True                    | Type                                |
| 6      | COMPLETE   | nvarchar | 24                | True                    | Acode to assign on completion       |
| 7      | VIOLCODE   | nvarchar | 24                | True                    | Acode to assign on violation        |
| 8      | TARGETCODE | nvarchar | 24                | True                    | Acode to assign on target violation |
| 9      | LSPECCODE  | nvarchar | 24                | True                    | Acode to assign on Ispec violation  |
| 10     | LWARNCODE  | nvarchar | 24                | True                    | Acode to assign on Iwarn violation  |
| 11     | UWARNCODE  | nvarchar | 24                | True                    | Acode to assign on uwarn violation  |
| 12     | USPECCODE  | nvarchar | 24                | True                    | Acode to assign on uspec violation  |
| 13     | RECALCCODE | nvarchar | 24                | True                    | Code to use as base for new         |

|  |  |  |  |  |             |
|--|--|--|--|--|-------------|
|  |  |  |  |  | calculation |
|--|--|--|--|--|-------------|

## WORKINGDAYTIME

Day of work working times

### Primary Keys

| Sr.No. | Name      | Type    | Size (Characters) | Allow Null (True/False) | Description |
|--------|-----------|---------|-------------------|-------------------------|-------------|
| 1      | DAY       | varchar | 50                | False                   | Day of week |
| 2      | STARTTIME | varchar | 50                | False                   | Start Time  |
| 3      | ENDTIME   | varchar | 50                | False                   | End Time    |

## XLCALCHEAD

Listing of EXCEL Calculation Fields as defined in EXCEL Calculation Setup program

### Primary Keys

- XLCALCCODE

| Sr.No. | Name       | Type     | Size (Characters) | Allow Null (True/False) | Description                   |
|--------|------------|----------|-------------------|-------------------------|-------------------------------|
| 1      | XLCALCCODE | varchar  | 16                | False                   | Excel Calculation Code        |
| 2      | XLCALCDESC | varchar  | 40                | True                    | Excel Calculation Description |
| 3      | XLSNAME    | varchar  | 8                 | False                   | Excel Workbook (.XLS) file    |
| 4      | WSNAME     | varchar  | 16                | True                    | Excel Worksheet Name          |
| 5      | MODUSER    | varchar  | 12                | True                    | Last Modified User            |
| 6      | MODDATE    | datetime |                   | True                    | Last Modified Date            |
| 7      | hSec       | int      | 10                | False                   | Security Handle               |
| 8      | WSMACRO    | varchar  | 50                | True                    | Excel Worksheet Macro name    |

## XLPARAMS

Listing of Calculation parameters for each calculation definition in XLCALCHEAD table, including details of cell location

### Primary Keys

- XLCALCCODE
- PARAMNUM

| Sr.No. | Name | Type | Size | Allow Null | Description |
|--------|------|------|------|------------|-------------|
|--------|------|------|------|------------|-------------|

|   |                |          | (Characters) | (True/False) |                        |
|---|----------------|----------|--------------|--------------|------------------------|
| 1 | XLCALCCODE     | varchar  | 16           | False        | Excel Calculation Code |
| 2 | PARAMNUM       | smallint |              | False        | Parameter ID           |
| 3 | PARAMTYPE      | smallint |              | False        | Parameter Type         |
| 4 | ACODE          | varchar  | 24           | False        | Analysis Code          |
| 5 | ANALYTE        | varchar  | 100          | True         | Analyte Name           |
| 6 | AITEM          | varchar  | 4            | True         | Analysis Item          |
| 7 | WSCELL         | varchar  | 6            | True         | Cell Address           |
| 8 | hSec           | int      | 10           | False        | Security Handle        |
| 9 | DATETIMEOPTION | smallint |              | False        |                        |

## Appendix: LABWORKS 7.1 Entry Relationship Diagrams

### Location Code / Analysis Definition

| <b>LOCLIST</b> |               |
|----------------|---------------|
| <b>KEY:</b>    | LOCCODE       |
|                | DESCR         |
|                | OWNER         |
|                | PROJECT       |
|                | REPNAME       |
|                | INVNAME       |
|                | USERPROG      |
|                | PRICELIST     |
|                | REPADD1       |
|                | REPADD2       |
|                | REPADD3       |
|                | REPADD4       |
|                | REPADD5       |
|                | INVADD1       |
|                | INVADD2       |
|                | INVADD3       |
|                | INVADD4       |
|                | INVADD5       |
|                | DOINV         |
|                | DOVAL         |
|                | DOSPEC        |
|                | DCOPY         |
|                | REPCOPIES     |
|                | BILLRATE      |
|                | CHOLDMINS     |
|                | RHOLDMINS     |
|                | DUEOPT        |
|                | COMTMASK      |
|                | MODDATE       |
|                | MODUSER       |
|                | hSec          |
|                | CURRENT_STATE |
|                | LREADOWNER    |
|                | LSAMPOWNER    |
|                | LATITUDE      |
|                | LONGITUDE     |
|                | ADDRESS       |
|                | LW_PROJECTID  |

| <b>LOCTESTS</b> |                 |
|-----------------|-----------------|
| <b>KEY:</b>     | LOCCODE         |
|                 | ACODE           |
|                 | CHOLDMINS       |
|                 | RHOLDMINS       |
|                 | LTESTNUM        |
|                 | hSec            |
|                 | NOOFREPLICATES  |
|                 | REPLICATEMETHOD |
|                 | AREF            |
|                 | REPSELECTION    |

| <b>USERFLDS</b> |            |
|-----------------|------------|
| <b>KEY:</b>     | LOCCODE    |
|                 | MYSAMPO    |
|                 | MYUSER2    |
|                 | hSec       |
|                 | DV_STATUS  |
|                 | SAMPLER_ID |

| <b>LABOBJCOMMENTS</b> |             |
|-----------------------|-------------|
| <b>KEY:</b>           | OBJID       |
|                       | OBJTYPE     |
| <b>KEY:</b>           | COMMENTNUMB |
|                       | COMMENTTEXT |
|                       | MODDATE     |
|                       | MODUSER     |
|                       | HSEC        |

| <b>ANALYTES</b> |                  |
|-----------------|------------------|
| <b>KEY:</b>     | ACODE            |
|                 | ANLNAME          |
|                 | ANLNUM           |
|                 | ANLABBR          |
|                 | ANLMDL           |
|                 | CASNUMB          |
|                 | ANLPQL           |
|                 | hSec             |
|                 | ANLUNIT          |
|                 | AREF             |
|                 | MODDATE          |
|                 | DEFAULTQUALIFIER |

| <b>ANL_LIST</b> |                  |
|-----------------|------------------|
| <b>KEY:</b>     | ACODE            |
|                 | ANNAME           |
|                 | AUNIT            |
|                 | AMDL             |
|                 | ADEPT            |
|                 | AREF             |
|                 | CHOLDMINS        |
|                 | RHOLDMINS        |
|                 | APRICE           |
|                 | NONREP           |
|                 | NONINV           |
|                 | SIGFIGS          |
|                 | WORKUNIT         |
|                 | COMPFLE          |
|                 | REPALL           |
|                 | ADDCOMPS         |
|                 | SIFORM           |
|                 | MODDATE          |
|                 | MODUSER          |
|                 | AOWNER           |
|                 | hSec             |
|                 | RLT_TYPE         |
|                 | RLT2_TYPE        |
|                 | QUAL_TYPE        |
|                 | CURRENT_STATE    |
|                 | ANLOWNER         |
|                 | ANLREADOWNER     |
|                 | ANLRLOWNER       |
|                 | NOOFREPLICATES   |
|                 | REPLICATEMETHOD  |
|                 | REPSELECTION     |
|                 | DEFAULTRESULT    |
|                 | RLTUNIT_TYPE     |
|                 | DEFAULTQUALIFIER |

| <b>NTTEXT</b> |          |
|---------------|----------|
| <b>KEY:</b>   | ACODE    |
|               | NTRESULT |
|               | hSec     |

**Sampe And Result Data**

| SAMPLE            |
|-------------------|
| SAMPNO            |
| OWNER             |
| SSTATUS           |
| LOCODE            |
| LOCDESCR          |
| LOGBATCH          |
| LOGUSER           |
| SUBDATE           |
| SAMPCOL           |
| COLDATE           |
| RDUEDATE          |
| DUEDATE           |
| DOVAL             |
| VALUSER           |
| VALIDATE          |
| REPNAME           |
| REPCOPIES         |
| DCOPY             |
| REPDATE           |
| REPADD1           |
| REPADD2           |
| REPADD3           |
| REPADD4           |
| REPADD5           |
| DOINV             |
| INVNAME           |
| BILLRATE          |
| PRICELIST         |
| INVDATE           |
| INVNO             |
| INVADD1           |
| INVADD2           |
| INVADD3           |
| INVADD4           |
| INVADD5           |
| PONUMBER          |
| PROJECT           |
| DOSPEC            |
| COMTMASK          |
| EXPDATE           |
| MODDATE           |
| MODUSER           |
| hSec              |
| CURRENT_STATE     |
| SREADOWNER        |
| LATITUDEREAL      |
| LONGITUDEREAL     |
| LATITUDEEXPECTED  |
| LONGITUDEEXPECTED |
| COLDUEDATE        |
| ADDRESS           |
| ADDRESSREAL       |
| IsReviewed        |
| SignUser          |
| SignDate          |
| SignReason        |
| CTReport          |
| SPRIORITY         |
| DEPARTMENT        |
| NUMBEROFLABELS    |
| PSSTATUS          |
| REQTIME           |
| COLOKTIME         |
| LABRELEASETIME    |
| PRODUCTOKTIME     |
| PARENTID          |
| PAUSED            |
| CUSTOMER          |
| SHIPTIME          |
| DISABLED          |
| OKTOCOLLECT       |
| ORIGINALTIME      |
| CREATEDATE        |
| COMPLETEDATE      |
| INITIALSTATE      |
| LW_PROJECTID      |

| ANALYSIS        |
|-----------------|
| SAMPNO          |
| ACODE           |
| ADEPT           |
| ASTATUS         |
| QBATCHED        |
| ASSIGN_ANL      |
| ASSIGN_INST     |
| RADUEDATE       |
| ADUEDATE        |
| ASDATE          |
| AEDATE          |
| APRICE          |
| ANALYST         |
| AVALUSER        |
| AVALDATE        |
| RLTSOURCE       |
| ANLLIMIT        |
| SIFORM          |
| ANUM            |
| AMODDATE        |
| AMODUSER        |
| APRICEST        |
| AOWNER          |
| hSec            |
| RLT_TYPE        |
| RLT2_TYPE       |
| QUAL_TYPE       |
| AREADOWNER      |
| SGACODE         |
| CACODE          |
| NOOFREPLICATES  |
| REPLICATEMETHOD |
| AREF            |
| REPSELECTION    |
| INSTRUMENT      |
| PREPDATE        |

| RESULT          |
|-----------------|
| SAMPNO          |
| ACODE           |
| ANALYTE         |
| RESULT          |
| RESULT2         |
| QUALIFY         |
| MDL             |
| VIOLOTYPE       |
| VIOLOVALUE      |
| VIOLDATE        |
| VIOLUSER        |
| RLTNUM          |
| RMODDATE        |
| RMODUSER        |
| DILFACTOR       |
| RAWRESULT       |
| STARTDATE       |
| ENDDATE         |
| ANALYST         |
| hSec            |
| PQL             |
| RAWMDL          |
| RAWPQL          |
| RLTUNIT         |
| RLTSOURCE       |
| RESULTPART      |
| REPLNUM         |
| RESULTCHECKSUM  |
| CHECKSUMVERSION |
| AREF            |

| SUSERFLDS  |
|------------|
| SAMPNO     |
| MYAMPNO    |
| MYUSER2    |
| hSec       |
| DV_STATUS  |
| SAMPLER_ID |

| NTRLTS          |
|-----------------|
| SAMPNO          |
| ACODE           |
| NTRESULT        |
| hSec            |
| RESULTCHECKSUM  |
| CHECKSUMVERSION |
| AREF            |
| RMODDATE        |

| LABOBJCOMMENTS |
|----------------|
| OBJID          |
| OBJTYPE        |
| COMMENTNUMB    |
| COMMENTTEXT    |
| MODDATE        |
| MODUSER        |
| HSEC           |

### Common Tables

| <b>RESULTSPECs</b> |                |
|--------------------|----------------|
| KEY                | OBJECTTYPE     |
| KEY                | OBJECTID       |
| KEY                | SPECNAME       |
| KEY                | ANALYSISISCODE |
| KEY                | ANALYTENAME    |
| KEY                | RESULTPART     |
|                    | NUMVALUE1      |
|                    | NUMVALUE2      |
|                    | TEXTVALUE      |
|                    | HSEC           |

| <b>LABOBJSPECINFO</b> |            |
|-----------------------|------------|
| KEY                   | OBJID      |
| KEY                   | OBJTYPE    |
| KEY                   | SIFLDNAME  |
| KEY                   | FORMNO     |
|                       | SIFORMNAME |
|                       | FIELDNUM   |
|                       | FLDVALUE   |
|                       | FLDPROMPT  |
|                       | MODDATE    |
|                       | MODUSER    |

| <b>LABOBJMAILLIST</b> |               |
|-----------------------|---------------|
| KEY                   | OBJID         |
| KEY                   | OBJTYPE       |
| KEY                   | MLREFERENCE   |
| KEY                   | OBJNUMB       |
|                       | DOCTYPE       |
|                       | ADDRTYPE      |
|                       | [PRIMARY]     |
|                       | ADDRESSEE     |
|                       | STREET1       |
|                       | STREET2       |
|                       | CITY          |
|                       | STATE         |
|                       | POST_CODE     |
|                       | COUNTRY       |
|                       | PHONE_NUM     |
|                       | FAX_NUM       |
|                       | EMAIL_ADDR    |
|                       | CONTACT       |
|                       | CONTACT_PHONE |
|                       | CONTACT_EMAIL |
|                       | MODUSER       |
|                       | MODDate       |
|                       | hsec          |

| <b>LABOBJOBJECTS</b> |          |
|----------------------|----------|
| KEY                  | OBJID    |
| KEY                  | OBJTYPE  |
| KEY                  | OBJNUMB  |
|                      | OBJDESCR |
|                      | OBJSPEC  |
|                      | MODDATE  |
|                      | MODUSER  |
|                      | OBJDATA  |
|                      | HSEC     |

**Process Scheduler**

| <b>PSTIMEMAIN</b>  |  |
|--|--|
|  PSID           |  |
|  PSTIME         |  |
| PSINTERVAL   |  |
|  PSINTERVALTYPE |  |
| PSSTARTTIME  |  |
| PSENDTIME  |  |
| PSENABLED  |  |
| hSec   |  |
| LW_PROJECTOVERRIDE   |  |
| LW_PROJECTID   |  |

| <b>PSTIMEHEAD</b>  |  |
|--|--|
|  PSTIMEHEADID |  |
| PSID   |  |
| PSTIME   |  |
| PSLOCODE   |  |
| PSINTERVALTYPE   |  |
| PSLOCDESCR   |  |
| PSLOCOWNER   |  |
| PSNUMBEROFLABELS   |  |
| PSPPRIORITY  |  |
| PSOWNER  |  |
| PSCOMMENT  |  |
| PSANALYSES   |  |
| PSANALYSES2  |  |
| PSEVENT  |  |
| PSCUSTOMER   |  |
| PSOKTOCOLLECT  |  |
| PSUSER1  |  |
| PSUSER2  |  |
| PSUSER3  |  |
| PSUSER4  |  |
| PSUSERNUMBER1  |  |
| PSUSERNUMBER2  |  |
| PSPRELOGBATCH  |  |
| hSec   |  |
| PSACTIVEFROM   |  |
| PSACTIVETO   |  |
| PRINTERNAME  |  |
| LABELNAME  |  |
| LW_PROJECTID   |  |

| <b>PSTIMEHEADEXTENSION</b>  |  |
|---|--|
|  PSTIMEEXTID |  |
| PSTIMEHEADID  |  |
| PSINTERVALTYPE  |  |
| PSINTERVAL  |  |
| PSANALYSES  |  |

| <b>PSpriority</b>   |  |
|---|--|
|  PSLPriority |  |
| PSPriorityABREV   |  |
| PSPriorityDESCR   |  |
| hSec  |  |

| <b>PSCONTAINER_PRELOG</b>  |  |
|--|--|
|  PSID             |  |
|  PSTIME           |  |
| PSLOCODE   |  |
| PSINTERVALTYPE   |  |
|  PSCONTAINERINDEX |  |
| PSCONTAINERNLABELS   |  |
| PSCONTAINERDESC  |  |
| PSCONTAINERANALYSES  |  |
| PSCONTAINERCOMMENT   |  |
| hSec   |  |

| <b>PSSHelfLife</b>  |  |
|---|--|
|  PSSHelfLifeID |  |
| PSSAMPLEID  |  |
| PSSAMPNO  |  |
| PSID  |  |
| PSSHelfLife_OFFSET  |  |
| PSANALYSES  |  |
| PSCOMMENT   |  |
| PSMASTERTEMPLATE  |  |
| PSMASTERID  |  |

| <b>PSCONTAINER</b>   |  |
|--|--|
| PSSAMPLEID   |  |
| PSCONTAINERINDEX   |  |
| PSCONTAINERNLABELS   |  |
| PSCONTAINERDESC  |  |
| PSCONTAINERANALYSES  |  |
| PSCONTAINERCOMMENT   |  |
| hSec   |  |
| PSSAMPNO   |  |
|  ID |  |

## LABWORKS Built-In Calculation

## LABWORKS Excel Calculation

## Project Analyte Management

| <b>CALCDEFS</b> |                |
|-----------------|----------------|
| 🔑               | ACODE          |
|                 | KEYTEST        |
|                 | CALCMDL        |
|                 | NNOPTION       |
|                 | INVAR1         |
|                 | INVAR2         |
|                 | INVAR3         |
|                 | INVAR4         |
|                 | INVAR5         |
|                 | INVAR6         |
|                 | INVAR7         |
|                 | INVAR8         |
|                 | INVAR9         |
|                 | INVAR10        |
|                 | CFUNCT         |
|                 | MODDATE        |
|                 | MODUSER        |
|                 | hSec           |
|                 | DATETIMEOPTION |

| <b>XLCALCHEAD</b> |            |
|-------------------|------------|
| 🔑                 | XLCALCCODE |
|                   | XLCALCDESC |
|                   | XLSNAME    |
|                   | WSNAME     |
|                   | MODUSER    |
|                   | MODDATE    |
|                   | hSec       |
|                   | WSMACRO    |

| <b>RLDEFHED</b> |         |
|-----------------|---------|
| 🔑               | RLGROUP |
|                 | RLDESCR |
|                 | MODDATE |
|                 | MODUSER |
|                 | hSec    |

| <b>RLSMPHED</b> |         |
|-----------------|---------|
| 🔑               | SAMPNO  |
|                 | RLGROUP |
|                 | RLDESCR |
|                 | MODDATE |
|                 | MODUSER |
|                 | hSec    |

| <b>RLSMPANL</b> |             |
|-----------------|-------------|
| 🔑               | SAMPNO      |
| 🔑               | ACODE       |
| 🔑               | ANALYTE     |
|                 | REPLIMIT    |
|                 | LTRLRESULT  |
|                 | LTRLQUAL    |
|                 | GTRLQUAL    |
|                 | LTMDLRESULT |
|                 | LTMDLQUAL   |
|                 | ANLNUM      |
|                 | hSec        |

| <b>CALCPARAMS</b> |             |
|-------------------|-------------|
| 🔑                 | ACODE       |
|                   | INVAR       |
| 🔑                 | INVAR_INDEX |

**Analysis Qualification - Personal**

| <b>ANALYSTS</b>  |  |
|--|--|
|  INITIALS |  |
| FULLNAME   |  |
| STATUS   |  |
| EmpDate  |  |
| EmpType  |  |
| Other  |  |
| hSec   |  |
| TEAMNAME   |  |
| COMMENTTEXT  |  |

| <b>ANLTESTS</b>  |  |
|--|--|
|  INITIALS |  |
|  ACODE    |  |
| EXPDATE  |  |
| SOP  |  |
| hSec   |  |

| <b>PTExperience</b>   |  |
|---|--|
|  Initials  |  |
|  Lab       |  |
|  StartDate |  |
| EndDate   |  |
| Position  |  |
| Experience  |  |
| hSec  |  |

| <b>PTTraining</b>  |  |
|--|--|
|  Initials     |  |
|  SchoolType   |  |
|  DateAttended |  |
| DateEnded  |  |
| SchoolName   |  |
| hSec   |  |
| SchoolDesc   |  |

| <b>ANALYST_TEAM</b>  |  |
|--|--|
|  INITIALS |  |
|  TEAMNAME |  |

| <b>PTLicense</b>   |  |
|--|--|
|  Initials |  |
|  License  |  |
|  Granted  |  |
| Expire   |  |
| LicenseNo  |  |
| hSec   |  |

| <b>PTSchools</b>   |  |
|--|--|
|  SchoolType |  |
| SchoolDesc   |  |
| hSec   |  |

**Instrument Qualification - Maintenance**

| <b>INSTLIST</b>  |  |
|--|--|
|  INSTCODE |  |
| INSTNAME   |  |
| INSTSTATUS   |  |
| Manufacturer   |  |
| Installed  |  |
| Serial_No  |  |
| hSec   |  |
| INSTLOCATION   |  |
| INST_PROGRAM   |  |
| INSTTYPE   |  |
| SOFTWARE_VERSION   |  |
| USE_SCHUMAKER  |  |
| COMMENTTEXT  |  |

| <b>INSTTESTS</b>   |  |
|--|--|
|  INSTCODE |  |
|  ACODE    |  |
| EXPDATE  |  |
| hSec   |  |

| <b>IMCINSTMAINT</b>  |  |
|--|--|
|  INSTCODE   |  |
|  MAINTDATE  |  |
| INSTDESC   |  |
| DONEBY   |  |
|  TYPEOFWORK |  |
| PONUMBER   |  |
| COST   |  |
| DOWNTIME   |  |
| DOWNFROM   |  |
| DOWNTO   |  |
| COMPLETED  |  |
| SCHEDULEDATE   |  |
| hSec   |  |
| MAINT_EMAIL_WARN_DATETIME  |  |

| <b>IMCINSTCALI</b>   |  |
|--|--|
|  InstCode |  |
|  CaliDate |  |
| CaliUser   |  |
|  SampNo   |  |
| WorkDone   |  |
| Completed  |  |
| hSec   |  |
| CALIB_EMAIL_WARN_DATETIME  |  |

| <b>IMCPROCS</b>  |  |
|--|--|
|  INSTCODE |  |
|  PROCTYPE |  |
| PROCTEXT   |  |
| hSec   |  |

**QA-QC Templates and Samples**

| <b>BATCHHEAD</b>  |  |
|---|--|
|  BATCHID |  |
| BATCHDESCR  |  |
| TEMPLATENAME  |  |
| WORKFLOW  |  |
| ASSIGNANALYST   |  |
| ASSIGNINSTR   |  |
| CURRENT_STATE   |  |
| MODUSER   |  |
| MODDATE   |  |
| CREATEDBY   |  |
| CREATEDATE  |  |
| eWorksheetId  |  |
| PREPDATE  |  |

| <b>BATCHTEMPLATE</b>  |  |
|---|--|
|  BATCHID |  |
| TEMPLATE  |  |

| <b>BATHEAD</b>  |  |
|---|--|
|  BATNAME |  |
| BATNUMB   |  |
| BATTEST   |  |
| BATDATE   |  |
| BATUSER   |  |
| QASAMP  |  |
| hSec  |  |

| <b>BATCHSAMPS</b>   |  |
|---|--|
|  BATCH_NAME  |  |
|  BATCH_INDEX |  |
| BATCH_SAMPNO  |  |
| BATCH_ANALYSES  |  |
| BATCH_SAMPTYPE  |  |
| hSec  |  |
| BATCH_SUBBATCH  |  |

| <b>BATSAMPS</b>   |  |
|---|--|
|  BATNAME |  |
|  BSAMPNO |  |
| hSec  |  |

| <b>BATCHITEMSTOCKS</b>   |  |
|--|--|
|  ID |  |
| BatchName  |  |
| ItemStockID  |  |
| Quantity   |  |

## Persisted Groups

| GROUPHEADER   |  |
|---|--|
|  GRPID |  |
| GRPTYPE   |  |
| TITLE   |  |
| CREATEDATE  |  |
| CREATEDBY   |  |
| CURRENT_STATE   |  |
| MODUSER   |  |
| MODDATE   |  |

| GROUPPARAMS   |  |
|---|--|
|  GRPID     |  |
|  PARAMNAME |  |
| PARAMNUMB   |  |
| PARAMVALUE  |  |
| TYPE  |  |
| PICKLIST  |  |

| GROUPSIPROMPTS   |  |
|--|--|
|  GRPID      |  |
|  PROMPTNO |  |
| SIPROMPT   |  |
| SIFORM   |  |

| GROUPMEMBERS   |  |
|--|--|
| MEMBNUM  |  |
|  GRPID    |  |
|  MEMBTYPE |  |
|  MEMBID   |  |